page 1/6

BASIX Certificate

Building Sustainability Index www.basix.nsw.gov.au

Alterations and Additions

Certificate number: A460586

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Alterations and Additions Definitions" dated 06/10/2017 published by the Department. This document is available at www.basix.nsw.gov.au

Secretarv Date of issue: Tuesday, 24, May 2022 To be valid, this certificate must be lodged within 3 months of the date of issue.



Planning, Industry & Environment

Project address	
Project name	2142 WHALE BEACH
Street address	94 Whale Beach Road whale beach 2107
Local Government Area	Northern Beaches Council
Plan type and number	Deposited Plan 10782
Lot number	72
Section number	
Project type	
i lojeci iype	
Dwelling type	Separate dwelling house

Certificate Prepared by (please complete before submitting to Council or PCA)

Name / Company Name: MM+J Architects

ABN (if applicable): 79153579867

Fixtures and systems	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Lighting			
The applicant must ensure a minimum of 40% of new or altered light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting-diode (LED) lamps.		~	~
Fixtures			
The applicant must ensure new or altered showerheads have a flow rate no greater than 9 litres per minute or a 3 star water rating.		\checkmark	~
The applicant must ensure new or altered toilets have a flow rate no greater than 4 litres per average flush or a minimum 3 star water rating.		\checkmark	~
The applicant must ensure new or altered taps have a flow rate no greater than 9 litres per minute or minimum 3 star water rating.		\checkmark	

Construction	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check		
Insulation requirements					
The applicant must construct the new or altered the table below, except that a) additional insular is not required for parts of altered construction	~	~	~		
Construction	Additional insulation required (R-value)	Other specifications			
concrete slab on ground floor.	nil				
suspended floor with open subfloor: framed (R0.7).	R0.8 (down) (or R1.50 including construction)				
suspended floor with enclosed subfloor: framed (R0.7).	R0.60 (down) (or R1.30 including construction)				
external wall: cavity brick	nil				
external wall: concrete block/plasterboard	R1.18 (or R1.70 including construction)				
flat ceiling, flat roof: framed	ceiling: R0.90 (up), roof: foil backed blanket (75 mm)	light (solar absorptance < 0.475)			

Glazing r	equirements	5					Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Windows	and glazed	doors						I	1
	The applicant must install the windows, glazed doors and shading devices, in accordance with the specifications listed in the table below. Relevant overshadowing specifications must be satisfied for each window and glazed door.						~	 	~
The followi	ng requiremen	nts must also	o be satisf	ied in relatior	n to each window and glaz	ed door:		\checkmark	\checkmark
have a U-va must be ca	alue and a So	lar Heat Gai cordance wit	in Coefficiona the Nationa	ent (SHGC) r I Fenestratio	no greater than that listed in Rating Council (NFRC) o	ar or toned glass may either match the description, or, in the table below. Total system U-values and SHGCs conditions.		~	~
	loor Orientati		· · · ·	<u> </u>	Shading device	Frame and glass type			
no.		glass inc. frame (m2)	Height (m)	Distance (m)					
W1	SW	1.22	0	0	none	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
W2	SW	1.34	0	0	none	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
W3	SW	1.34	0	0	none	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
DR01	SE	4.12	0	0	none	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
DR02	SE	3.42	0	0	none	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
DR03	SE	3.78	0	0	none	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
DR04	SE	2.07	0	0	none	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
DR05	SE	2.06	0	0	none	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
DR09	SE	1.89	0	0	none	standard aluminium, single clear, (or			

Glazing requirements								Show on CC/CDC Plans & specs	Certifier Check
Window / door no.	Orientation	Area of glass inc. frame (m2)	Oversha Height (m)	dowing Distance (m)	Shading device	Frame and glass type			
						U-value: 7.63, SHGC: 0.75)			
DR11	SW	9.88	0	0	none	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
DR12	SW	9.88	0	0	none	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
DR13	SW	3.15	0	0	none	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a " / " in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a "
"
"
"
"
"
"
"
"
"
"
"
"
Show on CC/CDC plans & specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a " / " in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate for the development may be issued.