

11/02/13

Pittwater Council
PO Box 882
Mona Vale NSW 2103

Dear Sir or Madam

¥

RE:

Lodgement of CC 2012-253 for DA No. N0090/12

Site address:

No. 21 Wallumatta Road, Newport NSW 2106

Please find attached all required documentation relied upon to issue Construction Certificate and Notice of Commencement for the above development:

- Part 4A Lodgement Fee \$36.00 payable to Council
- Copy of Home Owners Warranty Insurance
- Sydney Water approval
- 1 full set of Council approved plans/Construction Certificate plans
- 1 Structural Engineers plans & certificate of adequacy

· ·

- 1 Geotechnical Form 2A & 2B
- 1 Schedule of finishes
- 1 Basix certificate

Yours faith folly

Craig Formosa

RECEIVED
1 3 FEB 2013
PITTWATER COUNCIL





CONSTRUCTION CERTIFICATE

Approved 11/02/13

Issued in accordance with the provisions of the Environmental & Assessment Act 1979 under Sections 109C(1)(b) and 109F

Date Application Received	23/11/12					
Council	Pittwater					
Development Consent No.	N0090/12	Date Approved		06.07.12		
Certifying Authority	Craig Formosa	Accredited Certifier		Craig Forn	nosa -	BPB012
Accreditation Body	Building Professionals Board	BCA In Force		BCA2012		
APPLICANT DETAILS						
Name F	Glenda Hanks		Ph No.	0433 8005	22	
Address	21 Wallumatta Road, Newport NS					
OWNER DETAILS .						
Name	Glenda Hanks					
Address	21 Wallumatta Road, Newport NS	W 2106				
DEVELOPMENT DETAILS :						
Subject Land	21 Wallumatta Road, Newport NS	SW 2106	Lot No.	8	DP	8184
Description of Development	Alterations & additions to the exist	ting dwelling including s	wimming	pool.		
Class of Building	1a, 10a, 10b	Value of Work		\$224,400.0	00	
BUILDER DETAILS		ra vita i vije i i i i i i i i i i i i i i i i i i	on conservable.		va (segu) Rijani Rijani	
Name	Planbuilt Pty Ltd					
Address	33 Argyle Street, Bilgola NSW 21	07				
Contact Number ·	0459 408 881	License No.		227143C		
APPROVED PLANS & DOCU	JMENTS		o oprajeniostanti. Komen en egopolis	séperand Forum Sincial de la Calada	nigenony night in Nix 1,0 in	nya sam oddistor
Plans Prepared By	Anna Henry – AH Design	-				
Drawing Numbers	A-935 sheets 1 of 2, 2 of 2		Dated	11.10		
Engineer Details Prepared By	Mario F Benitez - VDM	Manfred Hausmann	- Geotect	nical Engine	er - V	OM .
Drawing Numbers	SD1201-002 1/3 - 3/3, 4/4, Form	2A & B	Dated	08.12, 07/0	02/13	
Basix Certificate No.	A945596		Dated	30.11.10		

CERTIFICATION

- I, Craig Formosa, as the certifying authority am satisfied that;
 - (a) The requirements of the regulations referred to in s81A (5) have been complied with. That is, work completed in accordance with the documentation accompanying the application for this certificate (with such modifications verified by the certifying authority as may be shown on that documentation) will comply with the requirements of the Regulation as referred to in section 81A (5) of the Act, and
 - (b) Long Service Levy has been paid where required under s34 of the Building & Construction Industry Long Service Payments Act 1986.

Signed:

Date: 11/02/13

GEOTECHNICAL RISK MANAGEMENT POLICY FOR PITTWATER FORM NO. 2 - PART A - To be submitted with detailed design for Construction Certificate

Development Application for Ms Glenda Hanks Name of Applicant

Address of site 21 Wallumatta Rd, Newport, NSW, 2106

PART A: Declaration made by Structural or Civil Engineer in relation to the incorporation of the Geotechnical issues into the project design

1, Mario F Benitez on behalf of VDM Consulting Engineers Pty Ltd

(trading or company name)

on this the Thursday, 7 February 2013

(date)

certify that I am a Structural er Civil Engineer as defined by the Geotechnical Risk Management Policy for Pittwater - 2009. I am authorised by the above organisation/company to issue this document and to certify that the organisation/company has a current professional indemnity policy of at least \$2million. I also certify that I have prepared the below listed structural documents in accordance with the recommendations given in the Geotechnical Report for the above development and that

Please mark appropriate box

 \square

the structural design meets the recommendations as set out in the Geotechnical Report or any revision thereto. the structural design has considered the requirements set out in the Geotechnical Report for Excavation and Landfill both for the excavation/construction phase and the final installation in accordance with Clause 3.2 (b)(iv) of the Geotechnical Risk Management Policy.

Geotechnical Report Details:

Report for Glenda Hanks - Geotechnical Assessment (According to Pittwater Council 2009)

Report Date: 8th March 2012 Author: Dr. Manfred Hausmann

Author's Company/Organization: VDM Consulting Engineers P/L

Structural - Construction Notes, Plan Views, Sections & Details pages 1 to 5

Swimming Pool -Structural - Construction Notes, Plan Views, Sections & Details pages 1 to 1

I am also aware that Pittwater Council relies on the processes covered by the Geotechnical Risk Management Policy, including this certification as the basis for ensuring that the geotechnical risk management aspects of the proposed development have been adequately addressed to achieve an "Acceptable Risk Management" level for the life of the structure taken as at least 100 years unless otherwise stated and instituted. and justified.

THIS PLAN / DOCUMENT FORMS PART OF FORM BUILDING CERTIFIERS CC / CDC

Signature

Name Mario F Benitez

Chartered Professional Status CPEng, MIEAust, IPENZ

Membership No. 418917, 111943

Company VDM Consulting Engineers P/L

GEOTECHNICAL RISK MANAGEMENT POLICY FOR PITTWATER FORM NO. 2 - PART B - To be submitted with detailed design for Construction Certificate

PART B Declaration made by Geotechnical Engineer or Engineering Geologist and/or Coastal Engineer (where applicable) in relation to the incorporation of the Geotechnical issues into the project design

I, Dr Manfred Hausmann on behalf of VDM Consulting Engineers Pty Ltd (insert name) (trading or company name)

on this the Thursday, 7 February 2013 (date)

certify that I am a Geotechnical Engineer or Engineering Geologist and/or Coastal Engineer as defined by the Geotechnical Risk Management Policy for Pittwater - 2099 and I am authorised by the above organisation/company to issue this document and to certify that the organisation/company has a current professional indemnity policy of at least \$2million. I also certify that I have reviewed the design plans and structural design plans for the Construction Certificate Stage and that I am satisfied that:

Please mark appropriate box

the structural design meets the recommendations as set out in the Geotechnical Report or any revision thereto. the structural design has considered the requirements set out in the Geotechnical Report for Excavation and Landfill both for the excavation/construction phase and the final installation in accordance with Clause 3.2 (b)(iv) of the Geotechnical Risk Management Policy.

Geotechnical Report Details:

Report Title: Glenda Hanks - Geotechnical Assessment (According to Pittwater Council 2009) Report Date: 8th March 2012 Author: Dr. Manfred Hausmann

Documentation which relates to or is relied upon in report preparation:

Architectural - AHDesign - pages A1 to A2 project #935-21

Structural - Construction Notes, Plan Views, Sections & Details pages 1 to 3

Swimming Pool -Structural - Construction Notes, Plan Views, Sections & Details pages 1 to 1

I am also aware that Pittwater Council relies on the processes covered by the Geotechnical Risk Management Policy, including this certification as the basis for ensuring that the geotechnical risk management aspects of the proposed development have been adequately addressed to achieve an "Acceptable Risk Management" level for the life of the structure taken as at least 100 years unless otherwise stated and justified.

mhausmann

Name Dr. Manfred Hausmann

Chartered Professional Status - CPE MIEAust

Membership No 339258

Company VDM Consulting Engineers P/L

THIS PLAN / DOCUMENT FORMS PART OF FORM BUILDING CERTIFIERS CC / CDC



calliden

NSWBIBHWI/145157-PermitAuthority

25/01/2013

Planbuilt Pty Ltd 33 Argyle Street BILGOLA NSW 2107 Calliden Insurance Ltd
ABN 47 004 125 268 AFS Licence 234438
Level 9, 11-33 Exhibition Street
MELBOURNE VIC 3000
Phone: (03) 9637 1300 FAX: 1300 662 215

Certificate of Insurance RESIDENTIAL BUILDING WORK BY CONTRACTORS

A contract of insurance complying with sections 92 and 96A of the <u>Home Building Act 1989</u> has been issued by **Calliden Insurance Limited** (ABN 47 004 125 268) (AFSL 234438) as agent for and on behalf of the NSW Self Insurance
Corporation (SICorp) (ABN 97 369 689 650) who is responsible for management of the Home Warranty Insurance Fund.

In respect of:

Structural Alterations/Additions

At:

21 Wallumatta Road

NEWPORT NSW 2106

Carried out by:

Planbuilt Pty Ltd

Licence Number:

227143C

ABN:

142896544

For:

Adam & Glenda Hanks

In the amount of:

\$224,400.00

Subject to the Act and the <u>Home Building Regulation 2004</u> and the conditions of the insurance contract, cover will be provided to:

- a beneficiary described in the contract and successors in title to the beneficiary,

ΛR

- the immediate successor in title to the contractor or developer who did the work and subsequent successors in title.

Authorisation: Signed by Calliden Insurance Ltd (ABN 47 004 125 268) (AFSL 234438) as agent for and on behalf of the NSW Self Insurance Corporation (SICorp) (ABN 97 369 689 650)

Issued on the 25th day of January, 2013.

NOTICE: To download a copy of your insurance policy wording visit http://www.policywording.com.au,

THIS PLAN / DOCUMENT FORMS

PART OF FORM BUILDING

CERTIFIERS CO / CDC

Page 1 of 1



VDM Consulting Engineers Pty Ltd ABN 40 101 544 763 94 Bassett Street Mona Vale, NSW, 2103 T: (02) 9999 4285 F: (02) 9999 0193 E:vdm1@optusnet.com.au

CERTIFICATE OF ADEQUACY

Re: 21 WAELUMATTA RD.

NEWPORT, NSW, 2106

Project Nº: SD1101-002

Reference: 120112-A

Date: 4 February 2013



1. Aim

To assess the structural integrity and stability of the existing dwelling and to ensure that the proposed additions and alterations to 21 Wallumatta Rd, Newport can be carry out without causing structura damages.

2. Introduction

The existing residence is a two storeys / split level dwelling consisting of a Lower Ground Floor brick veneer external walls with single timber stud internal walls and Ground Floor timber framed and weatherboard clad founded on brick piers on concrete footings for the main building and timber posts on mass and reinforced concrete for the external decks.

The alterations encompass mainly internal changes to the Lower and Ground Floors. In addition a new swimming pool will be built on the existing South Deck.

VDM Consulting Engineers Pty Ltd (VDM) inspected the dwelling on 15th February 2012 taken photographic records and geometrical measurements. The inspection (by VDM) focused mainly on sections of the existing residence where additions and alterations have been built as well as future plans.

Calculations and analyses were carry-out in order to ascertain the capability of the existing footings and structural components and to maintain its integrity, stability and adequate load-bearing capacity as determined by:

- AS/NZS 1170.0:2002: Structural design actions General principles,
- AS/NZS 1170.1:2002: Structural design actions Permanent, imposed and other actions
- AS/NZS 1170.1:2002: Structural design actions Wind actions,
- AS 1720:2010: Timber structures Part 1- design methods,
- AS 3600:2001: Concrete Structures Codes,
- AS 3700:2001: Masonry structures,
- AS 4100:1998: Steel structures,
- Building Code of Australia (BCA),
- Pittwater Council consent conditions,
- Principles of structural mechanics.

Loads used for the analysis included:

- Dead load (DL) 0.70kPa (69 kg/m²) self weight
- Live load (LL) 3.0kPa (294 kg/m²) (Deck / Balcony)
- Live load (LL) 1.5kPa (147 kg/m²) elsewhere
- Concrete self weight (sw) 25 kN/m³ (2,453 kg/ m³) includes steel reinforcement
- Steel $f_s = 300$ MPa
- Concrete $-f'_c = 25$ MPa

Serviceability factors:

- Short term $\psi_s = 0.7$
- Long term $\psi_l = 0.4$

Strength factors

- Dead load 1.2
- Live load 1.5

4/02/2013 3:03 PM

3. Conclusions	VI		M
The structural condition of the existing dwelling footings and structural elements generally found to be satisfactory. Based on the analyses results and the visual insperior opinion that the existing structure shall resist the proposed loads.	inspe etion	ected 1 it i	was s our
This analysis has been based on loads applied on areas inspected and mentioned in the any attempt to place these loads elsewhere shall required further analysis to ensure the structure is maintain.	is re integ	port rity (only of the
This certificate shall not construe as relicving any other party of their resliabilities, or contractual obligations.	pon	sibili	ities,
•			
Mario F. Benítez, (B.E.(Structural)), CPEng., MIEAust. (418917) MIPENZ Senior Structural Erigineer			
·			***************************************
		30.400000000000000000000000000000000000	

•			
•			200000000000000000000000000000000000000
· .			
•			

BASI Certificat

Building Sustainability Index www basix nsw gov au

Alterations and Additions

Certificate number A94596

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability if it is built in accordance with the commitments set out below. Terms used in this certificate or in the commitments have the meaning given by the document entitled. BASIX Alterations and Additions. Definitions, dated 29/9/2006 published by Department of Planning. This document is available at www.basix.naw.gov.au.

Director General Date of Issue Tussday 30 November 2010

NSW | Planning

My renovation work is valued at \$50,000 or more, and	Type of atteration and addition
Separate dwelling house	Dwelling type
	rojectiyoo ka ka
	Section number
	Lot number
Deposited Plan 8184	Plan type and number
Pithwater Council	Local Government Area
21 Wallumatta Road Newport 2106	Street address
Walturnatta	Project name

Description of project

THIS PLAN / DOCUMENT FORMS

PART OF FORM BUILDING

CERTIFIERS CC / CDC

page 1 / 🕇

inwater tank applicant must install a rainwater tank of at least 2100 litres on the site. This rainwater tank must meet and be installed in accordance. a applicant must configure the rainwater tank to collect rainwater runoff from at least 78 square metres of roof area. a applicant must connect the rainwater tank to a tap located within 10 metres of the pool. Iddoor swimming pool must be outdoors. a swimming pool must not have a capacity greater than 50 kilchities. a applicant must install a pool pump biner for the swimming pool.	ainwaler tank ainwaler tank he applicant must install a rainwaler tank of at least 2100 tires on the site. This rainwater tank must meet and be installed in accordance with the requirements of all applicable regulatory authorities. he applicant must configure the rainwater tank to collect rainwater runoff from at least 78 square metres of roof area. he applicant must connect the rainwater tank to a tap located within 10 metres of the edge of the pool utdoor swimming pool. he swimming pool must be outdoors. he swimming pool must not have a capacity greater than 50 kilobities. he applicand must install a pool pump bmer for the swimming pool.	<u> </u>	ζ,		The applicant must not incorporate any heating system for the swimming gool that is part of this development
Inwater tank applicant must install a reinwater tank of at least 2100 lifes on the site. This reinwater tank must meet and be installed in accordance. The applicant must configure the reinwater tank to collect reinwater runoff from at least 78 square metres of roof area. The applicant must connect the rainwater tank to a tap located within 10 metres of the edge of the pool. Iddoor swimming pool must be outdoors. The swimming pool must not have a capacity greater than 50 kilokitres.		۲,	د 		The applicant must install a pool pump bmer for the swimming pool
Inwater tank applicant must install a rainwater tank of at least 2100 lifes on the site. This rainwater tank must meet and be installed in accordance. In the requirements of all applicable regulatory authorities, applicant must configure the rainwater fank to collect rainwater runoff from at least 78 square metres of roof area. applicant must connect the rainwater tank to a tap located within 10 metres of the edge of the pool idoor switting pool. This rainwater tank must meet and be installed in accordance. A configuration of the rainwater tank to a tap located within 10 metres of the edge of the pool. Idoor switting pool must be outdoors.	ainwater tank he applicant must install a rainwater tank of at least 2100 lifres on the site. This rainwater tank must meet and be installed in accordance. Specially the requirements of all applicable regulatory authorities. he applicant must configure the rainwater tank to collect rainwater runoff from at least 78 square metres of roof area. The applicant must connect the rainwater tank to a tap located within 10 metres of the edge of the pool. utdoor swimming pool. **This rainwater tank must meet and be installed in accordance. The pool of the applicant must connect the rainwater tank to a tap located within 10 metres of the edge of the pool.	<	~ —-	<u> </u>	he swimming pool must not have a capacity greater than 50 kitokires
Inwater tank applicant must install a rainwater tank of at least 2100 liftes on the site. This rainwater tank must meet and be installed in accordance. The requirements of all applicable regulatory authorities applicant must configure the rainwater tank to collect rainwater runoff from at least 78 square metres of roof area. The applicant must connect the rainwater tank to a tap located within 10 metres of the edge of the pool. The pool of the pool of the pool.	Annwater tank annwater tank be applicant must install a reinwater tank of at least 2100 tires on the site. This reinwater tank must meet and be installed in accordance with the requirements of all applicable regulatory authorities. The applicant must configure the rainwater tank to collect rainwater runoff from at least 78 square metres of roof area. The applicant must connect the rainwater tank to a tap located within 10 metres of the edge of the pool. The applicant must connect the rainwater tank to a tap located within 10 metres of the edge of the pool.	< !	< !	< !	
Inwater tank applicant must install a rainwater tank of at least 2100 lifes on the site. This rainwater tank must meet, and be installed in accordance. The requirements of all applicable regulatory authorities applicant must configure the rainwater tank to collect rainwater runoff from at least 78 square metres of roof area. The applicant must connect the rainwater tank to a tap located within 10 metres of the edge of the pool.	Allow on Show on Certific DAPais OAPais OAPais Coropc Check the applicant must install a rainwaler tank of at least 2100 lifes on the site. This rainwater tank must meet and be installed in accordance the rainwater tank to collect rainwater runoff from at least 78 square metres of roof area. The applicant must connect the rainwater tank to a tap located within 10 metres of the pool.				;
inwater tank applicant must install a rainwater tank of at least 2100 litres on the site. This rainwater tank must meet, and be installed in accordance. The requirements of all applicable regulatory authorities applicant must configure the rainwater tank to collect rainwater runoff from at least 78 square metres of roof area.	DAPlais COCCD Check annwater tank the applicant must install a rainwater tank of at least 2100 lifres on the site. This rainwater tank must meet and be installed in accordance with the requirements of all applicable regulatory authorities. The applicant must configure the rainwater tank to collect rainwater runoff from at least 78 square metres of roof area.	<	\		he applicant must connect the rainwater tank to a tap located within 10 metres of the edge of the pool
Inwater tank applicant must install a rainwater tank of at least 2100 liftes on the site. This rainwater tank must meet, and be installed in accordance. The requirements of all applicable regulatory authorities.	DAPlais CC/CDC Check anwater tank the applicant must install a rainwater tank of at least 2100 liftes on the site. This rainwater tank must meet and be installed in accordance.	۲,	<u>`</u>		he applicant must configure the rannwater tank to collect rainwater runoff from at least 78 square metres of roof area
nwatertank		<	<u> </u>	<	he applicant must install a rainwater tank of at least 2100 liftes on the site. This rainwater tank must meet, and be installed in accordance with the requirements of all applicable regulatory authorities.
				•	kanwater tank
		Check	Shewor.	O'A'Plans	

The applicant must ensure new or altered taps have a flow rate no greater than 9 likres per minute or minimum 3 star water rating	The applicant must ensure new or aftered toilets have a flow rate no greater than 4 litres per average flush or a minimum 3 star water rating	The applicant must ensure new or altered showerheads have a flow rate no greater than 9 litres per minute or a 3 star water rating	Fixtures	The applicant must ensure a minimum of 40% of new or altered light fixtures are fitted with fluorescent, compact fluorescent, or light emitting-chode (LED) lamps	Lighting	Extures and systems DAF1an
\ .< 	ζ	ر ا ا		4 m		Show on, Scottoc
	<	۲		۲		Certifier? Check

raked ceiling pitched/skillion roof framed	external walt framed (weatherboard fibro	suspended floor with open subfloor framed (R0 7)	Construction	The applicant must construct the new or aftered construction (floor(s) walls a the table below except that a) additional insulation is not required where the a is not required for parts of allered construction where insulation already exists	Insulation requirements	Construction
ceiling R1 74 (up) roof foil backed blanket — medium (solar absorptance 0 475 - 0 70) (75 mm)	R1 30 (ar R1 70 including construction)	R0 8 (down) (or R1 50 including construction)	ion Additional insulation regioned (Rivature) (Ciner specifications	The applicant must construct the new or aftered construction (floor(s), walfs, and ceilings/roofs) in accordance with the specifications tisted in the table below, except that a) additional insulation is not required where the area of new construction is less than 2m2, b) insulation specified is not required for parts of allered construction where insulation already exists.		
				\		Show on DA Plans
	, <u> </u>			· · · · ·		Show on College
				۲,	-	C-arthur C-arthur

			W3 N 126 0 0 awning (adjustable) >=900 mm improved aluminium single clear (U-value
			W2 N 27 0 0 projection/height above sill ratio improved aluminium single clear (U value 544 SHGC 0.75)
			;
			(m)
			Windows and glazed doors glazing requirements Window Orientation Aries of Overstadowing Sheding device. Frame and glass type (doors Control Control
<u> </u>	<u>`</u>	<u>ر</u> 	
<u> </u>	<		Pergolas with fixed battens must have battens parallel to the window or glazed door above which they are situated unless the pergola also shades a perpendicular window. The spacing between battens must not be more than 50 mm.
<u> </u>	۲,		Pergolas with polycarbonate roof or similar translucent material must have a shading coefficient of less than 0.35
۲	<	4	For projections described as a ratio the ratio of the projection from the wall to the height above the window or glazed door still must be at least that shown in the table below
۲	<	<u> </u>	For projections described in milimetres, the leading edge of each eave, pergola, verandah, balcony or awning must be no more than 500 mm. I above the head of the window or glazed door and no more than 2400 mm above the sill.
<u> </u>	\	······································	Each window or glazed door with improved frames or pytolylic low eiglass or clear/air gap/clear glazing or toned/air gap/clear glazing must have a U-value and a Solar Heat Gain Coefficient (SHGC) no greater than that listed in the table below. Total system U-values and SHGCs must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions. The description is provided for information only. Alternative systems with complying U-value and SHGC may be substituted.
۲	ζ,		The following requirements must also be satisfied in relation to each window and glazed door
<	~	~	The applicant must install the windows, glazed doors and shading devices, in accordance with the specifications listed in the table below. Relevant overshadowing specifications must be satisfied for each window and glazed door.
	Specis:		Windows and glazed doors
Orack.	Show on .	Show on DA Plans	Glazing requirements

Skylights glazing requirements Skylights glazing requirements Simplify the control of the cont	Each skylight may either match the description or have a U value and a Solar Heat Gain Coefficient (SHGC) no greater than that listed in the table below	Skylights. The applicant must install the skylights in accordance with the specifications listed in the table below.	W6 S i8 64 0 0 eave/verandah/pergola/balcony improved aluminium single clear (U-value >=900 mm 6 44 SHGC 0 75)	W5 E 126 13 38 none improved aluminium single clear (U-value 5 44 SHGC 0 75)	W4 E 18 13 38 none improved aluminium single clear (U-value 6 44 SHGC 0 75)	And the state of t	
	· · ·	\ \					

Commitments identified with development may be issued	Commitments identified with a "\square in the "Show on CC/CDC plans & specs" certificate / complying development certificate for the proposed development	Commitments identified with a 💸 in the Show on DA plans column a development application is to be lodged for the proposed development)	In these commitments applicant means the person carrying out the development	
elop Time i	<u>r</u>	dopa Juuru	1ese	
	re (Imer Imer	S	
글 중 :	Sign	_ n.ts	3	
∯ <u>वि</u>	np de	를 전 다	3	
5 m			. Sing	
fied with	6 ₹ 0 Ω	3 6	<u> </u>	
8 🚊	<u>6</u>	유	<u>Š</u>	
« <u>"</u> -	Jacob Market	, B.	<u> </u>	
=	<u>∓</u> }		; ∄	
쿬		s identified with a v in the application is to be lodged to	eans	
0	<u>S</u>	<u> </u>		
ᇍ	e to Mov	Show on	pg l	
Ε <u>τ</u> .	<u>7</u> 9	बु	. g	
ec	ž C	DA_	E3 (
~~ [ğ Ç	plan de	; 3	
	96 <u>5</u>	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	o Di	
를	ans dev	S S S S		
ık i	e or		اھ	
g i) Meg	aus.	eve	
요 !	ֆ જુ.	ģ.		
養	olua	S ₂	nen	
Ş i	3	וושנ	-	
a	12m.	9		
ertife	be.	he		
	Shor	ä		
a <u>ut</u>	5	sac		
hors.	5	эссап		
y ag	皇	par		
इं!	ans i	July		
je je	and	7		
bee	spe	g i		
, i	cific	velo		
in the second	atio	ğ		
ä	กร 2	<u> </u>		
ě	ဂ္ဂ	ģ.		
Б В 1	mpa	r <u>s</u>		
fina	inyii	3 1		
8	3 <u>3</u>	를 [
- Ç	ನ ಖ	ดั ซ		
alo '	p	် ကို		
o Ce	cati)esc		
	אָר אַנ אַר אַנ	. □		
Commitments identified with a 🗸 in the Certifier check column must be certified by a certifying authority as having been fulfilled before a final occupation certificate for the development may be issued	Commitments identified with a "\" in the "Show on CC/CDC plans & specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development	Commitments identified with a 🦿 in the Show on DA plans column must be shown on the plans accompanying the development application is to be lodged for the proposed development (if a development application is to be lodged for the proposed development)		
ğ	5	Į,		
.	stru	ent (
	Choi	3		
:	ָ ו			
				136

A H	DESIGN
ANNA HENRY * 22 WA	NDEEN RD . CLAREVILLE NSW 2107

Schedule of Colours

Proposed alterations & additions at 21 Wallumatta Road Newport

for Mr. & Mrs. Hanks

or Baltanise op vede nysa er homatian bale mis nysa vedeen. Specification This schedule is to be read in conjunction with the enclosed plans.

Materials and Colours Provide material and colours as set out in the following schedule

Items	Material and Description	Colour	Sample
ROOF	COLORBOND CUSTOMORB ROOF SHEETING ON BATTENS & INSULATION (SEE BASIX)	TO MATCH EXISTING WOODLAND GREY	
GUTTERING & DOWNPIPES	QUAD GUTTERING WITH ROUND DOWNPIPES & LEAFGUARDS	SEE ABOVE	SEE ABOVE
ROOF FASCIA & BARGE BOARDS	FINGERJOINTED PRE-PRIMED TIMBER FASCIA	TO MATCH EXISTING	
EAVES LINING	6mm F.C. SHEETING	SEE ABOVE	N/A
WINDOWS & DOORS	ALUMINIUM FRAMED FOR DETAILS — SEE BASIX	WHITE	N/A
CLADDING	WEATHERBOARDS TO MATCH EXISTING FIXED TO TIMBER STUD WALLS WITH INSULATION (SEE BASIX)	TO MATCH EXISTING	
MASONRY WALLS	CEMENT RENDERED OR STONEFACED BLOCKWORK	'DULUX' LINSEED OR EQUAL	****



Application Lodgement Summary

Sydney WATER

Reference Number 8274089

Date Requested: Fri October 26 2012

Agent

Reece Mona Vale, 10 Taronga Pl Mona Vale

Applicant

AJ HANKS G HANKS, 21 WALLUMATTA RD NEWPORT 2106

Property/Asset

21 Wallumatta Rd, Newport 2106 (Aj Hanks G Hanks) PNum: 3460924

150 mm VC Sewer Main - (2808927) (WasteWater)

Product

Building Plan Approval Application

Charge Product Cost GST Total
Building Plan Approval Application \$16.71 \$0.00 \$16.71

Property Special Conditions for Plumbers

Boundary Trap Required	No
Watercharged/Tidal area	No
Partial Drainage area	No
Aggressive Soil area	No
Cast Iron Pipe area	Yes
Sewer Surcharge area	No
Minimum Gully Height area	No
Sewer Available	Yes
Connection Type	Gravity

You must contact Sydney Water to clarify the property special conditions where the property special conditions are not shown (yes or no), are shown as "unset", "unknown" or "not available" or if the proposed development is being built over more than one existing property.

Please note that boundary traps must be fitted for all commercial and industrial properties and you must ensure that all plumbing/drainage and building works are carried out in accordance with the relevant codes and standards.

A water meter is required to be fitted to the property during construction. You will need to ensure that your licensed plumber carries out this work in accordance to the relevant codes and standards.

THIS PLAN / DOCUMENT FORMS

PART OF FORM BUILDING

CERTIFIERS CC / CDC

Levy Online Payment Receipt



Thank you for using our Levy Online payment system. Your payment for this building application has been processed.

Applicant Name:	GLENDA HANKS
Levy Application Reference:	5035156
Application Type:	DA
Application No.:	N0090/12
Local Government Area/Government Authority:	PITTWATER COUNCIL
Site Address:	21 WALLUMATTA RD
	NEWPORT
	NSW
	2106
Value Of Work:	\$181,000
Levy Due:	\$633
Levy Payment:	\$633
Online Payment Ref.:	672210949
Payment Date:	26/10/2012 12:53:39 PM

THIS DEAN ADOCUMENT FORMS

PART OF FORM BUILDING

CERTIFIERS COVICEC

Mean Val. 1897, 2023

Mean Val. 1897, 2023

Pr. (20) 2899 2025

Fr. (20) 2899 2035

ACM 05124176

ACM 05124176

ADM 40 101 544 752

CONSTRUCTION NOTES

ings is to be read in conjunction with the architectural drawings. Intuction the structure shall be maintained in a stable condition and no part shall uilder to ensure stability of existing structures in the vicinity of excavation works. lility of existing structuresin the vicinity of excavation works.

otherwise.

on these drawings have been designed for live loads as follows:

Pa

- 0.25kPa
- 1.5/1.8/2.0kPa
Elsewhere
- 1.5/1.8/2.0kPa
as required in accordance with AS 1170
ansions shall not be obtanied by scaling from the drawings. All setting out dimensions shall be refired any discrepancies shall be referred to the Engineer prior to commencement of works.

G6 Annual probabilities of exceedance - Importance level
The importance level for this structure has been ascertained using AS/NZS 1170.0 Structural design
actions Partly General Principles and the Building Code of Australia (BCA) as described below:
Consequence of failure - Ordinary
Description - Medium consequences for loss of human life, or considerable economic, social or
environmental consequences
Importance level - 2

bability of Exceedance
Design working life - 50 years
Importance level - 2
Wind (non-cyclonic) - 1/1000 (Category - N3)
Earthquake - 1/1000

workmanship and materials shall be in according to the comments.

The comment of the comment of

Pumped concrete shall have a minimum slump of 170mm (±25mm) Flood curing of concrete 14 days minimum with NO curing agents

Exposure Egmed not Formed exposed Not (gmed class)

Class Westler Earth backfill Membrane and A5 and 40 45 and 45

C4 Mechanically various (C5 Conduits shall not be placed between transmissing conduits shall not be placed between transmissing conductions and the conduction of the construction joints shall be properly formed and used only where shown or specifically approved to Engineer.

C7 No holes, chases or embedment of pipes, other than those shown on the structural drawings, shall be made in concrete members without prior approval by the Engineer.

C8 Spices in reinforcement shall be made only in the positions shown or as otherwise approved by the Engineer.

N32

MASONRY

MASONRY

MI Provide sliding surface consisting of 2 layers of galvanised iron sheets with graphile grease in between top an bottom of all load bearing masonry walls in contact with suspended slabs. Prior to application of sliding surface the concrete or masonry shall be level and smooth.

M2 Normasonry walls to be erected on suspended slabs and bearns unit all propring has been removed.

M3 Brids used in load bearing construction shall have a minimum compressive strength (as per A.S. 3700) of 20 MP a unless otherwise noted.

M4 Provide 12mm polystyrene bond breaker between vertical face of masonry walls and concrete.

Lapped fabric splices shall be so made that the overlap, measured between outermost transverse wires of each sheet of fabric, is not less than the spacing of the wires plus 25mm

and materials to be in accordance with current editions of AS 1720 and AS 1884, infimum stress grade F7 U.N.O. All hardwood to be minimum stress grade F14 U.N.O., or joist to be notiched unless specified by the Expineer, sits around openings and under walls above U.N.O., be durability class 1 or 2 cut ends with Reseal by Probit to manufacturer's specifications to achieve required haz-

nn shall be bloked over supports and at a maximum of 3,000mm centres, succlusize. Weathers shall be 3.0mm thickness (min.) and at least $2\frac{1}{2}$ times the bolt be M16 Grade 4.6 U.N.0 with the first connections.

orcement fabric shall be to AS 1304 Galvanized where external orcement bars shall be to AS 1302 Galvanized where external orcement bars shall be to AS 1302 Galvanized where external SL were reinforcing Barbic, R: structural grade round bar, N: ribbed bar 500MPa al grade, Y: ribbed bar 410MPa structural, BTM: bottom, T: Top, TM/L#TM trench stample of designation code for reinforcing bars:-

all cores.

Where vertical reinforcement is to be provided in both faces, bers are to be located in alternate cores.

Where horizontal reinforcement is to be provided in both faces it shall be provided in staggered courses.

urately positioned by templates or similar means. Starter bers must be approved by you and by the Structural Engineer prior to commencement of blockwor, to starter bars through inspection openings at the base of the wall & also accurately fixed in appropriate method.

concreite shall be placed directly with the ground. Isolate all surfaces from contact with tioon (or similar) with tipped joints. or surface with tipped joints are surface building and pavement to minimum 98% standard imput fill areas and subgrade under building and pavement to minimum 98% standard imput of yearsity in accordance with AS 1288 CL 5.2.1

encased or where noted otherwise all structural steelwork sliding in-skill is required on any galvanized material the teld using galvanized paint in accordance with ASNAZS 4680 . rawing to be submitted to the Engineer and approval obtained in on its commenced. Approval cowers shuctural sufficiency of sloning accuracy, and post of 500mm. All cross wires to trench mesh received.

wres.

194 @ 750mm maximum centres to maintain the nominated ant shall be tied at alternate intersections.

made in accordance with the provisions of Table 13.1.2.2.A of

REGISTERED PROFESSIONAL ENGINEER
Mario F. Benitaz, Ber (Struct) MELaust. (PErp. (1418917) MIPENZ (111943)
Hario F. Benitaz, Ber (Struct) MELaust. (PErp. (1418917) MIPENZ (111943)
Har appropriately qualified to certify this component of the project.
Hereby state that these plans or details comply with the conditions to development consent provisions of the BCA (Building Code of Australia), AS1170.1, AS1170.2, AS1684, AS1720, AS3600 & AS4100

SPECTION BY ENGINEER

SPECTION BY ENGINEER

HOURS NOTICE IS REQUIRED BEFORE ANY SITE INSPECTION

Being stata of all forings prior to controlle pour

Any inflorement prior to controlle pour

Any inflorement prior to controlle pour

Timber & Sheel familiago prior to cladding and/or ining

Links after installation

ONINGT YOUR PCA (Principal Certifying Authority) AS TO REQUIREMENTS FOR MANDATORY CRITICAL STAGE

INSPECTIONS IN ACCORDANCE WITH REVISED EPAA ACT REGULATIONS EFFECTIVE JULY 1, 2004

the Environment Planning and Assessment Act 1979

these plans and specifications will comply with certify that work completed in accordance with

referred to in Section 81A(5) of

C12 Where transverse tie bars are not shown, provide N12-400. Splice where necessary with main bars for 400mm.
C13 All concrete shall be placed and "curred" in accordance with AS 3800. Where curing compound is used it must applied (a) onto slabs within 2 hours of finishing operation walls and columns immediately after removal of formwork.
C14 Horizontal formwork shall be shipped when approved by the Engineer.
C15 Slabs and beams shall bear only on the beams, walls, etc., shown on the drawings: a building elements shall be kept 15mm obear from soft ros structure.
C16 All slabs-on-ground shall be placed on 200 µm damp proof membrane over 50mm la compacted samd.
C17 No connecte shall be placed directly with the ground. Isolate all surfaces from contact from soft fill areas and subgrade under building and pavement to minimum 98% star maximum dry density in accordance with AS 1289 C1 5.2.1 In the placed and "cured" in accordance with AS 3600. Where curing shall be placed and "cured" in accordance with AS 3600. Where curing used it must applied (a) onto slabs within 2 hours of finishing operation, (b) onto furnish mediately after removal of formwork.

Trinork shall be stripped when approved by the Engineer.

Trinork shall be stripped when approved by the Engineer.

Trinork shall be stripped when approved by the Engineer.

Trinork shall be stripped when approved by the Engineer.

Trinork shall be stripped when approved by the Engineer.

cavation and backfill shall be carried out neatly to the lines. Levels and grades specified backfill material required or specified shall be compacted generally to at least 95% of its mum dry density (test method in accordance with AS 1289-E:1.1 - Standard Compactive

material beneath edge beams to be compacted in accordance with clause 6.4.2 of AS 10.1998 and as specified in E2 above. To 500, regetation and deterious material shall be stripped from the building platform a commencement of earthworks.

B9
a total cover to outside of blockwork shall 65mm,
b vertical the demolecular of blockwork shall 65mm,
b vertical the demolecular of the format by positioned by a format by the wall must be demolecular of the format by the f © form continuous fliet U.N.O. and welling to be in accordance with AS1554. steel work bearing on mansary to be bedded on 20mm thick and full width and mortar grout pad.

The provides a content of the provides all structural traints diseal. She disease, used inheritally or where noted otherwise all structural traintsed Sheel. She disease, used inheritally or where noted otherwise all structural traintsed Sheel. She disease the structural structural structural traintsed Sheel. She disease the structural structural structural ST be painted/coated using galvanized plant in accordance with ASNZS 4680. ST be painted/coated using galvanized plant in accordance with ASNZS 4680 sed workshop of dwing to be submitted to the Engineer and approval obtained in before fabrication is commenced. Approval covers structural sufficiency of each ord dimensionion accuracy.

ot dimensioning accuracy.

ding steel plates shall comply with AS 1538-1988
egory SP using E41xx electrodes. All butt welds shall be complete

points and members and not amentsoning accuracy.

So Rolled steel sections including seed plates shall comply with AS 1538-1988

S10 UNO all welds shall be category SP using E41xx electrodes. All butt welds shall be complete penetration category SP.

S11 Grouling of anothor bolt seevesand base plates shall be completed by the contractor using high strength, non-strincable grout.

S12 Purlin bolts shall be M12 - 4.6S

S13 Steel work shall have one of the following grades of corrosion protection:

INTERNAL.

INTERNAL

INTERNAL

INTERNAL

a. thoroughly cleaned wire brushing, followed by two coets of zinc phosphate primer equivalent to Dulux Luxsprime applied by hand using brushes to achieve a total dry film thickness (drt) of 70µm (microns)

EXTERNAL ELEMENTS & ELEMENTS WITHIN EITHER SKIN OF EXTERNAL CAVITY WALLS

b. Preparation blast clean to a minimum standard class 2.5 in accordance with AS 1627 Part 4, Primer 2-pack epoxy phosphate at dft of 75µm (Dulux Durepon P14)

Barrier coat 2-pack epoxy microacous iron oxide, aft of 100µm

Finish coat 2-pack epoxy ging ploss acrylic to dft of 75µm(e.g. Dulux Acrathane 1 F) in an approve colour.

c. Hot dipped galvanized to AS 4880

where the galvanic (not dip galvanized) coating is compromised by welding, boiling or damage, inorganic zinc-rich paint (minimum 95% zinc content) is to be applied after wire brushing affected area (uses 3 coasts minimum) or hot metal spray in accordance with AS 4880.

d. As specified by others e.g. architect, etc.

DRAWINGS
1. CONSTRUCTION NOTES
2. BASSMENT & GROUND FLOOR - PLAN VIEW - SUSPENDED SLABS & SECTIONS
3. UPPER FLOOR + ROOFING - PLAN VIEW - SUSPENDED SLAB, FRAMING + SECTIONS

Ny August 2012 for: Ms Glenda Hanks 21 Wallumatta Rd Newport NSW 2106 A1

CONSTRUCTION NOTES









