# **BASIX** Certificate

Building Sustainability Index www.basix.nsw.gov.au

# **Alterations and Additions**

Certificate number: A362532 02

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Alterations and Additions Definitions" dated 06/10/2017 published by the Department. This document is available at www.basix.nsw.gov.au

#### Secretary

Date of issue: Sunday, 03, November 2019

To be valid, this certificate must be lodged within 3 months of the date of issue.



## **Project address** Project name 105 Prince Alfred Pde - DA 02 105 Prince Alfred Parade Newport 2106 Street address Local Government Area Northern Beaches Council Deposited Plan 13457 Plan type and number Lot number 72 Section number Project type Separate dwelling house Dwelling type Type of alteration and My renovation work is valued at \$50,000 or more, addition and includes a pool (and/or spa).

Certificate Prepared by (please complete before submitting to Council or PCA)

Name / Company Name: Phil Brown Drafting

ABN (if applicable): 16164362569

escriptio

BASIX Certificate number: A362532\_02 page 2 / 5

Pool and Spa	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Rainwater tank			
The applicant must install a rainwater tank of at least 745 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	<b>✓</b>	<b>✓</b>	<b>✓</b>
The applicant must configure the rainwater tank to collect rainwater runoff from at least 101 square metres of roof area.		<b>✓</b>	<b>✓</b>
The applicant must connect the rainwater tank to a tap located within 10 metres of the edge of the pool.		✓	✓
Outdoor swimming pool	,		
The swimming pool must be outdoors.	<b>✓</b>	<b>✓</b>	<b>✓</b>
The swimming pool must not have a capacity greater than 10.1 kilolitres.	✓	<b>✓</b>	✓
The swimming pool must have a pool cover.		<b>✓</b>	✓
The applicant must install a pool pump timer for the swimming pool.		<b>✓</b>	<b>✓</b>
The applicant must install the following heating system for the swimming pool that is part of this development: gas.		<b>V</b>	<b>✓</b>

BASIX Certificate number: A362532\_02 page 3 / 5

Fixtures and systems	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Lighting			
The applicant must ensure a minimum of 40% of new or altered light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting-diode (LED) lamps.		<b>V</b>	<b>✓</b>

BASIX Certificate number: A362532\_02 page 4 / 5

Glazing requ	irements						Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Windows and	glazed do	ors							
The applicant must install the windows, glazed doors and shading devices, in accordance with the specifications listed in the table below. Relevant overshadowing specifications must be satisfied for each window and glazed door.						<b>✓</b>	<b>✓</b>	<b>✓</b>	
The following requirements must also be satisfied in relation to each window and glazed door:							<b>V</b>	<b>✓</b>	
Each window or glazed door with improved frames, or pyrolytic low-e glass, or clear/air gap/clear glazing, or toned/air gap/clear glazing must have a U-value and a Solar Heat Gain Coefficient (SHGC) no greater than that listed in the table below. Total system U-values and SHGCs must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions. The description is provided for information only. Alternative systems with complying U-value and SHGC may be substituted.								<b>✓</b>	~
For projections described in millimetres, the leading edge of each eave, pergola, verandah, balcony or awning must be no more than 500 mm above the head of the window or glazed door and no more than 2400 mm above the sill.						✓	✓	✓	
Pergolas with polycarbonate roof or similar translucent material must have a shading coefficient of less than 0.35.							<b>✓</b>	✓	
Pergolas with fixed battens must have battens parallel to the window or glazed door above which they are situated, unless the pergola also shades a perpendicular window. The spacing between battens must not be more than 50 mm.							<b>✓</b>	✓	
Windows an	d glazed d	doors g	lazing r	equireme	nts		-		
Window / door no.	Orientation	Area of glass inc. frame (m2)	Oversha Height (m)	dowing Distance (m)	Shading device	Frame and glass type			
W1	N	5.8	0	0	eave/verandah/pergola/balcony >=900 mm	improved aluminium, single clear, (U-value: 6.44, SHGC: 0.75)			
W2	N	2.7	0	0	eave/verandah/pergola/balcony >=900 mm	improved aluminium, single clear, (U-value: 6.44, SHGC: 0.75)			
W3	N	8.3	0	0	eave/verandah/pergola/balcony >=900 mm	improved aluminium, single clear, (U-value: 6.44, SHGC: 0.75)			

BASIX Certificate number: A362532\_02 page 5 / 5

### Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a "

"" in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a "

"in the "Show on CC/CDC plans & specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a "

"" in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate for the development may be issued.