

NatHERS Thermal Performance Specifications (BASIX Thermal Comfort)
396-402 Sydney Road, Balgowlah

These are the specifications upon which the NatHERS assessment is based. If details included in these Specifications vary from other drawings or written specifications, these Specifications shall take precedence. If only one specification option is detailed for a building element, that specification must apply to all instances of that element for the project.

Windows	Glass	Frame	U value	SHGC	Detail
Default	Single glazed, low E high solar gain	Aluminium	5.4	0.49	Generally for window types: Awning, bi-fold, casement, tilt 'n' turn
Default	Single glazed, low E high solar gain	Aluminium	5.4	0.58	Generally for window types: Sliding window/ door, double hung, fixed, louvre
Default	Double glazed, low E high solar gain	Aluminium	4.3	0.47	For unit 3.03 - window types: Awning, bi-fold, casement, tilt 'n' turn
Default	Double glazed, low E high solar gain	Aluminium	4.3	0.53	For unit 3.03 - window types: Sliding window/ door, double hung, fixed, louvre

* The glass type and frame descriptions are indicative only. The U-value and SHGC performance figures must be met to achieve compliance

Skylights	Glass	Frame	U value	SHGC	Detail
Default	Single glazed, clear	Aluminium	7.3	0.79	For unit 3.03

External walls	Construction	Added Insulation	Detail
	Concrete + stud	R 2.0	As per drawings
	Framed with metal cladding	R 2.0	As per drawings

Internal walls	Construction	Added Insulation	Detail
	Hebel + stud	R 2.0	Walls separating units from open lobbies / breezeways
	Concrete	R 1.0	Walls separating units from stairwells and lifts
	Hebel + stud	None	Party walls
	Plasterboard on studs	None	Walls within units

Floors	Construction	Added Insulation	Detail
	Concrete	None	Generally
	Concrete	R 1.5	For units 1.03 and 1.04 - floors over open air and non-conditioned areas

Ceilings	Construction	Added Insulation	Detail
	Plasterboard	See roof detail below	

Roof	Construction	Added Insulation	Detail
	Concrete	R 1.0	For units: 2.03 and 2.04
	Concrete	R 2.5	For units: 3.01, 3.02, 3.03

Other Requirements

All vents, exhaust fans and downlights (if installed) to be **sealed** to prevent air-infiltration.



Certificate no.: 0005757780
 Assessor Name: Robert Mallindine
 Accreditation no.: VIC/BDAV/12/1475
 Certificate date: 09 Mar 2021
 Dwelling Address:
 396-402 Sydney Road
 Balgowlah, NSW
 2093
www.nathers.gov.au

