

Building Sustainability Index www.basix.nsw.gov.au

Single Dwelling

Certificate number: 1780655S

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.basix.nsw.gov.au

Secretary

Date of issue: Wednesday, 22 January 2025

To be valid, this certificate must be submitted with a development application or lodged with a complying development certificate application within 3 months of the date of issue.



Project summary				
Project name	Proposed Secondary Dwelling			
Street address	98 BEACON HILL Road BEACON HILL 2100			
Local Government Area	Northern Beaches Council			
Plan type and plan number	Deposited Plan DP25604			
Lot no.	7			
Section no.	-			
Project type	dwelling house (detached) - secondary dwelling			
No. of bedrooms	1			
Project score				
Water	✓ 40	Target 40		
Thermal Performance	✓ Pass	Target Pass		
Energy	✓ 73	Target 68		
Materials	✓ 53	Target n/a		

Certificate Prepared by

Name / Company Name: Michael Airey

Certificate No.: 1780655S

ABN (if applicable): 26 769 291 556

Version: 4.03 / EUCALYPTUS 03 01 0

Description of project

Project address	
Project name	Proposed Secondary Dwelling
Street address	98 BEACON HILL Road BEACON HILL 2100
Local Government Area	Northern Beaches Council
Plan type and plan number	Deposited Plan DP25604
Lot no.	7
Section no.	-
Project type	
Project type	dwelling house (detached) - secondary dwelling
No. of bedrooms	1
Site details	
Site area (m²)	600
Roof area (m²)	38
Conditioned floor area (m²)	23.4
Unconditioned floor area (m²)	3.26
Total area of garden and lawn (m²)	60
Roof area of the existing dwelling (m²)	198
Number of bedrooms in the existing dwelling	4

Assessor details and thermal loads					
Assessor number	n/a				
Certificate number	n/a				
Climate zone	n/a				
Area adjusted cooling load (MJ/ m².year)	n/a				
Area adjusted heating load (MJ/m².year)	n/a				
Project score					
Water	✓ 40	Target 40			
Thermal Performance	✓ Pass	Target Pass			
Energy	✓ 73	Target 68			
Materials	✓ 53	Target n/a			

Certificate No.: 1780655S

Version: 4.03 / EUCALYPTUS_03_01_0

page 2/10

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Fixtures	-		
The applicant must install showerheads with a minimum rating of 4 star (> 4.5 but <= 6 L/min plus spray force and/or coverage tests) in all showers in the development.		~	~
The applicant must install a toilet flushing system with a minimum rating of 4 star in each toilet in the development.		~	~
The applicant must install taps with a minimum rating of 5 star in the kitchen in the development.		~	
The applicant must install basin taps with a minimum rating of 5 star in each bathroom in the development.		~	
Alternative water			
Rainwater tank			
The applicant must install a rainwater tank of at least 2500 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	~	~	~
The applicant must configure the rainwater tank to collect rain runoff from at least 38.35 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam).		~	~
The applicant must connect the rainwater tank to:			
all toilets in the development		~	~
 at least one outdoor tap in the development (Note: NSW Health does not recommend that rainwater be used for human consumption in areas with potable water supply.) 		~	-

Version: 4.03 / EUCALYPTUS_03_01_0

Department of Planning, Housing and Infrastructure

Thermal Performance and Materials commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Do-it-yourself Method			
General features			
The dwelling must be a Class 1 dwelling according to the National Construction Code, and must not have more than 2 storeys.	~	~	~
The conditioned floor area of the dwelling must not exceed 300 square metres.	~	~	~
The dwelling must not contain open mezzanine area exceeding 25 square metres.	~	~	~
The dwelling must not contain third level habitable attic room.	~	~	~
Floor, walls and ceiling/roof			
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	~	~	~
The applicant must adopt one of the options listed in the tables below to address thermal bridging in metal framed floor(s), walls and ceiling/roof of the dwelling.	~	~	~
The applicant must show through receipts that the materials purchased for construction are consistent with the specifications listed in the tables below.			~

Construction	Area - m²	Additional insulation required	Options to address thermal bridging	Other specifications
floor - concrete slab on ground, conventional slab.	23.4	nil;not specified	nil	
external wall: framed (solid or reconstituted timber weatherboard); frame: timber - hardwood predominant incl. glue laminated beams.	all external walls	2.50 (or 3.00 including construction);fibreglass batts or roll	nil	wall colour: Light (solar absorptance < 0.48)
internal wall: plasterboard; frame: timber - untreated softwood.	13	none	nil	

Department of Planning, Housing and Infrastructure

Construction	Area - m²	Additional insulation required	Options to address thermal bridging	Other specifications
ceiling and roof - flat ceiling / flat roof, framed - metal roof, timber - hardwood predominant incl. glue laminated beams.	38.35	ceiling: 4 (up), roof: foil/ sarking ;ceiling: fibreglass batts or roll; roof: foil/sarking.	nil	roof colour: light (solar absorptance 0.38-0.47); ceiling area fully insulated

Note	Insulation specified in this Certificate must be installed in accordance with the ABCB Housing Provisions (Part 13.2.2) of the National Construction Code.
Note	If the additional ceiling insulation listed in the table above is greater than R3.0, refer to the ABCB Housing Provisions (Part 13.2.3 (6)) of the National Construction Code.
Note	In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.
Note	Thermal breaks must be installed in metal framed walls and applicable roofs in accordance with the ABCB Housing Provisions of the National Construction Code.

page 5/10

Thermal Performance and Materials commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Ceiling fans			
The applicant must install at least one ceiling fan in at least one daytime habitable space, such as living room.	~	~	~
The applicant must install at least one ceiling fan in each bedroom.	~	~	~
The minimum number and diameter of ceiling fans in a daytime habitable space must be installed in accordance with the ABCB Housing Provisions (Part 13.5.2) of the National Construction Code .	~	~	~

Thermal Performance and Materials commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Glazed windows, doors and skylights			
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each glazed window and door.	~	~	~
The dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table.	~	~	~
The following requirements must also be satisfied in relation to each window and glazed door:	~	~	V
• The applicant must install windows and glazed doors in accordance with the height and width, frame and glazing types listed in the table.	~	~	V
• Each window and glazed door must have a U- value no greater than that listed and a Solar Heat Gain Coefficient (SHGC) within the range listed. Total system U values and SHGC must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions.		~	~
The applicant must install the skylights described in the table below, in accordance with the specifications listed in the table. Total skylight area must not exceed 3 square metres (the 3 square metre limit does not include the optional additional skylight of less than 0.7 square metres that does not have to be listed in the table).	~	~	~

Glazed window/door no.	Maximum height (mm)	Maximum width (mm)	Frame and glass specification	Shading device (Dimension within 10%)	Overshadowing			
South-East facing	South-East facing							
W1	450.00	600.00	aluminium, single glazed (U-value: <=7.5, SHGC: 0.74 - 0.90)	eave 420 mm, 270 mm above head of window or glazed door	not overshadowed			
South-West facing								
W3	980.00	1480.00	aluminium, single glazed (U-value: <=7.5, SHGC: 0.74 - 0.90)	eave 300 mm, 370 mm above head of window or glazed door	not overshadowed			
North-West facing								
W2	900.00	1160.00	aluminium, single glazed (U-value: <=7.5, SHGC: 0.74 - 0.90)	eave 300 mm, 460 mm above head of window or glazed door	not overshadowed			

Department of Planning, Housing and Infrastructure

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Hot water			
The applicant must install the following hot water system in the development, or a system with a higher energy rating: gas instantaneous with a performance of 5 stars.	~	~	~
Cooling system	·		
The living areas must not incorporate any cooling system, or any ducting which is designed to accommodate a cooling system.		~	~
The bedrooms must not incorporate any cooling system, or any ducting which is designed to accommodate a cooling system.		~	~
Heating system			
The living areas must not incorporate any heating system, or any ducting which is designed to accommodate a heating system.		~	~
The bedrooms must not incorporate any heating system, or any ducting which is designed to accommodate a heating system.		~	~
Ventilation			
The applicant must install the following exhaust systems in the development:			1
At least 1 Bathroom: no mechanical ventilation (ie. natural); Operation control: n/a		-	~
Kitchen: no mechanical ventilation (ie. natural); Operation control: n/a		~	~
Laundry: natural ventilation only, or no laundry; Operation control: n/a		~	~
Artificial lighting			,
The applicant must ensure that a minimum of 80% of light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting-diode (LED) lamps.		~	~
Natural lighting			
The applicant must install a window and/or skylight in the kitchen of the dwelling for natural lighting.	~	~	~

Department of Planning, Housing and Infrastructure

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
The applicant must install a window and/or skylight in 1 bathroom(s)/toilet(s) in the development for natural lighting.	~	~	~
Alternative energy			
The applicant must install a photovoltaic system as part of the development. The applicant must connect this system to the development's electrical system.	~	~	~
The photovolatic system must consist of: • photovolatic collectors with the capacity to generate at least 0.3 peak kilowatts of electricity, installed at an angle between 0 degrees and 10 degrees to the horizontal facing south east	_		

Legend

BASIX

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate (either interim or final) for the development may be issued.

Department of Planning, Housing and www.basix.nsw.gov.au Version: 4.03 / EUCALYPTUS_03_01_0 Certificate No.: 1780655S Wednesday, 22 January 2025 page 10/10 Infrastructure