

# Water Sensitive Urban Design Report

## Thompson Health Mona Vale, Basset Street

Prepared for: Thompson Health Care Pty Ltd

Issue no: A

| Revision | Date     | Purpose                           | Prepared By | Reviewed By |
|----------|----------|-----------------------------------|-------------|-------------|
| A        | 26/04/24 | Issue for Development Application | N.Pearce    |             |
|          |          |                                   |             |             |
|          |          |                                   |             |             |
|          |          |                                   |             |             |

### Table of Contents

1 Introduction .....3

2 Site Description .....4

3 Council Requirements .....5

4 Site Stormwater Layout .....6

5 Water Sensitive Urban Design .....7

Appendix A – Stormwater Management Plans .....8

Appendix B – Council Water Management Referral Response (26/11/2020) .....9

## 1 Introduction

This stormwater management report has been written to support the Development Application for the redevelopment of the Thompson Health Aged Care Facility located at which is proposed to be located at 23-25 Bassett Street, Mona Vale.

The aged care facility has previously been DA approved (DA2020/0816) by Northern Beaches Council and included a stormwater management plan completed by ACOR Consultants

The development is to be re-submitted for DA and is proposed to include following changes as indicated on the amended site architectural drawings completed by Gartner Trovato;

- Room numbers to remain the same but increase in size with a larger building gross floor area.
- Revised floor layouts which include the removal of the atrium and larger internal courtyard garden areas
- Basement floor level to be lowered 500mm with a minor increase in area
- Revised façade treatments including new balconies and bay window
- The building footprint has increased by approximately 300m<sup>2</sup> from the approved DA

These modifications do not significantly change the stormwater management of the site that has been previously outlined in the approved DA plan and as such the design intent remains the same. This report is aimed to inform the proposed changes between the approved scheme and demonstrate that the development still complies with the Council's stormwater requirements.

In the preparation of this report, the following reference information has been used:

- Architectural plans prepared by Gartner Trovato
- DA Approved Stormwater Management Plans completed by ACOR Consultants
- Northern Beaches Council DCP
- Northern Beaches Council Water Management Referral Response (DA2020/0816) dated 24/11/2020
- Notice of Determination – DA2020/0816

## 2 Site Description


The site is located at 23-33 Bassett Street, Mona Vale near the intersection of Barrenjoey Road.

It is 6503m<sup>2</sup> in area falls towards the south and east with levels that range 3.20 m AHD on the southern boundary and 4.70 m AHD along the northern road frontage. The existing aged care development on the site consists of a two-storey aged care facility, tennis court, carparking at the rear and two single-storey dwellings.

The proposed re-development works involve the demolition of the existing aged care facility and single-storey dwellings and the construction of a new two-storey, 118 bed aged care facility.



**Figure 1 - Existing Thompson Health Care Facility, Mona Vale**



**Figure 2 – Proposed Redevelopment architectural site plan**



### 3 Council Requirements

The redevelopment is to be designed in accordance with Northern Beaches Council DCP and is proposed to match the design intent of the approved DA stormwater management scheme completed by ACOR Consultants.

The site is flood-affected in the 1% AEP and PMF and is considered to be a flood-controlled lot by Council. Council has stated that the site acts as a flood storage area and that the development is to provide the equivalent storage area post-development. This requirement is achieved by the proposed development and is further discussed in the flood response letter which has been submitted as part of the Development Application.

Council DCP states that Onsite Detention is generally required for similar site redevelopments, however, the site is flood-affected as stated above and therefore Council has advised that OSD is not required for the development. As such, OSD was not provided as part of the previously approved scheme and is therefore not proposed for this resubmission.

Stormwater quality improvement systems are required to remove pollutants from the stormwater prior to discharging to the Council drainage network. The minimum pollutant reduction targets are listed below.

**Table 1 – Council Pollutant Removal Performance Targets**

| Pollutant              | Performance Requirements   |
|------------------------|--|
| Total Phosphorous      | 65% reduction in the post development mean annual load <sup>1</sup>  |
| Total Nitrogen         | 45% reduction in the post development mean annual load <sup>1</sup>  |
| Total Suspended Solids | 85% reduction in the post development mean annual load <sup>1</sup>  |
| Gross Pollutants       | 90% reduction in the post development mean annual load <sup>1</sup> (for pollutants greater than 5mm in diameter)  |
| pH                     | 6.5 - 8.5  |
| Hydrology              | The post-development peak discharge must not exceed the pre-development peak discharge for flows up to the 50% AEP |

#### 4 Site Stormwater Layout

The proposed building is to be located at the centre of the centre with landscaping and site drainage surrounding the building. The site generally drains towards the northeast and discharges to the Council network via a new new connection in Bassett Street. A new kerb inlet and junction pit over the existing Council drainage will be constructed in Bassett Street to allow for the site stormwater discharge.

There are two (2) existing inter-allotment drainage lines within easements located on the site. One line is located along the western boundary which will be retained and the other along the southern and eastern boundaries. The eastern easement is required to be diverted as part of the works to remove it from the building footprint.

The site drainage will include a 20kl rainwater tank, as required by Council DCP, and will collect 60% of the roof area for reuse for irrigation and toilet flushing. The rainwater tank overflow and the remainder of the roof catchment will be connected to inground stormwater which will directed to filter chambers. Stormwater filter cartridges, by Oceanprotect, will be within the chamber to treat the stormwater and ensure that Councils WSUD requirements are achieved. Grassed lined swales are provided around the building to collect overland flow from surrounding landscaping to provide some treatment and infiltration prior to being collected to inground drainage. Refer Appendix A for the proposed site stormwater management plans for further detail.




Figure 3 – Proposed Redevelopment architectural site plan

## 5 Water Sensitive Urban Design

A MUSIC model has been undertaken to represent the water quality measures required to meet the Council reduction targets. The MUSIC model, shown below, has been provided as part of the DA submission for Councils review.

The previous stormwater management plans completed by ACOR Consultants and approved as part of the notice of determination (DA2020/0816) was subject to Council referral and refusal on the basis of the WSUD measures implemented as part of the development were not supported. The development proposed to utilise filter cartridge systems to remove pollutants which the Council stated was against their policy of using natural bio-filtration infiltration swales to capture flows. Vegetated swale drains were subsequently included in the design however it was noted that these provided minimal treatment benefits due to the limited catchment area contributing to the swales. This was subsequently accepted by Council on the condition that the proposed rainwater tank was connected to at least 50% of toilets within the building, refer to the referral letter dated 26/11/2020 in Appendix B.

The proposed redevelopment and current ENTEC stormwater management plan intends to implement the same design intent as the approved scheme and include the 50% rainwater reuse provision for toilet flushing.




Figure 4 – WSUD Catchment Plan

The results of the MUSIC model and the comparison to Council targets are shown in the table below. Reduction targets are satisfied for all pollutants and as such are compliant with Council requirements.

Table 2 – Site MUSIC Model Results

| Stormwater Pollutant         | Council Target % | Site Reduction % |
|------------------------------|------------------|------------------|
| Gross Pollutants             | 90               | 98.6             |
| Total Suspended Solids (TSS) | 85               | 85.1             |
| Total Phosphorus (TP)        | 65               | 71.6             |
| Total Nitrogen (TN)          | 45               | 50.5             |

Appendix A – Stormwater Management Plans



# THOMPSON HEALTH BASSETT PROPOSED AGED CARE FACILITY

## 23 & 25 BASSETT STREET, MONA VALE NSW

### CIVIL SERVICES

#### SITWORKS NOTES

- ORIGIN OF LEVELS :- AUSTRALIAN HEIGHT DATUM (A.H.D.)
- CONTRACTOR MUST VERIFY ALL DIMENSIONS AND EXISTING LEVELS ON SITE PRIOR TO COMMENCEMENT OF WORK.
- ALL WORK IS TO BE UNDERTAKEN IN ACCORDANCE WITH THE DETAILS SHOWN ON THE DRAWINGS, THE SPECIFICATIONS AND THE DIRECTIONS OF THE PRINCIPAL'S REPRESENTATIVE.
- EXISTING SERVICES HAVE BEEN PLOTTED FROM SUPPLIED DATA AND AS SUCH THEIR ACCURACY CANNOT BE GUARANTEED. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO ESTABLISH THE LOCATION AND LEVEL OF ALL EXISTING SERVICES PRIOR TO THE COMMENCEMENT OF ANY WORK. ANY DISCREPANCIES SHALL BE REPORTED TO THE PRINCIPAL'S REPRESENTATIVE. CLEARANCES SHALL BE OBTAINED FROM THE RELEVANT SERVICE AUTHORITY.
- WHERE NEW WORKS ABUT EXISTING THE CONTRACTOR SHALL ENSURE THAT A SMOOTH EVEN PROFILE, FREE FROM ABRUPT CHANGES IS OBTAINED.
- THE CONTRACTOR SHALL ARRANGE ALL SURVEY SETOUT TO BE CARRIED OUT BY A REGISTERED SURVEYOR.
- CARE IS TO BE TAKEN WHEN EXCAVATING NEAR EXISTING SERVICES. NO MECHANICAL EXCAVATIONS ARE TO BE UNDERTAKEN OVER COMMUNICATIONS OR ELECTRICAL SERVICES. HAND EXCAVATE IN THESE AREAS.
- ALL SERVICE TRENCHES UNDER VEHICULAR PAVEMENTS SHALL BE BACKFILLED WITH AN APPROVED NON-NATURAL GRANULAR MATERIAL AND COMPACTED TO 98% STANDARD MAXIMUM DRY DENSITY IN ACCORDANCE WITH AS 1289.5.1.1.
- ALL TRENCH BACKFILL MATERIAL SHALL BE COMPACTED TO THE SAME DENSITY AS THE ADJACENT MATERIAL.
- ON COMPLETION OF PIPE INSTALLATION ALL DISTURBED AREAS MUST BE RESTORED TO ORIGINAL, INCLUDING KERBS, FOOTPATHS, CONCRETE AREAS, GRAVEL AND GRASSED AREAS AND ROAD PAVEMENTS.
- PROVIDE 10mm WIDE ABELFLEX JOINTS BETWEEN CONCRETE PAVEMENTS AND ALL BUILDINGS, WALLS, FOOTINGS, COLUMNS, KERBS, DISH DRAINS, GRATED DRAINS, BOLLARD FOOTINGS ETC.
- CONTRACTOR TO OBTAIN ALL AUTHORITY APPROVALS.
- ALL BATTERS TO BE GRASSED LINED WITH MINIMUM 100 TOPSOIL AND APPROVED COUCH LAID AS TURF.
- MAKE SMOOTH TRANSITION TO EXISTING SERVICES AND MAKE GOOD.
- THE CONTRACTOR SHALL PROVIDE ALL TEMPORARY DIVERSION DRAINS AND MOUNDS TO ENSURE THAT AT ALL TIMES EXPOSED SURFACES ARE FREE DRAINING AND WHERE NECESSARY EXCAVATE SUMPS AND PROVIDE PUMPING EQUIPMENT TO DRAIN EXPOSED AREAS.
- ON COMPLETION OF WORKS ALL DISTURBED AREAS MUST BE RESTORED TO ORIGINAL INCLUDING, BUT NOT LIMITED TO, KERBS, FOOTPATHS, CONCRETE AREAS, GRASS AND LANDSCAPED AREAS.

#### EXISTING SERVICES AND FEATURES

- THE CONTRACTOR SHALL ALLOW FOR THE CAPPING OFF, EXCAVATION, REMOVAL AND DISPOSAL IF REQUIRED OF ALL EXISTING SERVICES IN AREAS AFFECTED BY WORKS WITHIN THE CONTRACT AREA, AS SHOWN ON THE DRAWINGS UNLESS DIRECTED OTHERWISE BY THE SUPERINTENDENT.
- THE CONTRACTOR SHALL ENSURE THAT AT ALL TIMES SERVICES TO ALL BUILDINGS NOT AFFECTED BY THE WORKS ARE NOT DISRUPTED.
- PRIOR TO COMMENCEMENT OF ANY WORKS THE CONTRACTOR SHALL GAIN WRITTEN APPROVAL OF HIS PROGRAMME FOR THE RELOCATION/CONSTRUCTION OF TEMPORARY SERVICES.
- EXISTING BUILDINGS, EXTERNAL STRUCTURES, AND TREES SHOWN ON THESE DRAWINGS ARE FEATURES EXISTING PRIOR TO ANY DEMOLITION WORKS.
- CONTRACTOR SHALL CONSTRUCT TEMPORARY SERVICES TO MAINTAIN EXISTING SUPPLY TO BUILDINGS REMAINING IN OPERATION DURING WORKS TO THE SATISFACTION AND APPROVAL OF THE SUPERINTENDENT. ONCE DIVERSION IS COMPLETE AND COMMISSIONED THE CONTRACTOR SHALL REMOVE ALL SUCH TEMPORARY SERVICES AND MAKE GOOD TO THE SATISFACTION OF THE SUPERINTENDENT.
- INTERRUPTION TO SUPPLY OF EXISTING SERVICES SHALL BE DONE SO AS NOT TO CAUSE ANY INCONVENIENCE TO THE PRINCIPAL. CONTRACTOR TO GAIN APPROVAL OF SUPERINTENDENT FOR TIME OF INTERRUPTION.

#### GENERAL NOTES

- THESE DRAWINGS SHALL BE READ IN CONJUNCTION WITH ALL ARCHITECTURAL AND OTHER CONSULTANTS DRAWINGS AND SPECIFICATIONS AND WITH SUCH OTHER WRITTEN INSTRUCTIONS AS MAY BE ISSUED.
- ALL DIMENSIONS RELEVANT TO SETTING OUT AND OFF-SITE WORK SHALL BE VERIFIED BY THE CONTRACTOR BEFORE CONSTRUCTION.
- DIMENSIONS SHALL NOT BE OBTAINED BY SCALING THE DRAWINGS.
- ALL DIMENSIONS ON DETAILS ARE IN MILLIMETRES UNLESS STATED OTHERWISE. ALL PLANS AND LEVELS ARE EXPRESSED IN METRES.
- DURING CONSTRUCTION THE CONTRACTOR SHALL BE RESPONSIBLE FOR MAINTAINING THE STRUCTURAL STABILITY OF THE WORKS AND ENSURE NO PARTS BE OVER STRESSED UNDER CONSTRUCTION ACTIVITIES.
- WORKMANSHIP AND MATERIALS ARE TO BE IN ACCORDANCE WITH THE RELEVANT CURRENT AUSTRALIAN STANDARDS INCLUDING ALL AMENDMENTS, AND THE LOCAL STATUTORY AUTHORITIES, EXCEPT WHERE VARIED BY THE CONTRACT DOCUMENTS.
- THE APPROVAL OF A SUBSTITUTION SHALL BE SOUGHT FROM THE ENGINEER BUT IS NOT AN AUTHORISATION FOR A VARIATION. ANY VARIATIONS INVOLVED MUST BE TAKEN UP WITH THE ARCHITECT OR PROJECT MANAGER BEFORE THE WORK COMMENCES.
- ANY DISCREPANCIES OR OMISSIONS SHALL BE REFERRED TO THE ENGINEER FOR A DECISION BEFORE PROCEEDING WITH THE WORK.
- THE BUILDER SHALL GIVE 48 HOURS NOTICE FOR ALL ENGINEERING INSPECTIONS.
- BUILDING FROM THESE DRAWINGS IS NOT TO COMMENCE UNTIL APPROVED BY THE LOCAL AUTHORITIES
- THE WORD 'ENGINEER' USED IN THESE NOTES REFER TO AN EMPLOYEE OR NOMINATED REPRESENTATIVE OF **ENTEC CONSULTANTS PTY.LTD.**

#### STORMWATER NOTES

- ALL 300 DIA. DRAINAGE PIPES AND LARGER SHALL BE CLASS "2" APPROVED SPIGOT AND SOCKET FRC OR RCP. PIPES WITH RUBBER RING JOINTS. (U.N.O.) ALL DOWNPIPE DRAINAGE LINES SHALL BE SEWER GRADE UPVC WITH SOLVENT WELD JOINTS. (U.N.O.)
- EQUIVALENT STRENGTH REINFORCED CONCRETE PIPES MAY BE USED.
- ALL PIPE JUNCTIONS UP TO AND INCLUDING 450 DIA. AND TAPERS SHALL BE VIA PURPOSE MADE FITTINGS.
- MINIMUM GRADE TO STORMWATER LINES TO BE IN ACCORDANCE WITH AS/NZS 3500.3-2018 TABLE 6.3.4. (U.N.O.)
- CONTRACTOR TO SUPPLY AND INSTALL ALL FITTINGS AND SPECIALS INCLUDING VARIOUS PIPE ADAPTORS TO ENSURE PROPER CONNECTION BETWEEN DISSIMILAR PIPEWORK.
- ALL CONNECTIONS TO EXISTING DRAINAGE PITS SHALL BE MADE IN A TRADESMAN-LIKE MANNER AND THE INTERNAL WALL OF THE PIT AT THE POINT OF ENTRY SHALL BE CEMENT RENDERED TO ENSURE A SMOOTH FINISH.
- PRECAST PITS SHALL NOT BE USED UNLESS WRITTEN APPROVAL IS OBTAINED FROM THE SUPERINTENDENT.
- WHERE TRENCHES ARE IN ROCK, THE PIPE SHALL BE BEDDED ON A MIN. 50MM CONCRETE BED (OR 75MM THICK BED OF 12MM BLUE METAL) UNDER THE BARREL OF THE PIPE. THE PIPE COLLAR AT NO POINT SHALL BEAR ON THE ROCK. IN OTHER THAN ROCK, PIPES SHALL BE LAID ON A 75MM THICK SAND BED. IN ALL CASES BACKFILL THE TRENCH WITH SAND TO 200MM ABOVE THE PIPE. WHERE THE PIPE IS UNDER PAVEMENTS BACKFILL REMAINDER OF TRENCH WITH SAND OR APPROVED GRANULAR BACKFILL COMPACTED IN 150MM LAYERS TO 98% STANDARD MAX. DRY DENSITY.
- BEDDING SHALL BE TYPE H51, IN ACCORDANCE WITH CURRENT RELEVANT AUSTRALIAN STANDARDS.
- WHERE UPVC STORMWATER LINES PASS UNDER FLOOR SLABS, SEWER GRADE RUBBER RING JOINTS ARE TO BE USED.
- 100 DIA SLOTTED UPVC SUBSOIL DRAINAGE LINES SHALL BE INSTALLED BEHIND ALL RETAINING WALLS, KERBS AND WITHIN PLANTERS.
- WHERE SUBSOIL DRAINAGE LINES PASS UNDER FLOOR SLABS AND VEHICULAR PAVEMENTS UNSLOTTED UPVC SEWER GRADE PIPE SHALL BE USED.
- PROVIDE 3.0M LENGTH OF 100 DIA. SUBSOIL DRAINAGE PIPE WRAPPED IN FABRIC SOCK, AT UPSTREAM END OF EACH PIT.

#### RAINWATER REUSE SYSTEM

##### MARKING & LABELLING

- THE WATER SUPPLY SYSTEM FROM A RAINWATER TANK SHALL BE CLEARLY MARKED 'RAINWATER' AT INTERVALS NOT EXCEEDING 1m WITH CONTRASTING COLOURED WORDING. WATER OUTLETS SHALL BE IDENTIFIED AS 'RAINWATER' WITH A LABEL OR A RAINWATER TAP IDENTIFIED BY A GREEN COLOURED INDICATOR WITH THE LETTERS 'RW'.

##### NON-DRINKING WATER SERVICES - HOSE TAP OUTLETS

- HOSE TAP OUTLETS SHALL:-
  - BE CLEARLY MARKED 'WARNING: NOT FOR DRINKING' IN ACCORDANCE WITH THE REQUIREMENTS OF AS 1319.
  - BE OF A TYPE THAT HAS A REMOVABLE HANDLE.

##### PROXIMITY TO OTHER SERVICES

- THE FOLLOWING APPLIES:
  - ABOVEGROUND INSTALLATION OF NON-DRINKING WATER SERVICES SHALL NOT BE INSTALLED WITHIN 100mm OF ANY PARALLEL DRINKING WATER SERVICE, EXCEPT WHEN INSTALLED IN PIPE DUCT OR STRUCTURALLY SEPARATED
  - BELOW-GROUND INSTALLATIONS OF NON-DRINKING WATER SERVICES SHALL NOT BE INSTALLED WITHIN 300mm OF ANY PARALLEL DRINKING WATER SUPPLY.

##### MARKING & LABELLING OF NON-DRINKING WATER PIPES & OUTLETS

###### GENERAL

- ALL PIPES, PIPE SLEEVES, IDENTIFICATION TAPES, & OUTLETS SHALL BE COLOURED LILAC (P23) IN ACCORDANCE WITH AS 2700
- ALL PIPES, PIPE SLEEVES & IDENTIFICATION TAPES, IN ACCORDANCE WITH AS 1345, SHALL BE MARKED WITH THE FOLLOWING, WARNING: RECYCLED OR RECLAIMED - WATER - DO NOT DRINK

###### BELOW GROUND PIPES

- ALL BELOW GROUND PIPES SHALL HAVE AN IDENTIFICATION TAPE IN ACCORDANCE WITH CLAUSE GENERAL INSTALLED ON TOP OF THE WATER PIPELINE, RUNNING LONGITUDINALLY, & FASTENED TO THE PIPE AT NOT MORE THAN 3m INTERVALS.

###### OUTLET POINTS

- ALL OUTLET POINTS SHALL BE CLEARLY & PERMANENTLY MARKED 'WARNING: NOT FOR DRINKING' WITH SAFETY SIGNS TO COMPLY WITH AS 1319 & AS 1345.

###### PRE-TREATMENT

- ALL GUTTERS SHALL BE FITTED WITH PROPRIETARY GUTTER SCREENS IN ACCORDANCE WITH THE MANUFACTURERS SPECIFICATIONS
- BELOW-GROUND FIRST FLUSH DIVERTER SHALL BE INSTALLED TO ALL INLET PIPELINE(S) PRIOR TO ENTERING THE RAINWATER TANK. FIRST FLUSH DIVERTER TO BE SIZED BY THE HYDRAULIC CONSULTANT.
- REFER THE THE HYDRAULIC CONSULTANTS DRAWINGS FOR FURTHER DETAILS OF RAINWATER RE-USE PRE-TREATMENT MEASURES.

#### EROSION AND SEDIMENT CONTROL NOTES

##### GENERAL INSTRUCTIONS

- THIS PLAN IS TO BE READ IN CONJUNCTION WITH THE ENGINEERING PLANS, AND ANY OTHER PLANS OR WRITTEN INSTRUCTIONS THAT MAY BE ISSUED AND RELATING TO DEVELOPMENT AT THE SUBJECT SITE.
- THE SITE SUPERINTENDENT WILL ENSURE THAT ALL SOIL AND WATER MANAGEMENT WORKS ARE LOCATED AS INSTRUCTED IN THIS SPECIFICATION.
- ALL BUILDERS AND SUB-CONTRACTORS WILL BE INFORMED OF THEIR RESPONSIBILITIES IN MINIMISING THE POTENTIAL FOR SOIL EROSION AND POLLUTION TO DOWNSLOPE LANDS AND WATERWAYS.

##### CONSTRUCTION SEQUENCE

- THE SOIL EROSION POTENTIAL ON THIS SITE SHALL BE MINIMISED, HENCE WORKS SHALL BE UNDERTAKEN IN THE FOLLOWING SEQUENCE :
  - INSTALL SEDIMENT FENCES, TEMPORARY CONSTRUCTION EXIT AND SANDBAG KERB INLET SEDIMENT TRAP.
  - UNDERTAKE SITE DEVELOPMENT WORKS IN ACCORDANCE WITH THE ENGINEERING PLANS. PHASE DEVELOPMENT SO THAT LAND DISTURBANCE IS CONFINED TO AREAS OF WORKABLE SIZE.

##### EROSION CONTROL

- DURING WINDY CONDITIONS, LARGE UNPROTECTED AREAS WILL BE KEPT MOIST (NOT WET) BY SPRINKLING WITH WATER TO KEEP DUST UNDER CONTROL.
- FINAL SITE LANDSCAPING WILL BE UNDERTAKEN AS SOON AS POSSIBLE AND WITHIN 20 WORKING DAYS FROM COMPLETION OF CONSTRUCTION ACTIVITIES.

##### FENCING

- STOCKPILES WILL NOT BE LOCATED WITHIN 2 METRES OF HAZARD AREAS, INCLUDING LIKELY AREAS OF CONCENTRATED OR HIGH VELOCITY FLOWS SUCH AS WATERWAYS, WHERE THEY ARE BETWEEN 2 AND 5 METRES FROM SUCH AREAS. SPECIAL SEDIMENT CONTROL MEASURES SHOULD BE TAKEN TO MINIMISE POSSIBLE POLLUTION TO DOWNSLOPE WATERS, E.G. THROUGH INSTALLATION OF SEDIMENT FENCING.

- ANY SAND USED IN THE CONCRETE CURING PROCESS (SPREAD OVER THE SURFACE) WILL BE REMOVED AS SOON AS POSSIBLE AND WITHIN 10 WORKING DAYS FROM PLACEMENT.

- WATER WILL BE PREVENTED FROM ENTERING THE PERMANENT DRAINAGE SYSTEM UNLESS IT IS RELATIVELY SEDIMENT FREE, I.E. THE CATCHMENT AREA HAS BEEN PERMANENTLY LANDSCAPED AND/OR ANY LIKELY SEDIMENT HAS BEEN FILTERED THROUGH AN APPROVED STRUCTURE.


- TEMPORARY SOIL AND WATER MANAGEMENT STRUCTURES WILL BE REMOVED ONLY AFTER THE LANDS THEY ARE PROTECTING ARE REHABILITATED.

##### OTHER MATTERS

- ACCEPTABLE RECEPTORS WILL BE PROVIDED FOR CONCRETE AND MORTAR SLURRIES, PAINTS, ACID WASHINGS, LIGHT-WEIGHT WASTE MATERIALS AND LITTER.
- RECEPTORS FOR CONCRETE AND MORTAR SLURRIES, PAINTS, ACID WASHINGS, LIGHT-WEIGHT WASTE MATERIALS AND LITTER ARE TO BE EMPTIED AS NECESSARY. DISPOSAL OF WASTE SHALL BE IN A MANNER APPROVED BY THE SITE SUPERINTENDENT.

##### SITE INSPECTION & MAINTENANCE

- EROSION AND SEDIMENT CONTROL MEASURES SHALL BE INSPECTED AFTER RAINFALL EVENTS TO ENSURE THAT THEY OPERATE EFFECTIVELY. REPAIR AND OR MAINTENANCE SHALL BE UNDERTAKEN AS REQUIRED.



LOCALITY PLAN

#### CIVIL LEGEND

|  |   |
|--|---|
|  | NOMINAL 200 x 100 SANDSTONE BLOCK   |
|  | INDICATIVE DIRECTION OF FALL TO RWO OR PIT  |
|  | PROPOSED COVER LEVEL  |
|  | PROPOSED SURFACE LEVEL  |
|  | EXISTING SURFACE LEVEL  |
|  | RAINWATER OUTLET, Ø150 ROUND PUSH-IN FLOOR DRAIN, SPS R150SR4 OR APPROVED EQUIVALENT  |
|  | STORMWATER DRAINAGE STRUCTURE WITH NUMBER (REFER TO PLANS AND STORMWATER DRAINAGE STRUCTURES SCHEDULE)  |
|  | STORMWATER DRAINAGE LINE WITH: <ul style="list-style-type: none"> <li>USIL 10.00..... INVERT LEVEL UPSTREAM</li> <li>Ø375 RCP 2'..... PIPE SIZE AND MATERIAL CLASS</li> <li>1.0%..... PIPE GRADE</li> <li>10m..... PIPE LENGTH</li> <li>DSIL 9.90..... INVERT LEVEL DOWNSTREAM</li> </ul> |
|  | PROPOSED GRATED DRAIN <ul style="list-style-type: none"> <li>GD1 = ACO K5100 WITH CLASS B' HEELSAFE GRATE</li> <li>GD2 = ACO K200 WITH CLASS 'D' GRATE</li> </ul>   |
|  | REDUNDANT SERVICE TO BE REMOVED OR DECOMMISSIONED OVERLAND FLOW PATH  |
|  | DRAINAGE EASEMENT WIDTH AS SHOWN ON PLAN  |
|  | EXISTING 1m WIDE DRAINAGE EASEMENT  |
|  | CREST LINE  |

#### EXISTING SERVICES LEGEND

|  |                               |
|--|-------------------------------|
|  | EXISTING SEWER                |
|  | EXISTING GAS                  |
|  | EXISTING COMMUNICATIONS       |
|  | EXISTING STORMWATER           |
|  | EXISTING IN-GROUND ELECTRICAL |
|  | EXISTING OVERHEAD ELECTRICAL  |

#### DRAWING LIST

| DWG No. | DESCRIPTION                               | REVISION |
|---------|---|----------|
| C1.01   | COVER SHEET, LEGENDS AND NOTES            | A        |
| C1.05   | DETAILS - SHEET 1                         | A        |
| C1.06   | DETAILS - SHEET 2                         | A        |
| C3.00   | EXISTING SERVICES AND SURVEY PLAN         | A        |
| C3.01   | CIVIL WORKS PLAN                          | A        |
| C3.15   | CATCHMENT PLAN                            | A        |
| C5.01   | SOIL EROSION AND SEDIMENT CONTROL PLAN    | A        |
| C5.02   | SOIL EROSION AND SEDIMENT CONTROL DETAILS | A        |

#### SOIL EROSION AND SEDIMENT CONTROL LEGEND

|  |   |
|--|---|
|  | MOBILE SEDIMENT TANK  |
|  | FILTER FABRIC DROP INLET PIT, PROVIDE AT ALL EXISTING SURFACE STORMWATER PITS |
|  | SEDIMENT FENCE  |
|  | SAND BAG SEDIMENT TRAP  |
|  | STABILISED CONSTRUCTION EXIT  |
|  | CUT OFF DRAIN   |
|  | ROCK CHECK DAM  |

#### DIAL BEFORE YOU DIG



IMPORTANT: THE CONTRACTOR IS TO MAINTAIN A CURRENT SET OF "DIAL BEFORE YOU DIG" DRAWINGS ON SITE AT ALL TIMES.

| ISSUE | AMENDMENT                         | DATE     | DRAWN | APP |
|-------|-----------------------------------|----------|-------|-----|
| A     | ISSUE FOR DEVELOPMENT APPLICATION | 17.04.24 | JL    | NP  |

CLIENT  
**THOMPSON HEALTH CARE**  
PO BOX 658  
GORDON NSW 2072  
PHONE : (02) 8467 9333

**THOMPSON HEALTH CARE**

ARCHITECT  
**BARTNETT ROYATO**  
90/47 MONA VALE RD  
MONA VALE NSW 2103  
PHONE : (02) 9979 4411


CIVIL CONSULTANT  
**ENTEC CONSULTANTS**

PROJECT  
**THOMPSON HEALTH BASSETT PROPOSED AGED CARE FACILITY**  
23 & 25 BASSETT STREET,  
MONA VALE, N.S.W. 2103

NORTH POINT

| DRAWING TITLE                  |             |             |    |          |      |
|--------------------------------|-------------|-------------|----|----------|------|
| COVER SHEET, LEGENDS AND NOTES |             |             |    |          |      |
| DRAWN                          | DATE        | SCALE       | A1 | QA CHECK | DATE |
| JL                             | APRIL 24    | N/A         |    |          |      |
| DESIGNED                       | PROJECT NO. | DRAWING NO. |    | ISSUE    |      |
| NP                             | 230127      | C1.01       |    | A        |      |







SECTION 1  
SCALE 1:20

| MINIMUM INTERNAL PIT DIMENSIONS |     |      |
|---------------------------------|-----|------|
| "D"                             | "X" | "Y"  |
| D < 600                         | 450 | 450* |
| D < 900                         | 600 | 600* |
| D < 1200                        | 600 | 900  |
| D > 1200                        | 900 | 900  |

NOTE  
PITS DENOTED \* SHALL BE USED ONLY WHERE SPECIFIED IN DRAINAGE SCHEDULE OR ON PLAN.




PIT EDGE DETAIL "A"  
SCALE 1:10




TYPICAL OCEANGUARD ARRANGEMENT DETAIL - SURFACE INLET TREATMENT

NOT TO SCALE  
NOTE: REFER TO MANUFACTURER'S DRAWINGS FOR OCEANGUARD FILTER ARRANGEMENT AND COMPONENTS DETAILS




TYPICAL OCEANGUARD ARRANGEMENT DETAIL - DOWNPIPE CONNECTION / DROP PIT


NOT TO SCALE  
NOTE: REFER TO MANUFACTURER'S DRAWINGS FOR OCEANGUARD FILTER ARRANGEMENT AND COMPONENTS DETAILS



PLAN




TYPICAL PIT CORNER DETAIL  
SCALE 1:20




PIT EDGE DETAIL "C"  
SCALE 1:10


SURFACE INLET/JUNCTION PIT 'TYPE A'  
SCALE 1:20




GRADED DRAIN SECTION 03  
SCALE 1:10 (C3.01)




GRADED DRAIN TYPE 'A'  
SCALE 1:10



STEP IRON DETAIL  
N.T.S.




SECTION 2  
SCALE 1:20




SECTION 1  
SCALE 1:20

| SCHEDULE OF STORMWATER DRAINAGE STRUCTURES                             |  |   |
|--|--|---|
| PIT CLEAR INTERNAL DIMENSION SIZE AND TYPE                             | STRUCTURE NUMBER                           | NOTES   |
| 1.8m LINTEL KERB INLET PIT TYPE 'C' WITH CLASS 'D' GRATE AND FRAME     | A7   |   |
| 900 x 900 SURFACE INLET PIT TYPE 'A' WITH CLASS B GRATE AND FRAME      | A5, A6, B1, B2, B3, B4, B5, B6, C4, A8, E1 | PIT B2, B4 AND C4 TO BE CONSTRUCTED WITH OCEANGUARD FILTER BASKET, SURFACE INLET TREATMENT AS PER DETAILS   |
| 900 x 900 SURFACE INLET PIT TYPE 'A' WITH CLASS D GRATE AND FRAME      | C2, C5                                     | PITS C2, C5 TO BE CONSTRUCTED WITH OCEANGUARD FILTER BASKET. PROVIDE DROP PIT ARRANGEMENT FOR C2 AND SURFACE INLET TREATMENT FOR PIT C5. REFER TO DETAILS |
| 900 x 900 JUNCTION PIT TYPE 'A' WITH CLASS B GRATE AND FRAME           | A4, C1, E2                                 |   |
| 600 x 600 SURFACE INLET PIT TYPE 'A' WITH CLASS B GRATE AND FRAME      | A1, A2, A3, D1, G1                         |   |
| 600 x 600 SURFACE INLET PIT TYPE 'A' WITH CLASS D GRATE AND FRAME      | F1   |   |
| 2250Ø STORMWATER MANHOLE   | B7, C6                                     | REFER TO OCEAN PROTECT DRAWINGS AND SPECIFICATION FOR CONFIGURATION AND DETAILS   |
| EXISTING COUNCIL PIT TO BE INVESTIGATED FURTHER AT DETAIL DESIGN STAGE | A9   | COUNCIL PIT NO. SPP50073 (INFORMATION FROM NORTHERN BEACHES COUNCIL E-SERVICES)   |




RAINWATER OUTLET DETAIL  
SCALE 1:10



PLAN

KERB INLET PIT TYPE "C"  
SCALE 1:20



SECTION 3  
SCALE 1:20

| ISSUE | AMENDMENT                         | DATE     | DRAWN | APP |
|-------|-----------------------------------|----------|-------|-----|
| A     | ISSUE FOR DEVELOPMENT APPLICATION | 17.04.24 | JL    | NP  |

CLIENT  
**THOMPSON HEALTH CARE**  
PO BOX 658  
GORDON NSW 2072  
PHONE : (02) 8467 9333

ARCHITECT  
**BARTNETT ROVATO**  
ARCHITECTS  
90/47 MONA VALE RD  
MONA VALE NSW 2103  
PHONE : (02) 9979 4411

CIVIL CONSULTANT  
**ENTEC**  
CONSULTANTS

PROJECT  
**THOMPSON HEALTH BASSETT PROPOSED AGED CARE FACILITY**  
23 & 25 BASSETT STREET,  
MONA VALE, N.S.W. 2103

NORTH POINT


| DRAWING TITLE     |             |             |          |      |
|-------------------|-------------|-------------|----------|------|
| DETAILS - SHEET 1 |             |             |          |      |
| DRAWN             | DATE        | SCALE       | QA CHECK | DATE |
| JL                | APRIL 24    | 1:20        |          |      |
| DESIGNED          | PROJECT NO. | DRAWING NO. | ISSUE    |      |
| NP                | 230127      | C1.05       | A        |      |




**STORMFILTER DESIGN TABLE**

- STORMFILTER TREATMENT CAPACITY VARIES BY NUMBER OF FILTER CARTRIDGES INSTALLED.
- THE STANDARD CONFIGURATION IS SHOWN. ACTUAL CONFIGURATION OF THE SPECIFIED STRUCTURE(S) PER THE MANUFACTURER'S CERTIFYING ENGINEER WILL BE SHOWN ON SUBMITTAL DRAWING(S).
- FILTER CARTRIDGES SHALL BE MEDIA-FILLED, PASSIVE, SIPHON ACTUATED, RADIAL FLOW, AND SELF-CLEANING. RADIAL MEDIA DEPTH SHALL BE 178mm.


|   |     |
|---|-----|
| CARTRIDGE NAME / SIPHON HEIGHT (mm)       | 690 |
| CARTRIDGE PHYSICAL HEIGHT (mm)            | 840 |
| TYPICAL WEIR HEIGHT [H] (mm)              | 920 |
| CARTRIDGE FLOW RATE FOR PSORB MEDIA (L/s) | 0.9 |




**STORMFILTER CARTRIDGE DETAIL**




**TYPICAL EASEMENT CHANNEL ALONG EASTERN BOUNDARY SECTION**  
SCALE 1:20



**PLAN**




**TYPICAL EASEMENT CHANNEL ALONG SOUTH BOUNDARY SECTION**  
SCALE 1:20



**SECTION A-A**

**TYPICAL CARTRIDGE STORMFILTER SYSTEM MANHOLE DETAIL**  
NOT TO SCALE



**TYPICAL SECTION THROUGH SWALE**  
N.T.S.

| ISSUE | AMENDMENT | DATE | DRAWN | APP |
|-------|-----------|------|-------|-----|
|       |           |      |       |     |
|       |           |      |       |     |
|       |           |      |       |     |

CLIENT  
**THOMPSON HEALTH CARE**  
PO BOX 658  
GORDON NSW 2072  
PHONE : (02) 8467 9333

**THOMPSON HEALTH CARE**

ARCHITECT  
**BARTNETT ROVATO ARCHITECTS**  
90/47 MONA VALE RD  
MONA VALE NSW 2103  
PHONE : (02) 9979 4411

CIVIL CONSULTANT  
**ENTEC CONSULTANTS**


PROJECT  
**THOMPSON HEALTH BASSETT PROPOSED AGED CARE FACILITY**  
23 & 25 BASSETT STREET,  
MONA VALE, N.S.W. 2103

NORTH POINT

| DRAWING TITLE    |             |             |       |          |      |
|------------------|-------------|-------------|-------|----------|------|
| DETAIL - SHEET 2 |             |             |       |          |      |
| DRAWN            | DATE        | SCALE       | A1    | QA CHECK | DATE |
| JL               | APRIL 24    | N/A         |       |          |      |
| DESIGNED         | PROJECT NO. | DRAWING NO. | ISSUE |          |      |
| NP               | 230127      | C1.06       | A     |          |      |



**NOTE:**  
 EXISTING SITE SERVICES HAVE BEEN SHOWN INDICATIVELY ONLY AND BASED THE SITE SURVEY PREPARED BY BEE & LETHBRIDGE PTY LTD ON 14.11.2019



**DIAL BEFORE YOU DIG**

**DIAL BEFORE YOU DIG**  
 www.1100.com.au

IMPORTANT: THE CONTRACTOR IS TO MAINTAIN A CURRENT SET OF "DIAL BEFORE YOU DIG" DRAWINGS ON SITE AT ALL TIMES.

|   |                                   |          |    |    |  |
|---|-----------------------------------|----------|----|----|--|
|   |                                   |          |    |    |  |
|   |                                   |          |    |    |  |
|   |                                   |          |    |    |  |
| A | ISSUE FOR DEVELOPMENT APPLICATION | 17.04.24 | JL | NP |  |
|   | AMENDMENT                         |          |    |    |  |


CLIENT  
**THOMPSON HEALTH CARE**  
 PO BOX 658  
 GORDON NSW 2072  
 PHONE : (02) 8467 9333



ARCHITECT  
**BARTNERTROVATO ARCHITECTS**  
 90/47 MONA VALE RD  
 MONA VALE NSW 2103  
 PHONE : (02) 9979 4411

CIVIL CONSULTANT  
**ENTEC CONSULTANTS**

PROJECT  
**THOMPSON HEALTH BASSETT PROPOSED AGED CARE FACILITY**  
 23 & 25 BASSETT STREET,  
 MONA VALE, N.S.W. 2103




DRAWING TITLE  
**EXISTING SERVICES AND SURVEY PLAN**

|                |                       |                      |    |          |      |
|----------------|-----------------------|----------------------|----|----------|------|
| DRAWN<br>JL    | DATE<br>APRIL 24      | SCALE<br>N/A         | A1 | QA CHECK | DATE |
| DESIGNED<br>NP | PROJECT NO.<br>230127 | DRAWING NO.<br>C3.00 |    |          |      |










| WSUD CATCHMENT DETAILS   |                           |           |                |  |
|--------------------------|---------------------------|-----------|----------------|--|
| CATCHMENT                | TYPE                      | AREA (m2) | IMPERVIOUS (%) | REMARKS  |
| [Pink]                   | ROOF (60%)                | 2350      | 100            | DRAINING TO RAINWATER TANK & FILTER CARTRIDGES   |
|                          | ROOF (40%)                | 1390      | 100            | DRAINING TO FILTER CARTRIDGES                    |
| [Light Blue]             | TERRACE                   | 125       | 75             | DRAINING TO FILTER CARTRIDGES                    |
| [Light Orange]           | COURTYARD                 | 410       | 42             | DRAINING TO FILTER CARTRIDGES                    |
| [Light Green]            | LANDSCAPE                 | 400       | 0              | DRAINING TO FILTER CARTRIDGES                    |
| [Light Cyan]             | EASEMENT                  | 735       | 18             | BYPASS TREATMENT TRAIN                           |
| [Yellow]                 | ROAD                      | 255       | 100            | DRAINING TO FILTER BASKETS AND FILTER CARTRIDGES |
| [Purple]                 | DRIVEWAY TO BASEMENT      | 130       | 100            | PUMP OUT TO FILTER CARTRIDGES                    |
| [Green with cross-hatch] | LANDSCAPE, ROAD, TERRACES | 715       | 39             | DRAINING TO SWALES AND TO FILTER CARTRIDGES      |



**MUSIC MODEL**

ACHIEVED WATER QUALITY TARGETS AS PER NORTHERN BEACHES COUNCIL DCP REQUIREMENTS:

- GROSS POLLUTANT LOADS 90%
- TOTAL SUSPENDED SOLIDS 85%
- TOTAL PHOSPHORUS 65%
- TOTAL NITROGEN 45%

BASSETT STREET

|                                | Sources | Residual Load | % Reduction |
|--------------------------------|---------|---------------|-------------|
| Flow (ML/yr)                   | 6.8     | 6.31          | 7.3         |
| Total Suspended Solids (kg/yr) | 676     | 100           | 85.1        |
| Total Phosphorus (kg/yr)       | 1.69    | 0.479         | 71.6        |
| Total Nitrogen (kg/yr)         | 15      | 7.42          | 50.5        |
| Gross Pollutants (kg/yr)       | 162     | 2.34          | 98.6        |

| ISSUE | AMENDMENT                         | DATE     | DRAWN | APP |
|-------|-----------------------------------|----------|-------|-----|
| A     | ISSUE FOR DEVELOPMENT APPLICATION | 17.04.24 | JL    | NP  |


CLIENT  
**THOMPSON HEALTH CARE**  
PO BOX 658  
GORDON NSW 2072  
PHONE : (02) 8467 9333



ARCHITECT  
**BARTNETT ROVATO ARCHITECTS**  
90/47 MONA VALE RD  
MONA VALE NSW 2103  
PHONE : (02) 9979 4411


CIVIL CONSULTANT  
**ENTEC CONSULTANTS**

PROJECT  
**THOMPSON HEALTH BASSETT PROPOSED AGED CARE FACILITY**  
23 & 25 BASSETT STREET,  
MONA VALE, N.S.W. 2103



| DRAWING TITLE  |             |             |       |          |
|----------------|-------------|-------------|-------|----------|
| CATCHMENT PLAN |             |             |       |          |
| DRAWN          | DATE        | SCALE       | A1    | QA CHECK |
| JL             | APRIL 24    | N/A         |       | DATE     |
| DESIGNED       | PROJECT NO. | DRAWING NO. | ISSUE |          |
| NP             | 230127      | C3.15       | A     |          |





INSTALL TEMPORARY ROCK CHECK DAMS TO CUT OFF SWALE AT APPROX. 20m CENTRES

CUTOFF SWALE DRAIN

BASEMENT WALL OUTLINE

PROVIDE MOBILE SEDIMENT CONTROL TANK SYSTEM IN ACCORDANCE WITH LANDCOM BLUE BOOK REQUIREMENTS

INSTALL TEMPORARY SEDIMENT FENCE TO BOUNDARY PERIMETER. REFER TO DETAIL ON DRAWING C5.02

INDICATIVE LOCATION OF STOCKPILE WITH WIND EROSION FENCE. EXACT LOCATION TBC ON SITE BY THE CONTRACTOR

CONSTRUCT TEMPORARY STABILISED CONSTRUCTION EXIT. EXACT LOCATION TO BE DETERMINED ON SITE BY THE CONTRACTOR. REFER TO DETAIL ON DRAWING C5.02

PROVIDE SANDBAG SEDIMENT TRAP. TYPICAL REFER TO DETAIL ON DRAWING C5.02

|   |                                   |          |    |    |  |
|---|-----------------------------------|----------|----|----|--|
|   |                                   |          |    |    |  |
|   |                                   |          |    |    |  |
| A | ISSUE FOR DEVELOPMENT APPLICATION | 17.04.24 | JL | NP |  |
|   | AMENDMENT                         |          |    |    |  |


CLIENT  
**THOMPSON HEALTH CARE**  
PO BOX 658  
GORDON NSW 2072  
PHONE : (02) 8467 9333



ARCHITECT  
**BARTNERTROVATO**  
90/47 MONA VALE RD  
MONA VALE NSW 2103  
PHONE : (02) 9979 4411


CIVIL CONSULTANT  
**ENTEC**  
CONSULTANTS

PROJECT  
**THOMPSON HEALTH BASSETT PROPOSED AGED CARE FACILITY**  
23 & 25 BASSETT STREET,  
MONA VALE, N.S.W. 2103



|   |                       |                      |    |          |            |
|---|-----------------------|----------------------|----|----------|------------|
| DRAWING TITLE<br>SOIL EROSION AND SEDIMENT CONTROL PLAN |                       |                      |    |          |            |
| DRAWN<br>JL   | DATE<br>APRIL 24      | SCALE<br>N/A         | A1 | QA CHECK | DATE       |
| DESIGNED<br>NP  | PROJECT NO.<br>230127 | DRAWING NO.<br>C5.01 |    |          | ISSUE<br>A |






**CONSTRUCTION NOTES**

1. CONSTRUCT SEDIMENT FENCE AS CLOSE AS POSSIBLE TO PARALLEL TO THE CONTOURS OF THE SITE.
2. DRIVE 1.5m LONG STAR PICKETS INTO GROUND, 2.5 METRES APART (MAX). ENSURE STAR PICKETS ARE FITTED WITH SAFETY CAPS.
3. DIG A 150mm DEEP TRENCH ALONG THE UPSLOPE LINE OF THE FENCE FOR THE BOTTOM OF THE FABRIC TO BE ENTRENCHED.
4. BACKFILL TRENCH OVER BASE OF FABRIC.
5. FIX SELF-SUPPORTING GEOTEXTILE TO UPSLOPE SIDE OF POSTS WITH WIRE TIES OR AS RECOMMENDED BY GEOTEXTILE MANUFACTURER.
6. JOIN SECTIONS OF FABRIC AT A SUPPORT POST WITH A 150mm OVERLAP.

**SEDIMENT CONTROL FENCE**


N.T.S.



**SANDBAG KERB INLET SEDIMENT TRAP**

N.T.S.

**SOURCE:**  
MANAGING URBAN STORMWATER  
SOILS AND CONSTRUCTION. THIRD  
EDITION, AUGUST 1998 PRODUCED  
BY THE DEPARTMENT OF HOUSING




**CONSTRUCTION NOTES**

1. LOCATE STOCKPILE AT LEAST 5 METRES FROM EXISTING VEGETATION, CONCENTRATED WATER FLOWS, ROADS AND HAZARD AREAS.
2. CONSTRUCT ON THE CONTOUR AS A LOW, FLAT, ELONGATED MOUND.
3. WHERE THERE IS SUFFICIENT AREA TOPSOIL STOCKPILES SHALL BE LESS THAN 2 METERS IN HEIGHT.
4. REHABILITATE IN ACCORDANCE WITH THE SWMP/ESCP.
5. CONSTRUCT EARTH BANK (STANDARD DRAWING 5-2) ON THE UPSLOPE SIDE TO DIVERT RUN OFF AROUND THE STOCKPILE AND A SEDIMENT FENCE (STANDARD DRAWING 6-7) 1 TO 2 METRES DOWNSLOPE OF STOCKPILE.

**STOCKPILES**

N.T.S.

**NOTE**  
ENSURE THAT ALL UTILITY ASSETS ARE MAINTAINED AND PROTECTED AT ALL TIMES IN THE VICINITY OF THE TEMPORARY CONSTRUCTION EXIT



GEOTEXTILE FABRIC DESIGNED TO PREVENT INTERMIXING OF SUBGRADE AND BASE MATERIALS AND TO MAINTAIN GOOD PROPERTIES OF THE SUB-BASE LAYERS. THE GEOTEXTILE MAY BE WOVEN OR NEEDLE PUNCHED PRODUCT WITH A MINIMUM CBR BURST STRENGTH (A53706.4-90) OF 2500N.

**CONSTRUCTION NOTES**


1. STRIP TOPSOIL AND LEVEL SITE.
2. COMPACT SUBGRADE.
3. COVER AREA WITH NEEDLE-PUNCHED GEOTEXTILE.
4. CONSTRUCT 200mm THICK PAD OVER GEOTEXTILE USING 30mm SINGLE SIZE AGGREGATE.
5. CONSTRUCT HUMP IMMEDIATELY WITHIN BOUNDARY TO DIVERT WATER TO A SEDIMENT FENCE OR OTHER SEDIMENT TRAP WHERE THE SEDIMENT IS COLLECTED AND REMOVED.

**MAINTENANCE NOTES**


THE EXIT SHALL BE MAINTAINED IN A CONDITION WHICH PREVENTS TRACKING OR FLOWING OF SEDIMENT OFF THE CONSTRUCTION SITE. THIS MAY REQUIRE PERIODIC TOP DRESSING WITH ADDITIONAL GRAVEL AS CONDITIONS DEMAND AND REPAIR AND/OR CLEANOUT OF ANY MEASURES USED TO TRAP SEDIMENT. ALL SEDIMENT SPILLED, DROPPED, WASHED OR TRACKED OFF THE CONSTRUCTION SITE MUST BE REMOVED IMMEDIATELY.

**TEMPORARY STABILISED CONSTRUCTION EXIT**

N.T.S.




**SANDBAG SEDIMENT TRAP - AT KERB SAG PIT**



**SANDBAG SEDIMENT TRAP - AT OTHER THAN KERB SAG PIT**

**SANDBAG SEDIMENT TRAP DETAILS**

N.T.S.



**INLET TRAP**

N.T.S.

**NOTE**  
TO BE USED IN PAVED AREAS WHERE TRAFFIC ACCESS IS REQUIRED

|   |                                   |          |    |    |  |
|---|-----------------------------------|----------|----|----|--|
|   |                                   |          |    |    |  |
|   |                                   |          |    |    |  |
|   |                                   |          |    |    |  |
|   |                                   |          |    |    |  |
| A | ISSUE FOR DEVELOPMENT APPLICATION | 17.04.24 | JL | NP |  |
|   | AMENDMENT                         |          |    |    |  |

CLIENT  
**THOMPSON HEALTH CARE**  
GORDON NSW 2072  
PHONE : (02) 8467 9333

**THOMPSON HEALTH CARE**

ARCHITECT  
**BARTNETT ROYATO ARCHITECTS**  
90/47 MONA VALE RD  
MONA VALE NSW 2103  
PHONE : (02) 9979 4411

CIVIL CONSULTANT  
**ENTECC CONSULTANTS**

PROJECT  
**THOMPSON HEALTH BASSETT PROPOSED AGED CARE FACILITY**  
23 & 25 BASSETT STREET,  
MONA VALE, N.S.W. 2103

NORTH POINT

|   |                       |                      |    |            |      |
|---|-----------------------|----------------------|----|------------|------|
| DRAWING TITLE<br><b>SOIL EROSION AND SEDIMENT CONTROL DETAILS</b> |                       |                      |    |            |      |
| DRAWN<br>JL   | DATE<br>APRIL 24      | SCALE<br>N/A         | AT | QA CHECK   | DATE |
| DESIGNED<br>NP  | PROJECT NO.<br>230127 | DRAWING NO.<br>C5.02 |    | ISSUE<br>A |      |

Appendix B – Council Water Management Referral Response (26/11/2020)

## Water Management Referral Response

|  |  |
|--|--|
| <b>Application Number:</b>             | DA2020/0816  |
| <b>Date:</b>                           | 26/11/2020   |
| <b>To:</b>                             | Adam Croft   |
| <b>Land to be developed (Address):</b> | Lot 38 DP 7236 , 23 Bassett Street MONA VALE NSW 2103<br>Lot 2 DP 748426 , 33 Bassett Street MONA VALE NSW<br>2103 |

### Reasons for referral

Council's Water Management Officers are required to consider the likely impacts.

### Officer comments

#### Referral comments 18/11/20 - recommended for approval

The applicant has provided revised stormwater plans and a written response. The only change is to include two small swales.

Due to the highly impervious nature of the site and the water use expected from the large number of residents, the concern remains that this development does not meet Council's objectives for water sensitive urban design.

The applicant has claimed that biofiltration is not possible in flood-affected areas. Bio-filtration is designed to capture and treat flows during normal, small rainfall events and therefore they are suitable for use in flood-affected areas. The swales that have been added to the design do not make a significant difference to water quality due to their small area and the lack of roof catchment draining to them, but they will contribute to increased infiltration.

The applicant has claimed that rainwater/stormwater reuse is not possible in aged care due to infection risk. The Seniors SEPP specifies in Clause 36 that re-use should be incorporated where practical for second quality water uses (this includes toilets and laundry). The NSW Health guidelines for stormwater re-use state that rainwater/stormwater in aged care developments only needs to be treated to a very high level if being used for drinking. It is not accepted that re-use will create an unacceptable maintenance load.

While this proposal meets Council's requirements for water quality, it does not meet the requirements for water sensitive urban design. The addition of the swales is welcomed and must be retained, as infiltration is necessary to supplement flows to the coastal sands aquifer under the site.

The applicant is conditioned to include water re-use for toilets as a minimum (laundries should be included as well), which will reduce their consumption of potable water and the quantity of runoff from the site.

This referral supports the increase of deep soil landscaped area of the site wherever or however possible, as this will contribute to further infiltration of stormwater.

#### Referral comments 15/8/20

The applicant was provided with additional advice on what Council's expectations were for water management (email to Shebak Khan, ACOR Consultants):

"You will note that Pittwater 21 DCP B5.9 requires that you demonstrate application of water sensitive



urban design principles in your approach.

In the Northern Beaches, we consider the WSUD principles to be represented in development through:

1. Protecting and enhancing receiving environments
2. Appropriate treatment for reuse or discharge to receiving environments
3. Reducing potable water demand
4. Minimising wastewater generation and treating for reuse
5. Integrated vegetated stormwater treatment and harvesting systems into the landscape
6. Increased biodiversity, amenity and micro-climate benefits
7. Providing green infrastructure and green links.

While you have met the 'targets' for water quality, filters are not the best solution and may not remove as many pollutants (especially dissolved nutrients) as a vegetated device given equal maintenance conditions.

The design includes a 30kL rainwater tank. 1500sqm of landscaping typically requires 30kL water a year, perhaps less when a percentage of your landscaped area is paving, shaded, and the site is on the coast and receives a fair amount of rainfall. There is likely to be insufficient demand for the water in the external areas.

Filters are below ground and therefore owners cannot easily determine when they require maintenance.

The landscaping is all narrow strips around the perimeter of the lot, and is unlikely to provide any significant biodiversity or micro-climate benefits.

There is limited capacity to reduce potable water demand, and there is no recycling proposed.

There is no green infrastructure, although rainwater is being captured for use on landscaping.

To apply water sensitive design to a greater degree the development must consider one or more of the following:

- reduce their footprint to allow the incorporation of a vegetated stormwater device. This would need to be approximately 85sqm and could include swales, bio-retention strips alongside roads/paths. There are many ways to include treatment without having one large basin.
- Reuse rainwater internally for toilets and laundry and cooling towers (if used). Treatment is not required for any of these uses, and with the number of residents expected, will significantly increase reuse and reduce potable water demand.
- Incorporation of a roof garden, or green roof given the significant roof space available.

"

### **Referral comments 30/7/20**

The use of filter cartridges for the removal of stormwater pollutants is not accepted for this development. The lot is located over a coastal sands groundwater aquifer and infiltration is important to maintain a balance against sea water ingress. Filters also fail to remove dissolved nutrients, and do not meet other objectives of water sensitive urban design.

The applicant must incorporate a vegetated infiltration device that removes pollutants according to the targets GPT 90, TSS 85, TP 65, TN 45 and a MUSIC model file to allow Council to check the parameters used.

The proposal is therefore supported.

Note: Should you have any concerns with the referral comments above, please discuss these with the Responsible Officer.

### **Recommended Water Management Conditions:**

## **CONDITIONS TO BE SATISFIED PRIOR TO THE ISSUE OF THE CONSTRUCTION CERTIFICATE**

### **Detailed Design of Stormwater Treatment Measures**

A certificate from a Civil Engineer, stating that the stormwater treatment measures have been designed in accordance with the plans by ACOR Consultants, the conditions of the development consent and Council's Water Management for Development Policy.

The certificate shall be submitted to the Certifying Authority prior to the release of the Construction Certificate.

Reason: Protection of the receiving environment.

### **Roofwater re-use**

The applicant must capture roof water for use for toilet flushing, connecting to at least 50 percent of toilets within the building. Roof water may also be used to irrigate landscaping and internally for washing machines. All stormwater treatment measures must make provision for convenient and safe regular inspection, periodic cleaning, and maintenance.

Details demonstrating compliance are to be submitted to the Certifying Authority for approval prior to the issue of the Construction Certificate.

Reason: To reduce potable water consumption and decrease stormwater runoff to protect receiving catchments.

### **Dewatering permit**

A dewatering permit is required from Council's Catchment Team at [catchment@northernbeaches.nsw.gov.au](mailto:catchment@northernbeaches.nsw.gov.au) to dewater tailwater from the sediment settling tank to be used as part of the sediment and erosion controls. The dewatering permit will also cover any dewatering required due to tailwater collecting in excavations.

To obtain a permit, the following information must be contained in a dewatering management plan and provided to Council's Catchment Team. The dewatering management plan must be certified by a suitably qualified civil engineer who has membership of Engineers Australia and appears on the National Engineering Register (NER).

1. Preliminary testing of groundwater/tailwater must be conducted by a NATA accredited laboratory to establish a correlation between NTU and TSS. This will allow the use of grab sampling at short notice prior to planned discharges.
2. Grab samples must be collected **within 1 hour before planned discharge** that comply with the parameters in the table below.
3. The groundwater/tailwater to be discharged must be compliant with the water quality requirements below, the General Terms of Approval/Controlled Activity permit issued by WaterNSW (if applicable), Landcom's 'Managing Urban Stormwater: Soils and Construction' (2004) (Blue Book), Council's Compliance and Enforcement Policy and legislation including Protection of the Environment Operations Act 1997 and Contaminated Lands Act 1997.

#### **Water Quality (<one hour of planned discharge)**

---

Oil and grease, not visible

pH, 6.5-8.5

Total Suspended Solids (TSS), <50mg/L NTU from a meter/grab sample

---

4. All approvals, water discharges and monitoring results are to be documented and kept on site. Copies of all records shall be provided to the appropriate regulatory authority, including Council, upon request.
5. Tailwater must be discharged to the nearest stormwater pit in accordance with Council's Auspec1 Design Manual and must not spread over any road, footpath and the like. Discharge to the kerb and gutter will not be accepted. Where there is no stormwater pit within 100 metres of the site, Council's Catchment Team must be contacted to discuss alternative arrangements.

On receipt of a satisfactory dewatering management plan, Council's Catchment Team will issue a permit that will allow dewatering for up to one year.

A dewatering permit must be obtained from Council prior to the issue of the Construction Certificate.

Reason: Protection of the receiving environment

### **CONDITIONS TO BE COMPLIED WITH DURING DEMOLITION AND BUILDING WORK**

#### **Substitution of Stormwater Treatment Measure**

The substitution of an "equivalent" device for the stormwater treatment measure approved under the Development Consent must be submitted to the Principal Certifying Authority for approval prior to installation.

Reason: To ensure stormwater is appropriately managed and in accordance with the Water Management for Development Policy.

### **Installation and Maintenance of Sediment and Erosion Control**

Sediment and erosion controls must be installed in accordance with Landcom's 'Managing Urban Stormwater: Soils and Construction' (2004) and the Erosion and Sediment Control Plan prepared by ACOR Consultants.

Erosion and sediment controls are to be adequately maintained and monitored at all times, particularly after periods of rain, and shall remain in proper operation until all development activities have been completed and the site is sufficiently stabilised with vegetation.

Reason: To protect the surrounding environment from the effects of sedimentation and erosion from the site.

## **CONDITIONS WHICH MUST BE COMPLIED WITH PRIOR TO THE ISSUE OF THE OCCUPATION CERTIFICATE**

### **Certification for the Installation of Stormwater Treatment Measures**

A certificate from a Civil Engineer, who has membership to Engineers Australia and the National Engineers Register must be provided, stating that the stormwater treatment measures and rainwater reuse system have been installed in accordance with the plans prepared by ACOR Consultants. The certificate must confirm that stormwater treatment measures are completed, online, in good condition and are not impacted by sediment. Vegetated measures must exhibit an 80 percent survival rate of plantings.

The certificate shall be submitted to the Principal Certifying Authority prior to the release of the Occupation Certificate.

Reason: Protection of the receiving environment.

### **Positive Covenant, Restriction as to User and Registration of Encumbrances for Stormwater Treatment Measures**

A positive covenant shall be created on the title of the land requiring the proprietor of the land to maintain the stormwater treatment measures in accordance with the standard requirements of Council, the manufacturer and as required by the Stormwater Treatment Measures Operation and Maintenance Plan.

A restriction as to user shall be created on the title over the stormwater treatment measures, restricting any alteration to the measures.

The terms of the positive covenant and restriction as to user are to be prepared to Council's standard requirements (available from Council) at the applicant's expense and endorsed by the Northern Beaches Council's delegate prior to lodgement with the Department of Lands. Northern Beaches Council shall be nominated as the party to release, vary or modify such covenant.

A copy of the certificate of title demonstrating the creation of the positive covenant and restriction as to user is to be submitted to the Principal Certifying Authority prior to the issue of the final Occupation Certificate.

Reason: To identify encumbrances on land, ensure ongoing maintenance, and ensure modification to the stormwater treatment measures is not carried out without Council's approval.

### **Stormwater Treatment Measures Operation and Maintenance Plan**

An Operation and Maintenance Plan is to be prepared to ensure the proposed stormwater treatment measures remain effective.

The Plan must be attached to the Positive Covenant (and the community or strata management statement if applicable) and contain the following:

1. Detail on the stormwater treatment measures:

- a) Work as executed drawings
- b) Intent of the stormwater treatment measures including modelled pollutant removal rates
- c) Site detail showing catchment for each device
- d) Vegetation species list associated with each type of vegetated stormwater treatment measure
- e) Impervious area restrictions to maintain the water balance for the site
- f) Funding arrangements for the maintenance of all stormwater treatment measures
- g) Identification of maintenance and management responsibilities
- h) Maintenance and emergency contact information

2. Maintenance schedule and procedure - establishment period of one year following commissioning of the stormwater treatment measure:

- a) Activity description, and duration and frequency of visits  
Additionally for vegetated devices:
- b) Monitoring and assessment to achieve an 80 percent survival rate for plantings
- c) Management of weeds, pests and erosion, with weed and sediment cover limited to a maximum of 5 percent of the total area of the stormwater treatment measure

3. Maintenance schedule and procedure - ongoing

- a) Activity description, and duration and frequency of visits
- b) Routine maintenance requirements
- c) Work Health and Safety requirements
- d) Waste management and disposal
- e) Traffic control (if required)
- f) Renewal, decommissioning and replacement timelines and activities of all stormwater treatment measures (please note that a DA may be required if an alternative stormwater treatment measure is proposed)
- g) Requirements for inspection and maintenance records, noting that these records are required to be maintained and made available to Council upon request.

Details demonstrating compliance shall be submitted to the Principal Certifying Authority prior to the release of the Occupation Certificate.

Reason: Protection of the receiving environment.

### **Works as Executed Drawings - Stormwater Treatment Measures**

Works as Executed Drawings for the stormwater treatment measures must be prepared in accordance with Council's Guideline for Preparing Works as Executed Data for Council Stormwater Assets.

The drawings shall be submitted to the Principal Certifying Authority prior to the release of the Occupation Certificate.

Reason: Protection of the receiving environment.

### **Strata Management Statement**

The Strata Management Statement must specifically list the stormwater treatment measures that will be maintained under strata title. The statement must also reference the approved Stormwater Treatment Measure Operation and Maintenance Plan.

Details demonstrating compliance shall be submitted to the Principal Certifying Authority prior to the release of the **Occupation Certificate**.

Reason: To ensure maintenance of all stormwater management assets and protection of the receiving environment.

### **Installation of Water Efficient Fittings**

The following Water Efficiency Labelling and Standards (WELS) Scheme rated fittings must be installed:

- a) 4 star dual-flush toilets
- b) 3 star showerheads
- c) 4 star taps (for all taps other than bath outlets and garden taps)
- d) 3 star urinals
- e) 3.5 star washing machines
- f) 4 star dishwashers

A certificate from a licenced plumber shall be submitted to the Principal Certifying Authority prior to the release of the Occupation Certificate demonstrating compliance with this condition.

Reason: To conserve potable water.

### **Maintenance contract for stormwater filtration cartridges**

A minimum of a five-year contract with a suitably qualified provider is required for the maintenance of the stormwater filtration cartridges.

A copy of the maintenance contract must be submitted to the Principal Certifying Authority prior to the issue of the final Occupation Certificate.

Reason: To ensure maintenance of the stormwater treatment measures.

## **ON-GOING CONDITIONS THAT MUST BE COMPLIED WITH AT ALL TIMES**

### **Maintenance of Stormwater Treatment Measures**

Stormwater treatment measures and rainwater reuse systems must be maintained at all times in accordance with the Stormwater Treatment Measure Operation and Maintenance Plan, manufacturer's specifications to achieve the required stormwater quality targets for the development.

Vegetated stormwater treatment measures must maintain an 80 percent survival rate of plantings and limit weed cover to no more than 10 percent of the total area of the stormwater treatment measure.

Reason: Protection of the receiving environment.