## NatHERS Thermal Performance Specifications (BASIX Thermal Comfort) 5 Commonwealth Parade, Manly

These are the Specifications upon which the Certified Assessment is based. If details included in these Specifications vary from other drawings or written specifications, these Specifications shall take precedence. If only one specification option is detailed for a building element, that specification must apply to all instances of that element for the project.

Windows	Glass	Frame	U value	SHGC	Detail	
Default	Single glazed, clear	Aluminium	6.7	0.57	Generally for window types: Awning, bi-fold, casement, tilt 'n' turn	
Default	Single glazed, clear	Aluminium	6.7	0.70	Generally for window types: Sliding window/ door, double hung, fixed, louvre	
Default	Single glazed, low E High solar gain	Aluminium	5.4	0.58	To unit: 1 - all glazing (except glass blocks)	
Default	Single glazed, low E low solar gain	Aluminium	5.6	0.41	To unit: 3 - all west facing glazing	
Skylights	Glass	Frame	U value	SHGC	Detail	
Default	Single glazed, clear	Aluminium	7.3	0.79	All skylights	
External walls	Construction	Added Insulation		Detail		
Cavity brick		R 1.0		All exter	nal walls	
Internal walls	Construction	Added Insulation		Detail		
Brick plastered		None		Internal walls generally		
Brick plastered		R 1.5		To unit 1: walls adjoining car park, storage and lobby areas		
Framed		None		To unit 3: generally for internal walls for level 3		
Framed		R 2.5		To unit 3: level 3 internal walls adjoining roof void		
Floors	Construction	Added Insul	ation	Covering	g Detail	
Concrete		None		As per d	rawings Generally	
Concrete		R 1.5		As per d	rawings To units 1 and 2: floors over outside air or non- conditioned spaces – basement, services areas	
Ceilings	Construction	Added Insul	ation	Detail		
Plasterboard		None		Generally		
Plasterboard		R 1.5		To units 1 and 2: ceilings below roof		
Plasterboard R 3.0		To unit 3: ceilings below roof and roof space				
Roof	Construction	Added Insul	ation	Deta	iil	
Metal deck	etal deck (see above)					
Concrete		(see above)				

## Other Requirements

All exhaust fans and downlights (if installed) to be sealed to prevent air-infiltration



Certificate no.:
Assessor Name:
Accreditation no.:
Certificate date:
Dwelling Address:

0002593590 Robert Mallindine VIC/BDAV/12/1475 27 March 2018

5 Commonwealth Parade Manly, NSW 2095

www.nathers.gov.au

