

NatHERS and BASIX Assessment



Pittwater Design & Draft Proposed Residential Development

To be built at 1 Montauban Avenue, Seaforth NSW 2092

Issue	File Ref	Description	Author	Date
А	20-0988	NatHERS and BASIX Assessment	SF/DO	16/10/2020

This report has been prepared by Efficient Living Pty Ltd on behalf of our client Pittwater Design & Draft. Efficient Living prepares all reports in accordance with the BASIX Thermal Comfort Protocol and is backed by professional indemnity insurance. This report takes into account our Client's instructions and preferred building inclusions.





16 October 2020

Pittwater Design & Draft 1 Montauban Avenue, Seaforth

Report Contact: Daniel O'Neill, Sian Fishwick License Holder: Tracey Cools

Email: dan@efficientliving.com.au Accreditation Number: HERA10033

Prepared For:

Client Name: Pittwater Design & Draft Client Address: Mona Vale NSW 1660

Client Contact: Leigh Sym Client Phone: +61 422 050 001

Client Email: info@pittwaterdd.com.au

Specification

Heating and cooling loads for the development have been determined using BERS Pro Plus 4.4 Thermal Comfort Simulation Software.

The following specification was used to achieve the thermal performance values. Modelling proxies are used at times and if the building element details vary the thermal performance specifications below shall take precedence.

If there is a change to this specification during design or construction, please contact Efficient Living for advice. If required, an updated Certificate will be issued.

BASIX Details

Dwelling A:

Conditioned area: $141.5m^2$ Heating Load: $37.1 \text{ MJ/m}^2/\text{pa}$ Un-conditioned area: $9.16m^2$ Cooling Load: $23.2 \text{ MJ/m}^2/\text{pa}$

Dwelling B (South Facing):

Conditioned area: 141.5m^2 Heating Load: $33.5 \text{ MJ/m}^2/\text{pa}$ Un-conditioned area: 9.16m^2 Cooling Load: $24.3 \text{ MJ/m}^2/\text{pa}$

Floors

Concrete slab on ground with R1.0 insulation

Suspended timber floors with R2.5 insulation (insulation only value) to open and enclosed suspended areas

Concrete between levels, R2.5 insulation to garage ceiling where habitable rooms above. No insulation to garage where roof/balcony above.

Timber between levels, no insulation required

External Walls

Brick veneer with R2.5 insulation (insulation only value)

Lightweight cladding on framed walls with R2.5 insulation (insulation only value)

Concrete Block to garage walls

Double Skin Brick (between dwellings)

Note: No insulation is required to external Garage walls

External Colour:

Light (SA < 0.475)

Walls within dwellings



16 October 2020

Pittwater Design & Draft 1 Montauban Avenue, Seaforth

Plasterboard on studs, no insulation required

Single skin brick with R2.0 insulation only required to walls between garage and internal conditioned areas.

Glazing Doors/Windows

Unit A all windows:

U-value: 4.9 (equal to or lower than) SHGC: 0.33 (±10%)

Unit B all windows:

U-value: 2.2 (equal to or lower than) SHGC: 0.32 (±10%)

Given values are AFRC total window system values (glass and frame)

Note: BASIX Thermal Comfort Protocol Table 3 SHGC value of the unit should be within +/-10% of the value specified for the default window selection on the certificate.

Skylights

Fixed 1800x900mm:

U-value: 2.6 and SHGC: 0.24

Roof and Ceilings

Concrete roof, no insulation to garage

Metal roof with foil backed blanket (R_u 1.3 and R_d 1.3) (ie. Bradfords Anticon 60)

Plasterboard ceiling with R4 (Unit B), R3.5 (Unit A) insulation (insulation only value) where roof above or balcony above

Ceiling insulation require to verandah or porch where connected to main roof cavity or barrier provided

External Colour

Medium (0.475 < SA < 0.7)

Ceiling Penetrations

Sealed LED downlights not to exceed NatHERS certificate

Sealed LED downlights, one every 2.5m2. Once lighting plan has been developed NatHERS certificate can be updated to improve specification.

Floor coverings

Carpet to bedrooms and study, tiles wet areas, timber composite elsewhere

External Shading

Shading as per stamped drawings

Ventilation

All external doors have weather seals, all exhaust fans and chimneys have dampers, and down lights proposed will have capped fittings

Nationwide House Energy Rating Scheme — Multiple Class1-dwelling summary NatHERS Certificate No. 0005303250

Generated on 16 Oct 2020 using BERS Pro v4.4.0.2 (3.21)

Property

Address 1 Montauban Avenue, Seaforth

NSW . 2092

Lot/DP 42/35319

NatHERS climate zone 56



Tracey Cools

Efficient Living Pty Ltd

admin@efficientliving.com.au

02 9970 6181

Accreditation No.

Assessor Accrediting Organisation

HERA



Verification

To verify this certificate, scan the QR code or visit hstar.com.au/QR/Generate?p=ReqhJnhok When using either link, ensure you are visiting hstar.com.au

Summary of all dwellings

Certificate number and link	Unit Number	Heating load (MJ/m ² /p.a.)	Cooling load (MJ/m ² /p.a.)	Total load (MJ/m ² /p.a.)	Star rating
0005303169-01	Α	37.1	23.2	60.3	5.4
0005303185-01	В	33.5	24.3	57.8	5.5

National Construction Code (NCC) requirements

The NCC's requirements for NatHERS-rated buildings are detailed in 3.12.0(a)(i) and 3.12.5 of the NCC Volume Two. For apartments the requirements are detailed in J0.2 and J5 to J8 of the NCC Volume One.

In NCC 2019, these requirements include minimum star ratings and separate heating and cooling load limits that need to be met by buildings and apartments through the NatHERS assessment. Requirements additional to the NatHERS assessment that must also be satisfied include, but are not limited to: insulation installation methods, thermal breaks, building sealing, water heating and pumping, and artificial lighting requirements. The NCC and NatHERS Heating and Cooling Load Limits (Australian Building Codes Board Standard) are available at www.abcb.gov.au.

State and territory variations and additions to the NCC may also apply.







Explanatory Notes

About this report

This is a summary of NCC Class 1 dwellings in a development. The individual dwellings' ratings are a comprehensive, dynamic computer modelling evaluation of a home, using the floorplans, elevations and specifications to estimate the energy load. It addresses the building layout, orientation and fabric (i.e. walls, windows, floors, roofs and ceilings), but does not cover the water or energy use of appliances, or energy production of solar panels. For more details about an individual dwelling's assessment, refer to the individual dwelling's NatHERS Certificate (accessible via link).

Accredited Assessors

To ensure the NatHERS Certificate is of a high quality, always use an accredited or licenced assessor. NatHERS accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO). AAOs have specific quality assurance processes in place, and continuing professional development requirements, to maintain a high and consistent standard of assessments across the country.

Any questions or concerns about this report should be directed to the assessor in the first instance. If the assessor is unable to address these questions or concerns, the AAO specified on the front of this certificate should be contacted.

Disclaimer

The format of the NatHERS Certificate was developed by the NatHERS Administrator. However the content, input and creation of the NatHERS Certificate is by the assessor. It is the responsibility of the assessor who prepared this certificate to use NatHERS accredited software correctly and follow the NatHERS Technical Notes to produce a NatHERS Certificate.



Building Sustainability Index www.basix.nsw.gov.au

Multi Dwelling

Certificate number: 1145014M

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.basix.nsw.gov.au

Secretary

Date of issue: Friday, 16 October 2020

To be valid, this certificate must be lodged within 3 months of the date of issue.



Project summary					
Project name	1 Montauban Avenue,				
Street address	1 Montauban Avenue Seaforth 2092				
Local Government Area	Northern Beaches Council				
Plan type and plan number	deposited 35319				
Lot no.	42				
Section no.	-				
No. of residential flat buildings	0				
No. of units in residential flat buildings	0				
No. of multi-dwelling houses	2				
No. of single dwelling houses	0				
Project score					
Water	✓ 41 Target 40				
Thermal Comfort	✓ Pass Target Pass				
Energy	✓ 63 Target 50				

Certificate	Prepared by
-------------	-------------

Name / Company Name: Efficient Living Pty Ltd

ABN (if applicable): 82116346082

BASIX Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_12_7 Certificate No.: 1145014M Friday, 16 October 2020 page 1/12

Description of project

BASIX

Project address	
Project name	1 Montauban Avenue,
Street address	1 Montauban Avenue Seaforth 2092
Local Government Area	Northern Beaches Council
Plan type and plan number	deposited 35319
Lot no.	42
Section no.	-
Project type	
No. of residential flat buildings	0
No. of units in residential flat buildings	0
No. of multi-dwelling houses	2
No. of single dwelling houses	0
Site details	
Site area (m²)	689.9
Roof area (m²)	216
Non-residential floor area (m²)	0.0
Residential car spaces	4
Non-residential car spaces	0

Common area landscape	
Common area lawn (m²)	0.0
Common area garden (m²)	0.0
Area of indigenous or low water use species (m²)	0.0
Assessor details	
Assessor number	HERA10033
Certificate number	0005303250
Climate zone	56
Project score	
Water	✓ 41 Target 40
Thermal Comfort	✓ Pass Target Pass
Energy	✓ 63 Target 50

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_12_7 Certificate No.: 1145014M Friday, 16 October 2020 page 2/12

Description of project

The tables below describe the dwellings and common areas within the project

Multi-dwelling houses

BASIX

Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & lawn (m²)	Indigenous species (min area m²)
Α	3	140.0	53.0	157.6	0.0

Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & Iawn (m²)	Indigenous species (min area m²)
В	3	140.0	53.0	149.0	0.0

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_12_7 Certificate No.: 1145014M Friday, 16 October 2020 page 3/12



Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_12_7 Friday, 16 October 2020 page 4/12 Certificate No.: 1145014M

Schedule of BASIX commitments

- 1. Commitments for multi-dwelling houses
 - (a) Dwellings
 - (i) Water
 - (ii) Energy
 - (iii) Thermal Comfort
- 2. Commitments for single dwelling houses
- 3. Commitments for common areas and central systems/facilities for the development (non-building specific)
 - (i) Water
 - (ii) Energy

BASIX Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_12_7 Certificate No.: 1145014M Friday, 16 October 2020 page 5/12

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

1. Commitments for multi-dwelling houses

(a) Dwellings

(i) Water	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must comply with the commitments listed below in carrying out the development of a dwelling listed in a table below.			
(b) The applicant must plant indigenous or low water use species of vegetation throughout the area of land specified for the dwelling in the "Indigenous species" column of the table below, as private landscaping for that dwelling. (This area of indigenous vegetation is to be contained within the "Area of garden and lawn" for the dwelling specified in the "Description of Project" table).	~	~	
(c) If a rating is specified in the table below for a fixture or appliance to be installed in the dwelling, the applicant must ensure that each such fixture and appliance meets the rating specified for it.		•	V
(d) The applicant must install an on demand hot water recirculation system which regulates all hot water use throughout the dwelling, where indicated for a dwelling in the "HW recirculation or diversion" column of the table below.		•	V
(e) The applicant must install:			
(aa) a hot water diversion system to all showers, kitchen sinks and all basins in the dwelling, where indicated for a dwelling in the "HW recirculation or diversion" column of the table below; and		•	V
(bb) a separate diversion tank (or tanks) connected to the hot water diversion systems of at least 100 litres. The applicant must connect the hot water diversion tank to all toilets in the dwelling.		✓	V
(e) The applicant must not install a private swimming pool or spa for the dwelling, with a volume exceeding that specified for it in the table below.	V	~	
(f) If specified in the table, that pool or spa (or both) must have a pool cover or shading (or both).		~	
(g) The pool or spa must be located as specified in the table.	•	✓	
(h) The applicant must install, for the dwelling, each alternative water supply system, with the specified size, listed for that dwelling in the table below. Each system must be configured to collect run-off from the areas specified (excluding any area which supplies any other alternative water supply system), and to divert overflow as specified. Each system must be connected as specified.	~	~	~

BASIX Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_12_7 Certificate No.: 1145014M Friday, 16 October 2020 page 6/12

	Fixtures				Appliances Indivi			vidual pool		In	Individual spa			
Dwelling no.	All shower- heads	All toilet flushing systems	All kitchen taps	All bathroom taps	HW recirculation or diversion	All clothes washers	All dish- washers	Volume (max volume)	Pool cover	Pool location	Pool shaded	Volume (max volume)	Spa cover	Spa shaded
All dwellings	3 star (> 6 but <= 7.5 L/min)	4 star	5 star	5 star	no	-	-	-	-	-	-	-	-	-

	Alternative water source								
Dwelling no.	Alternative water supply systems	Size	Configuration	Landscape connection	Toilet connection (s)	Laundry connection	Pool top-up	Spa top-up	
All dwellings	individual water tank (no. 1)	Tank size (min) 2000.0 litres	To collect run-off from at least: 100.0 square metres of roof area;	yes	no	yes	no	no	
None	-	-	-	-	-	-	-	-	

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must comply with the commitments listed below in carrying out the development of a dwelling listed in a table below.			
(b) The applicant must install each hot water system specified for the dwelling in the table below, so that the dwelling's hot water is supplied by that system. If the table specifies a central hot water system for the dwelling, then the applicant must connect that central system to the dwelling, so that the dwelling's hot water is supplied by that central system.	~	~	~
(c) The applicant must install, in each bathroom, kitchen and laundry of the dwelling, the ventilation system specified for that room in the table below. Each such ventilation system must have the operation control specified for it in the table.		→	V
(d) The applicant must install the cooling and heating system/s specified for the dwelling under the "Living areas" and "Bedroom areas" headings of the "Cooling" and "Heating" columns in the table below, in/for at least 1 living/bedroom area of the dwelling. If no cooling or heating system is specified in the table for "Living areas" or "Bedroom areas", then no systems may be installed in any such areas. If the term "zoned" is specified beside an air conditioning system, then the system must provide for day/night zoning between living areas and bedrooms.		~	~

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_12_7 Certificate No.: 1145014M Friday, 16 October 2020 page 7/12

BASIX

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(e) This commitment applies to each room or area of the dwelling which is referred to in a heading to the "Artificial lighting" column of the table below (but only to the extent specified for that room or area). The applicant must ensure that the "primary type of artificial lighting" for each such room in the dwelling is fluorescent lighting or light emitting diode (LED) lighting. If the term "dedicated" is specified for a particular room or area, then the light fittings in that room or area must only be capable of being used for fluorescent lighting or light emitting diode (LED) lighting.		~	~
(f) This commitment applies to each room or area of the dwelling which is referred to in a heading to the "Natural lighting" column of the table below (but only to the extent specified for that room or area). The applicant must ensure that each such room or area is fitted with a window and/or skylight.	~	~	V
(g) This commitment applies if the applicant installs a water heating system for the dwelling's pool or spa. The applicant must:			
(aa) install the system specified for the pool in the "Individual Pool" column of the table below (or alternatively must not install any system for the pool). If specified, the applicant must install a timer, to control the pool's pump; and		✓	
(bb) install the system specified for the spa in the "Individual Spa" column of the table below (or alternatively must not install any system for the spa). If specified, the applicant must install a timer to control the spa's pump.		✓	
(h) The applicant must install in the dwelling:			
(aa) the kitchen cook-top and oven specified for that dwelling in the "Appliances & other efficiency measures" column of the table below;		✓	
(bb) each appliance for which a rating is specified for that dwelling in the "Appliances & other efficiency measures" column of the table, and ensure that the appliance has that minimum rating; and		~	V
(cc) any clothes drying line specified for the dwelling in the "Appliances & other efficiency measures" column of the table.		•	
(i) If specified in the table, the applicant must carry out the development so that each refrigerator space in the dwelling is "well ventilated".		~	
(j) The applicant must install the photovoltaic system specified for the dwelling under the "Photovoltaic system" heading of the "Alternative energy" column of the table below, and connect the system to that dwelling's electrical system.	V	~	~

	Hot water	Bathroom ventilation system		Kitchen venti	ilation system	Laundry ventilation system		
Dwelling no.	Hot water system	Each bathroom	Operation control	Each kitchen	Operation control	Each laundry	Operation control	
All dwellings	gas instantaneous 6 star	individual fan, ducted to façade or roof	manual switch on/off	individual fan, ducted to façade or roof	manual switch on/off	individual fan, ducted to façade or roof	manual switch on/off	

BASIX Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_12_7 Certificate No.: 1145014M Friday, 16 October 2020 page 8/12

	Cooling Heating		ting	Artificial lighting						Natural lighting		
Dwelling no.	living areas	bedroom areas	living areas	bedroom areas	No. of bedrooms &/or study	No. of living &/or dining rooms	Each kitchen	All bathrooms/ toilets	Each laundry	All hallways	No. of bathrooms &/or toilets	Main kitche
All dwellings	ceiling fans + 1-phase airconditioning EER 3.0 - 3.5	ceiling fans + 1-phase airconditioning EER 3.0 - 3.5	1-phase airconditioning EER 3.5 - 4.0	1-phase airconditioning EER 3.5 - 4.0	3	2	yes	yes	yes	yes	3	yes

	Individual po	ool	Individual s	ра	Appliances & other efficiency measures							
Dwelling no.	Pool heating system	Timer	Spa heating system	Timer	Kitchen cooktop/oven	Refrigerator	Well ventilated fridge space	Dishwasher	Clothes washer	Clothes dryer	Indoor or sheltered clothes drying line	Private outdoor or unsheltered clothes drying line
All dwellings	-	-	-	-	gas cooktop & gas oven	-	yes	-	-	-	no	no

	Alternative energy
Dwelling no.	Photovoltaic system (min rated electrical output in peak kW)
All dwellings	1.0

(iii) Thermal Comfort	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must attach the certificate referred to under "Assessor details" on the front page of this BASIX certificate (the "Assessor Certificate") to the development application and construction certificate application for the proposed development (or, if the applicant is applying for a complying development certificate for the proposed development, to that application). The applicant must also attach the Assessor Certificate to the application for a final occupation certificate for the proposed development.			
(b) The Assessor Certificate must have been issued by an Accredited Assessor in accordance with the Thermal Comfort Protocol.			
(c) The details of the proposed development on the Assessor Certificate must be consistent with the details shown in this BASIX Certificate, including the details shown in the "Thermal Loads" table below.			

BASIX Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_12_7 Certificate No.: 1145014M Friday, 16 October 2020 page 9/12

(iii) Thermal Comfort	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(d) The applicant must show on the plans accompanying the development application for the proposed development, all matters which the Thermal Comfort Protocol requires to be shown on those plans. Those plans must bear a stamp of endorsement from the Accredited Assessor, to certify that this is the case.	~		
(e) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), all thermal performance specifications set out in the Assessor Certificate, and all aspects of the proposed development which were used to calculate those specifications.		~	
(f) The applicant must construct the development in accordance with all thermal performance specifications set out in the Assessor Certificate, and in accordance with those aspects of the development application or application for a complying development certificate which were used to calculate those specifications.		~	~
(g) Where there is an in-slab heating or cooling system, the applicant must:	V	~	V
(aa) Install insulation with an R-value of not less than 1.0 around the vertical edges of the perimeter of the slab; or			
(bb) On a suspended floor, install insulation with an R-value of not less than 1.0 underneath the slab and around the vertical edges of the perimeter of the slab.			
(h) The applicant must construct the floors and walls of the development in accordance with the specifications listed in the table below.	V	~	~

	Thermal loads				
Dwelling no.	Area adjusted heating load (in mJ/m²/yr)	Area adjusted cooling load (in mJ/m²/yr)			
A	37.1	23.2			
All other dwellings	33.5	24.3			

	Construction of floors and walls							
Dwelling no.	Concrete slab on ground(m²)	Suspended floor with open subfloor (m²)	Suspended floor with endclosed subfloor (m²)	Suspended floor above garage (m²)	Primarily rammed earth or mudbrick walls			
All dwellings	102	15	-	14	No			

BASIX Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_12_7 Certificate No.: 1145014M Friday, 16 October 2020 page 10/12

3. Commitments for common areas and central systems/facilities for the development (non-building specific)

(b) Common areas and central systems/facilities

(i) Water	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) If, in carrying out the development, the applicant installs a showerhead, toilet, tap or clothes washer into a common area, then that item must meet the specifications listed for it in the table.		~	V
(b) The applicant must install (or ensure that the development is serviced by) the alternative water supply system(s) specified in the "Central systems" column of the table below. In each case, the system must be sized, be configured, and be connected, as specified in the table.	~	~	~
(c) A swimming pool or spa listed in the table must not have a volume (in kLs) greater than that specified for the pool or spa in the table.	V	~	
(d) A pool or spa listed in the table must have a cover or shading if specified for the pool or spa in the table.		V	
(e) The applicant must install each fire sprinkler system listed in the table so that the system is configured as specified in the table.		~	V
(f) The applicant must ensure that the central cooling system for a cooling tower is configured as specified in the table.		V	V

Common area	Showerheads rating	Toilets rating	Taps rating	Clothes washers rating
All common areas	no common facility	no common facility	no common facility	no common laundry facility

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) If, in carrying out the development, the applicant installs a ventilation system to service a common area specified in the table below, then that ventilation system must be of the type specified for that common area, and must meet the efficiency measure specified.		~	~
(b) In carrying out the development, the applicant must install, as the "primary type of artificial lighting" for each common area specified in the table below, the lighting specified for that common area. This lighting must meet the efficiency measure specified. The applicant must also install a centralised lighting control system or Building Management System (BMS) for the common area, where specified.		~	~
(c) The applicant must install the systems and fixtures specified in the "Central energy systems" column of the table below. In each case, the system or fixture must be of the type, and meet the specifications, listed for it in the table.	V	~	V

BASIX Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_12_7 Certificate No.: 1145014M Friday, 16 October 2020 page 11/12

Notes

- 1. In these commitments, "applicant" means the person carrying out the development.
- 2. The applicant must identify each dwelling, building and common area listed in this certificate, on the plans accompanying any development application, and on the plans and specifications accompanying the application for a construction certificate / complying development certificate, for the proposed development, using the same identifying letter or reference as is given to that dwelling, building or common area in this certificate.
- 3. This note applies if the proposed development involves the erection of a building for both residential and non-residential purposes (or the change of use of a building for both residential and non-residential purposes). Commitments in this certificate which are specified to apply to a "common area" of a building or the development, apply only to that part of the building or development to be used for residential purposes.
- 4. If this certificate lists a central system as a commitment for a dwelling or building, and that system will also service any other dwelling or building within the development, then that system need only be installed once (even if it is separately listed as a commitment for that other dwelling or building).
- 5. If a star or other rating is specified in a commitment, this is a minimum rating.
- 6. All alternative water systems to be installed under these commitments (if any), must be installed in accordance with the requirements of all applicable regulatory authorities. NOTE: NSW Health does not recommend that stormwater, recycled water or private dam water be used to irrigate edible plants which are consumed raw, or that rainwater be used for human consumption in areas with potable water supply.

Legend

BASIX

- 1. Commitments identified with a " in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).
- 2. Commitments identified with a " in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.
- 3. Commitments identified with a " in the "Certifier check" column must be certified by a certifying authority as having been fulfilled. (Note: a certifying authority must not issue an occupation certificate (either interim or final) for a building listed in this certificate, or for any part of such a building, unless it is satisfied that each of the commitments whose fulfillment it is required to monitor in relation to the building or part, has been fulfilled).

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_12_7 Certificate No.: 1145014M Friday, 16 October 2020 page 12/12