BASIX°Certificate

Building Sustainability Index www.basix.nsw.gov.au

Alterations and Additions

Certificate number: A404903

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Alterations and Additions Definitions" dated 06/10/2017 published by the Department. This document is available at www.basix.nsw.gov.au

Secretary

Date of issue: Tuesday, 06, April 2021

To be valid, this certificate must be lodged within 3 months of the date of issue.



Professional Profe

Project address							
Project name	Justine and Adam						
Street address	10 BERTANA Crescent WARRIEWOOD 2102						
Local Government Area	Northern Beaches Council						
Plan type and number	Deposited Plan 233448						
Lot number	17						
Section number							
Project type							
Dwelling type	Separate dwelling house						
Type of alteration and addition	My renovation work is valued at \$50,000 or more, and does not include a pool (and/or spa).						

Certificate Prepared by (please complete before submitting to Council or PCA)

Name / Company Name: JJDrafting

ABN (if applicable): 37 427 224 361

BASIX Certificate number: A404903 page 2 / 6

Fixtures and systems	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Lighting			
The applicant must ensure a minimum of 40% of new or altered light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting-diode (LED) lamps.		>	✓

BASIX Certificate number: A404903 page 3 / 6

Construction			Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Insulation requirements					
The applicant must construct the new or altered the table below, except that a) additional insula is not required for parts of altered construction	~	~	~		
Construction	Additional insulation required (R-value)	Other specifications			
suspended floor with open subfloor: framed (R0.7).	R0.8 (down) (or R1.50 including construction)				
external wall: framed (weatherboard, fibro, metal clad)	R1.30 (or R1.70 including construction)				
flat ceiling, flat roof: framed	ceiling: R2.08 (up), roof: foil backed blanket (55 mm)	medium (solar absorptance 0.475 - 0.70)			

BASIX Certificate number: A404903 page 4 / 6

	requirements						Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check			
Windows	and glazed do	ors										
					nading devices, in accordance with each window and glazed door.	the specifications listed in the table below.	✓	✓	✓			
The followi	ing requirements	must also	be satisf	ed in relation	to each window and glazed door:			✓	✓			
have a U-v	alue and a Solar	Heat Gair	n Coefficie	ent (SHGC) r		ed glass may either match the description, or, le below. Total system U-values and SHGCs		✓	✓			
					each eave, pergola, verandah, bal han 2400 mm above the sill.	cony or awning must be no more than 500 mm	✓	✓	✓			
Pergolas w	vith polycarbonate	e roof or s	imilar trar	slucent mate	erial must have a shading coefficien	nt of less than 0.35.		✓	✓			
External lo	ouvres and blinds	must fully	shade th	e window or	glazed door beside which they are	External louvres and blinds must fully shade the window or glazed door beside which they are situated when fully drawn or closed.						
shades a p	perpendicular wind	dow. The	spacing b	etween batte	ens must not be more than 50 mm.	ch they are situated, unless the pergola also		✓	✓			
shades a p	s and glazed	dow. The	spacing b	etween batte	ens must not be more than 50 mm.			✓	~			
shades a p	perpendicular wind	dow. The	spacing b	etween batte	ens must not be more than 50 mm.	ch they are situated, unless the pergola also		✓	✓			
Window / Win	s and glazed	dow. The doors g Area of glass inc. frame	lazing r Oversha Height	equirement adowing Distance	ens must not be more than 50 mm.			~	✓			
Windows Window / o	s and glazed of door Orientation	dow. The doors g Area of glass inc. frame (m2)	lazing r Oversha Height (m)	equirements adowing Distance (m)	ens must not be more than 50 mm. This Shading device eave/verandah/pergola/balcony	Frame and glass type standard aluminium, single clear, (or		~	\			
Windows Window / o no.	s and glazed of door Orientation	dow. The doors g Area of glass inc. frame (m2) 1.806	lazing r Oversha Height (m)	equirements adowing Distance (m)	ens must not be more than 50 mm. This Shading device eave/verandah/pergola/balcony >=900 mm eave/verandah/pergola/balcony	Frame and glass type standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75) standard aluminium, single clear, (or		~	\			
Window / ono. W01 W02	s and glazed of door Orientation SW SW	dow. The doors g Area of glass inc. frame (m2) 1.806	lazing r Oversha Height (m) 0	equirements adowing Distance (m) 0	ens must not be more than 50 mm. This Shading device eave/verandah/pergola/balcony >=900 mm eave/verandah/pergola/balcony >=900 mm eave/verandah/pergola/balcony	Frame and glass type standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75) standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75) standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			\			

BASIX Certificate number: A404903 page 5 / 6

Glazing requirements							Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Window / door									
no.		glass inc. frame (m2)	Height (m)	Distance (m)					
						U-value: 7.63, SHGC: 0.75)			
W06	NW	3.135	0	0	eave/verandah/pergola/balcony >=900 mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
W07	SW	2.755	0	0	eave/verandah/pergola/balcony >=600 mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
W08	SW	1.305	0	0	eave/verandah/pergola/balcony >=600 mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
W09a	W	1.015	0	0	eave/verandah/pergola/balcony >=750 mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
W09b	NW	1.55	0	0	external louvre/blind (adjustable)	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
W09c	N	1.015	0	0	eave/verandah/pergola/balcony >=750 mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			

BASIX Certificate number: A404903 page 6 / 6

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a " " in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a "

"in the "Show on CC/CDC plans & specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a "

"" in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate for the development may be issued.