BASIX Certificate

Building Sustainability Index www.basix.nsw.gov.au

Alterations and Additions

Certificate number: A365809

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Alterations and Additions Definitions" dated 06/10/2017 published by the Department. This document is available at www.basix.nsw.gov.au

Secretary

Date of issue: Tuesday, 10, December 2019

To be valid, this certificate must be lodged within 3 months of the date of issue.



Project address Project name Wcks Residence 32 Monserra Road Allambie Hrights 2100 Street address Local Government Area Northern Beaches Council Deposited Plan 241969 Plan type and number 3 Lot number Section number Project type Separate dwelling house Dwelling type Type of alteration and My renovation work is valued at \$50,000 or more, addition and does not include a pool (and/or spa).

Certificate Prepared by (please complete before submitting to Council or PCA)

Name / Company Name: Michael Airey Building Design & Drafting

ABN (if applicable): 26 769 291 556

escriptio

BASIX Certificate number: A365809 page 2 / 6

Fixtures and systems	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Lighting			
The applicant must ensure a minimum of 40% of new or altered light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting-diode (LED) lamps.		✓	~
Fixtures			
The applicant must ensure new or altered showerheads have a flow rate no greater than 9 litres per minute or a 3 star water rating.		✓	✓
The applicant must ensure new or altered toilets have a flow rate no greater than 4 litres per average flush or a minimum 3 star water rating.		✓	✓
The applicant must ensure new or altered taps have a flow rate no greater than 9 litres per minute or minimum 3 star water rating.		✓	

BASIX Certificate number: A365809 page 3 / 6

Construction			Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Insulation requirements					
The applicant must construct the new or altered construction (floor(s), walls, and ceilings/roofs) in accordance with the specifications listed in the table below, except that a) additional insulation is not required where the area of new construction is less than 2m2, b) insulation specified is not required for parts of altered construction where insulation already exists.					✓
Construction	Additional insulation required (R-value)	Other specifications			
external wall: brick veneer	R1.16 (or R1.70 including construction)				

BASIX Certificate number: A365809 page 4 / 6

	equirements						Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Windows	and glazed do	ors							•
The applicant must install the windows, glazed doors and shading devices, in accordance with the specifications listed in the table below. Relevant overshadowing specifications must be satisfied for each window and glazed door.							✓	~	✓
The following requirements must also be satisfied in relation to each window and glazed door:							✓	✓	
Each window or glazed door with standard aluminium or timber frames and single clear or toned glass may either match the description, or, have a U-value and a Solar Heat Gain Coefficient (SHGC) no greater than that listed in the table below. Total system U-values and SHGCs must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions.								✓	✓
For projections described in millimetres, the leading edge of each eave, pergola, verandah, balcony or awning must be no more than 500 mm above the head of the window or glazed door and no more than 2400 mm above the sill.							✓	✓	✓
Pergolas with polycarbonate roof or similar translucent material must have a shading coefficient of less than 0.35.								✓	✓
External louvres and blinds must fully shade the window or glazed door beside which they are situated when fully drawn or closed.								✓	V
shades a p	erpendicular wind	dow. The	spacing b	etween batte	ens must not be more than 50 mm.	ch they are situated, unless the pergola also		✓	✓
shades a p	erpendicular wind	dow. The	spacing b	etween batte	ens must not be more than 50 mm.			✓	~
shades a p	erpendicular wind	dow. The	spacing b	etween batte	ens must not be more than 50 mm.	Frame and glass type		✓	✓
windows Window / o	erpendicular wind	dow. The doors g Area of glass inc. frame	lazing r Oversha Height	etween batte equirement adowing Distance	ens must not be more than 50 mm.			~	✓
Windows Window / o	s and glazed of door Orientation	dow. The doors g Area of glass inc. frame (m2)	lazing r Oversha Height (m)	etween batte equirement adowing Distance (m)	ens must not be more than 50 mm. nts Shading device	Frame and glass type standard aluminium, single clear, (or		~	V
Windows Window / c no. W1	s and glazed of door Orientation	dow. The doors g Area of glass inc. frame (m2) 2.88	lazing r Oversha Height (m)	etween batte equirement adowing Distance (m) 0	ens must not be more than 50 mm. This Shading device external louvre/blind (adjustable)	Frame and glass type standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75) standard aluminium, single clear, (or		~	V
Windows Window / o no. W1 W2	s and glazed (door Orientation NE NW	dow. The doors g Area of glass inc. frame (m2) 2.88 0.82	Spacing be lazing r Overshat Height (m) 0	equirements adowing Distance (m) 0	ens must not be more than 50 mm. This Shading device external louvre/blind (adjustable) external louvre/blind (adjustable)	Frame and glass type standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75) standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75) standard aluminium, single toned, (or		~	

BASIX Certificate number: A365809 page 5 / 6

Glazing requirements							Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Window / door no.	Orientation	Area of glass inc. frame (m2)	Oversha Height (m)	Distance (m)	Shading device	Frame and glass type			
					>=900 mm	U-value: 7.63, SHGC: 0.75)			
D1	SW	9.18	0	0	eave/verandah/pergola/balcony >=900 mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
D2	SW	6.89	0	0	eave/verandah/pergola/balcony >=900 mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
W6	SE	1.66	0	0	none	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			

BASIX Certificate number: A365809 page 6 / 6

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a " " in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a "

"in the "Show on CC/CDC plans & specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a "

"" in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate for the development may be issued.