BASIX Certificate

Building Sustainability Index www.basix.nsw.gov.au

Alterations and Additions

Certificate number: A352868 02

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Alterations and Additions Definitions" dated 06/10/2017 published by the Department. This document is available at www.basix.nsw.gov.au

Secretarv Date of issue: Tuesday, 09, July 2019 To be valid, this certificate must be lodged within 3 months of the date of issue.



Desis et a sat	42 Ovinter Baad 00		
Project name	43 Quinton Road_02		
Street address	43 Quinton Road Manly 2095		
Local Government Area	Northern Beaches Council		
Plan type and number	Deposited Plan 1072958		
Lot number	1		
Section number			
Project type			
Dwelling type	Attached dwelling house		
Type of alteration and addition	My renovation work is valued at \$50,000 or mo and does not include a pool (and/or spa).		

Certificate Prepared by (please complete before submitting to Council or PCA)

Name / Company Name: Action Plans

ABN (if applicable): 17118297587

S **đ**1

Fixtures and systems	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Lighting			
The applicant must ensure a minimum of 40% of new or altered light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting-diode (LED) lamps.		×	~

Construction			Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Insulation requirements					
The applicant must construct the new or altered the table below, except that a) additional insular is not required for parts of altered construction	 ✓ 	~	~		
Construction	Additional insulation required (R-value)	Other specifications			
external wall: framed (weatherboard, fibro, metal clad)	R1.30 (or R1.70 including construction)				

Glazing requ	lirements						Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Windows and	d glazed do	ors							
The applicant must install the windows, glazed doors and shading devices, in accordance with the specifications listed in the table below. Relevant overshadowing specifications must be satisfied for each window and glazed door.								\checkmark	\checkmark
The following r	equirements i	must also	be satisfi	ed in relatior	n to each window and glazed door:			\checkmark	\checkmark
have a U-value	and a Solar	Heat Gair	Coefficie	ent (SHGC) r		d glass may either match the description, or, e below. Total system U-values and SHGCs		~	~
					e each eave, pergola, verandah, balo Than 2400 mm above the sill.	cony or awning must be no more than 500 mm	~	\checkmark	\checkmark
Pergolas with polycarbonate roof or similar translucent material must have a shading coefficient of less than 0.35.								~	\checkmark
External louvres and blinds must fully shade the window or glazed door beside which they are situated when fully drawn or closed.							~	~	
Pergolas with fixed battens must have battens parallel to the window or glazed door above which they are situated, unless the pergola also shades a perpendicular window. The spacing between battens must not be more than 50 mm.								\checkmark	\checkmark
Overshadowing buildings or vegetation must be of the height and distance from the centre and the base of the window and glazed door, as specified in the 'overshadowing' column in the table below.						~	\checkmark	\checkmark	
Windows ar	nd glazed o	doors g	azing r	equireme	nts		-		
Window / door	Orientation		Oversha	dowing	Shading device	Frame and glass type			
no.		glass inc. frame (m2)	Height (m)	Distance (m)					
W1	W	1.046	0	0	external louvre/blind (adjustable)	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
W2	W	4.28	10	4.7	eave/verandah/pergola/balcony >=450 mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
W3	S	1.716	0	0	eave/verandah/pergola/balcony >=450 mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
W4	S	1.858	0	0	eave/verandah/pergola/balcony	standard aluminium, single clear, (or			

Glazing requirements						Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check	
Window / door no.	Orientation	Area of glass inc.	Overshadowing Height Distance		Shading device	Frame and glass type			
		frame (m2)	(m)	(m)					
					>=450 mm	U-value: 7.63, SHGC: 0.75)			
W5	E	2.803	0	0	external louvre/blind (adjustabl	e) standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
W6	S	2.52	0	0	eave/verandah/pergola/balcon >=900 mm	y standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
D1	W	7.413	0	0	external louvre/blind (adjustabl	e) standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			
Skylights									
The applicant m	nust install the	e skylight	s in accor	dance with th	e specifications listed in the tab	le below.	\checkmark	~	~
The following re	quirements r	must also	be satisfi	ed in relation	to each skylight:			\checkmark	~
Each skylight may either match the description, or, have a U-value and a Solar Heat Gain Coefficient (SHGC) no greater than that listed in the table below.							~	~	
Skylights gla	azing requ	iiremen	ts						
Skylight numbe	er Area of g inc. fram		Shading	device	Frame a	Frame and glass type			
S1	0.44		no shad	ing		ım, moulded plastic single clear, (or U-value: IGC: 0.808)			
S2	0.44		no shading aluminium, moulded plastic single clear, (or U-value: 6.21, SHGC: 0.808)						

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a " / " in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a "
"
"
in the "Show on CC/CDC plans & specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a " " in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate for the development may be issued.