# **BASIX** Certificate

Building Sustainability Index www.basix.nsw.gov.au

## **Alterations and Additions**

Certificate number: A342658 02

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Alterations and Additions Definitions" dated 06/10/2017 published by the Department. This document is available at www.basix.nsw.gov.au

### Secretary

Date of issue: Friday, 29, May 2020

To be valid, this certificate must be lodged within 3 months of the date of issue.



# escription of project

Project address					
Project name	Roy_02				
Street address	26 Wabash Avenue Cromer 2099				
Local Government Area	Northern Beaches Council				
Plan type and number	Deposited Plan 1818				
Lot number	36				
Section number	2				
Project type					
Dwelling type	Separate dwelling house				
Type of alteration and addition	My renovation work is valued at \$50,000 or more, and includes a pool (and/or spa).				

Certificate Prepared by (please complete before submitting to Council or PCA)

Name / Company Name: Rapid Plans

ABN (if applicable): 43150064592

BASIX Certificate number: A342658\_02 page 2 / 6

Pool and Spa	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Rainwater tank			
The applicant must install a rainwater tank of at least 992 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	<b>~</b>	<b>✓</b>	~
The applicant must configure the rainwater tank to collect rainwater runoff from at least 228.25 square metres of roof area.		<b>✓</b>	✓
The applicant must connect the rainwater tank to a tap located within 10 metres of the edge of the pool.		✓	✓
Outdoor swimming pool		-	
The swimming pool must be outdoors.	<b>✓</b>	<b>✓</b>	~
The swimming pool must not have a capacity greater than 38 kilolitres.	✓	<b>✓</b>	✓
The swimming pool must have a pool cover.		<b>~</b>	✓
The applicant must install a pool pump timer for the swimming pool.		<b>✓</b>	✓
The applicant must install the following heating system for the swimming pool that is part of this development: gas.		✓	<b>✓</b>

BASIX Certificate number: A342658\_02 page 3 / 6

Fixtures and systems	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Lighting	'		'
The applicant must ensure a minimum of 40% of new or altered light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting-diode (LED) lamps.		<b>~</b>	<b>~</b>
Fixtures			
The applicant must ensure new or altered showerheads have a flow rate no greater than 9 litres per minute or a 3 star water rating.		<b>✓</b>	<b>✓</b>
The applicant must ensure new or altered toilets have a flow rate no greater than 4 litres per average flush or a minimum 3 star water rating.		<b>✓</b>	✓
The applicant must ensure new or altered taps have a flow rate no greater than 9 litres per minute or minimum 3 star water rating.		<b>✓</b>	

BASIX Certificate number: A342658\_02 page 4 / 6

Construction			Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Insulation requirements				'	
The applicant must construct the new or altered construction (floor(s), walls, and ceilings/roofs) in accordance with the specifications listed in the table below, except that a) additional insulation is not required where the area of new construction is less than 2m2, b) insulation specified is not required for parts of altered construction where insulation already exists.				<b>√</b>	<b>√</b>
Construction	Additional insulation required (R-value)	Other specifications			
concrete slab on ground floor.	nil				
suspended floor with enclosed subfloor: framed (R0.7).	R0.60 (down) (or R1.30 including construction)				
external wall: framed (weatherboard, fibro, metal clad)	R1.30 (or R1.70 including construction)				
raked ceiling, pitched/skillion roof: framed	ceiling: R1.74 (up), roof: foil backed blanket (75 mm)	medium (solar absorptance 0.475 - 0.70)			

BASIX Certificate number: A342658\_02 page 5 / 6

Glazing requ	irements						Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Windows and	glazed do	ors							
						the specifications listed in the table below.	<b>✓</b>	<b>✓</b>	<b>~</b>
The following re	ove the head of the window or glazed door and no more than 2400 mm above the sill.  It golas with polycarbonate roof or similar translucent material must have a shading coefficient of less than 0.35.  It golas with fixed battens must have battens parallel to the window or glazed door above which they are situated, unless the pergola all ades a perpendicular window. The spacing between battens must not be more than 50 mm.  Indows and glazed doors glazing requirements  Indow / door   Orientation   Area of   Overshadowing   Shading device   Frame and glass type						<b>✓</b>	✓	
have a U-value must be calcula	and a Solar accord	Heat Gair dance with	n Coefficion n Nationa	ent (SHGC) r I Fenestratio	no greater than that listed in the table n Rating Council (NFRC) conditions	le below. Total system U-values and SHGCs		~	<b>~</b>
	r projections described in millimetres, the leading edge of each eave, pergola, verandah, balcony or awning must be no more than 500 mr ove the head of the window or glazed door and no more than 2400 mm above the sill.					<b>✓</b>	✓	<b>✓</b>	
Pergolas with p	olycarbonate	roof or s	imilar trar	slucent mate	erial must have a shading coefficien	t of less than 0.35.		✓	✓
	Pergolas with fixed battens must have battens parallel to the window or glazed door above which they are situated, unless the pergola also shades a perpendicular window. The spacing between battens must not be more than 50 mm.					ch they are situated, unless the pergola also		✓	<b>✓</b>
Windows ar	d glazed o	doors g	lazing r	equireme	nts				
Window / door no.	Orientation	Area of glass inc. frame (m2)	Oversha Height (m)	Distance (m)	Shading device	Frame and glass type			
D2	NE	19.4	0	0	eave/verandah/pergola/balcony >=900 mm	improved aluminium, single clear, (U-value: 6.44, SHGC: 0.75)			
W1	SW	4.2	0	0	eave/verandah/pergola/balcony >=450 mm	improved aluminium, single clear, (U-value: 6.44, SHGC: 0.75)			
W2	SW	4.2	0	0	eave/verandah/pergola/balcony >=450 mm	improved aluminium, single clear, (U-value: 6.44, SHGC: 0.75)			

BASIX Certificate number: A342658\_02 page 6 / 6

### Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a " " in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a "

"in the "Show on CC/CDC plans & specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a "

" in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate for the development may be issued.