# FITZGERALD BUILDING CERTIFIERS PTY. LTD.

ABN 63 119 997 590 199 Pennant Hills Road Thomleigh NSW 2120 ph 9980 2155 fax 9980 2166 E mail admin@fitzgeralds com au

Juncil

# CONSTRUCTION CERTIFICATE PCA ENGAGEMENT - page 2 NOTICE OF COMMENCEMENT - page 2

Construction Certifica	te Number	сс	2008/263		Approval Da	te 22	22 06 08					
Issued in accordance with the provision	ons of the Environi	mental & Ass	sessment Act 1979 under S	ections 109C(1)	(b) and 109F							
Date Application Rece	ived		12 03 2008	12 03 2008								
Council		Pittwa	ter									
DEVELOPMENT CONS Name of Certifying Au Name of Accredited Co Accreditation Body	thority		590/07		APPROVAL DA Fitzgerald Build Paul Fitzgerald DIPNR, 20 Lee \$	ling Certifiers P - No BPB0119	-					
Address 7/8	Drafting - J 35 Pacific Pa 71 4353		n <b>kovec</b> ee Why NSW 2(	99								
Address 14	i <b>rìo Vieni</b> Hudson Par 18 0884	rade, Av	alon NSW 2107									
Subject Land Lot	8	DP	24003	No	14 Huds	on Parade, Avalo	חת					
Description of Develop	ment –		carport with decl	k cover								
Building Code of Austr	alıa Classıf	ication		10a	Value of Work	s <b>\$</b> 39,	000 00					
Builder DetailsNameEllLicence Number10Address6 NContact Number04	ola Plateau NSW	2107		SCANNE 2 9 SEP 200 ITTWATER COU	18							
			Approved	Plans								
Architectu	iral Plans p	repared	by		Drawing No	s	Dated					
JJ Draffting	F.			262 - DA1	to DA5 inclusive	<u> </u>	Sept 2007					
Stuctura	Engineer [	Details I	by		Drawing No	s	Dated					
Docherty Consulting Eng	ineers			S00 to S04		-	29 02 2008					
			R# 2	470	77							

## CERTIFICATION

I, Paul Fitzgerald, as the certifying authority am satisfied that,

.//

- (a) The requirements of the regulations referred to in s81A (5) have been complied with That is, work completed in accordance with the documentation accompanying the application for this certificate ( with such modifications verified by the certifying authority as may be shown on that documentation ) will comply with the requirements of the Regulation as referred to in section 81A (5) of the Act, and
- (b) Long Service Levy has been paid where required under s34 of the Building and Construction Industry Long Service Payments Act 1986

Signed		DATED	22 06 2008
	R		

## PRINCIPLE CERTIFYING AUTHORITY

Name of Certifying Authority	Fitzgerald Building Certifiers Pty Limited
Name of Accredited Certifier	Paul Fitzgerald
Accreditation Number	BPB0119
Contact Number	9980 2155
Address	199 Pennant Hills Rd, Thornleigh NSW 2120

### MANDATORY CRITICAL STAGE INSPECTIONS Class 1 & 10 Buildings

1 Commencement of Building Work	YES	
2 Piers prior to pour	N/A	
3 Footings prior to pouring of reinforced concrete	YES	
4 Timber frame prior to lining	YES	
5 Waterproofing of wet areas	N/A	
6 Stormwater pipes prior to backfilling	YES	
7 Pool Steel prior to pouring of reinforced concrete	N/A	
8 Pool Fence prior to water in the pool	N/A	
9 Final Inspection - issue of Occupation Certificate	YES	
PCA to State any additional inspections		
SIGNED	<b>Dated</b> 22 06 2008	

For Mr & Mrs VIENI 14 HUDSON PARADE, AVALON PROPOSED CARPORT AND BALCONY

# STRUCTURAL DRAWINGS

- S01 S02 S03 S04 00000 COVER SHEET
  - CONSTRUCTION NOTES
- LOWER GROUND FLOOR PLAN AND GROUND FLOOR PLAN & DETAILS ROOF PLAN AND DETAILS DETAILS



	DATI ISSI DISCRIFICION	29 02 08 0 ISSUE FOR CONSTRUCTION				
1-	Decherty Consuling English BF MF PF ng	building ( dde di Au; Edi e and/or relevant Australian/ind r ry trandard:	computence of use proper i incredy task and the provides and of the DochERTY CONSULTING ENGINEERS	ME (Structural) and I am oppropriately qualified to conify his structural	PLAN CERTIFICATION	
	Dartrity Consulting Engineers Ply Lid – AGN 74 0 ix/i – AGN 105 101 540 17 /rzac Anenui Collway N°W 2097 ph/tax (z. 927, -3812 email tybe dochen)e@b apond.com	Structural & Civil	DOCHERTY CONSULTING ENGINEERS			
	COVER SHEET	- FOF MF & MFS VIENI	14 HUDSON PARADE, AVALON	PROPOSED CARPORT AND BALCONY	Project	
	Scole Sheet Project No Drg No Rcv Showrn A3 80205 S00 0	29 02 08 CONSTRUCTION	Date Purpose of Issue	KRD K R DOCHERTY	Drawn Approved	

DAE	29 02 08								· · ·																				
			C6	2 C	Fo	PC	B	<u> s</u>	Ē	S				7	C2		<u>0</u> 2			G6		G5	G4	0	GJ	G2		വ വെ ലെ	
ISSUE 0	0				ootings	<u>Columns</u> Pedestals	Beams	Slabs	Element		Su	S S	st	0	000	N N	CONCRETE			TH S	shall In a	Dustr	₽₫	N N	₽ oł	All	a d	GENERAL G1 This othe such	
DESCRIPTION	ISSUE FOR CONSTRUCTION		ose lices sitio herw	hol	sp	als			otherwise shall be Formed Not expose	Clear	Suspended slab		uct	ncre	Cement shall be Typ	2 5 6	ĕ E		g Sp	e st	in a stable condition	structural drawings During construction	tabrication is commenced Dimensions shall not be c	<del>ال</del> ح د	din ≘	woi	d vc	cher d	
2	FOR		show t th ins s ins s	struction / where s Engineer holes, ch					Ise	concrete	Ided	n gr	ural	ete o	nt sh	urre	rkm	_	_ L	ruct	table	og Ira	sions	shall	relev	rk sl	the	rawır work other	
	ONST		e wi rein show appr	chas	JU	- υ	4	30	Shall For	rete	sa	OUD.	Elen	com	hall	nt e	ansh	Nind	)eck	ural	UPICO	)stru	s sh	be be	ions	hall	ION S	ng s ung s	
	RUCTI		on the force	oint: own	Ō	50 50	40	30	Formed	cover	0	а <u>-</u>	nent	pone	be ]	ditio	σ	Cla	floc	elei	ndit	ictio	all r	veri	reid	be _	irse sho	hall drav	
	N		ne s n pr emer n th d by	or e					ä			001	2+12	nts	ype 's	5 ns	nd r	ssific	ಳಷ ಕರ	neni	e n	n ∾ th	ot t	led		n with	l of	be Ing	
			nt s nt s e St the	spec	┿		$\left  \right $	_	e X	to re		0	2	and	"∧"	of A	nate	catic	a ř đ	N N	und	e st	ve o	befo	rent	cor	e ref	read an truc	
Do X	<b>5</b> 9	Roo ME	tural hall En En	ifical					Former exposed soil	einfo				quo	uni	S36(	rials	ă	ie fo	nowr	no	ruct	btaır	reo	set	All work shall be in accordance	during the course of construction and variations shall be referred to	d sp	
Kyre Pocinicity BF ME Pting Bachely Consulting Engines Pty Ltd		m a St (Struc (Struc	those shown on the structural drawings , shall be without the written prior approval of the Engineer Splices in reinforcement shall be made only in the positions shown on the Structural drawings or as otherwise approved by the Engineer	Construction joints shall be properly formed and used only where shown or specifically approved by the Engineer No holes, chases or embedment of pipes , other than	65	50	50	04	Formed	reinforcement unless	32	NN	Structural Element MPa minip		Contract documents Cement shall be Type "A" unless specified otherwise	with current editions of AS3600 except as varied by	<b>CRETE</b> All workmanship and materials shall be in accordance	 	have been designed for the following superimposed loads Deck floor load = 2.0 kPa	The structural elements shown on these drawings	stable condition and no part of the structure	structural drawings During construction the structure shall be maintained	tabrication is commenced Dimensions shall not be obtained by scaling the	work shall be verified before construction and	of all relevant and current SAA Codes All dimensions relevant to setting out and off-site	before proceeding with the work All work shall be in accordance with the requirements	during the course of construction All discrepa and variations shall be referred to the Engineer	RAL This drawing shall be read in conjunction with all other working drawings and specifications and with such other written instructions as may be issued	
marty Wiling En		orde of the	nade of t drav er	-ly fo ppro					or rain	lent		JUIC		shal	spec	хсер	u P	12	00	the	of.	shal	by s	ruct	odes	th t	te≥	unct catio	
ginces Pt		and I Engin hir proj Aurt of	the E wing:	ved ved	-					unle	80	80		be	ufied	ot as	e D		<pa supe<="" td=""><td>se o</td><td>the</td><td></td><td>scalır</td><td>ion</td><td>and</td><td>he r</td><td>All discrepancies the Engineer</td><td>ons be</td><td></td></pa>	se o	the		scalır	ion	and	he r	All discrepancies the Engineer	ons be	
y tid		PEAN PEAN Pect I h pect I h	shall be made Engineer ly in the s or as	, by a					Poured against membrane	SSS :			SIZe		oth	Var	acc		rimp	Irawi	stru	ma	ng ti	and	off	equi	ginee	and Issi	
ک		CFRTI ding th opriate hereby dovelop	l be neer the as	nd u	40	n/a	n/a	30 n / n	membrane	shown				as follows	ierwi	rled	ordo		ose	ngs	oture	Intai	ле	(	- sit	rem	er.	all with	
		TICATIO e quai state state	mo	used					linst	S	2400	2400	$\left(\frac{\text{kg/m3}}{3400}\right)$	SMO	Ise	ЪУ	Ince		ū		(D	ned		(	መ	ents	les	2	
h		N fied on fied to that the convent	1de	- [				1		1	10		U.V.	<u>د</u>															
/18	5	εινόματας τρατισμού ματοματιστη τοιακαίου πόχρου σύρεμας το αναστι το ματο από το προτευρατιστική μοτοιατοριστηρία το ποιρημοτοί τη αι στοιαστο ποιροματιστική το αναία αναστη τοιακασητοπό μοι τοιακαία το παρία τη του αναία αναστη τοιακασητοπό μαριστοιακατιστική το της Τριπτηριά το αναία αναστη τοιακασητοποί μαι τοι αναστη το ποιροματιστική το αναστη αναστη τοι αναστη τοι ποιροματιστική το αναστη αναστη τοι αναστη τοι ποιροματί το αναία αναστη τοι αναστη τοι αναστη τοι τοι αναστη τοι αναστη τοι αναστη τοι αναστη ποιροματί τοι αναστη αναστη τοι αναστη τοι αναστη τοι αναστη ποιροματί τοι αναστη αναστη τοι αναστη αναστη τοι αναστη τοι αναστη ποιροματί τοι αναστη αναστη τοι αναστη τοι αναστη τοι αναστη τοι αναστη ποιροματί τοι αναστη αναστη τοι αναστη τοι αναστη τοι αναστη τοι αναστη ποιροματί τοι αναστη αναστη τοι αναστη τοι αναστη τοι αναστη τοι αναστη τοι αναστη τοι αναστη ποιροματί τοι αναστη αναστη τοι αναστη αναστη τοι αναστη τοι αναστη τοι αναστη τοι αναστη τοι αναστη τοι αναστη ποιροματί τοι αναστη αναστη τοι αναστη τι αναστη τοι αναστη τοι	A1 EP	5 A		۶W	M2	:	A N			C14		C13	C N	3		C11		C10						60	80	C7 00	$\sum_{i=1}^{n}$
	0	(Civil) the str the str fovisions	<u> </u>		⊆⊐				<u>ن</u>	æ			ν, C				្ខុខ្		ਯੂ <b>≺</b>		= <u>-</u>	z	: ლ		Ś			z	ONSTRUCTION NOTE
	7	and uctural details t of th	<b>(Y AND MECHANI</b> After drilling hold remove all debris 'bottle' type stif by manufacturer	All mason Standards Masonry s by AS287 selections	nles	r be ricks	lasor	hall	NRY here	pr	lear p	e ke urin:	truct	labs	orizontal formv by the Engineer	nme	pplie oncr		Y12—400 Splice bars for 400mm	here		o of	, Xamj	S a	Symbols W G	All reinforcement All reinforcement	einfo	ETE Predst	$\sum_{i=1}^{i}$
- Dec 77			D drill e' t anuf	asor lards hry s 5287	ot	ams	עוק– עוק–	be	<u>n</u>	even	of v	co t t	tural	and	e yn Ca	diate	ete d (o	nore	for 400	tra		ba	ole Gro		e slo	Infor	saril	d fa Jred	
harty Con Anzac Av			MECHANIC rilling hole all debris type stiff type stiff	shall to	com	ed in	valls	evel,	50	t pl	et n	ncre	dra		Igine	y a	urf	Šē	400r	In SVE	h q t q	s' n	of d	Grade 200		.cem	nent y sh	bric bet Is n	דא
cnue (.al)		2 <i>000</i>	ANIC hole bris stiff	shall be sa	Ibre:	- ::: o al	sho	n sm	r T	astic	g pl	te c	wing	ams	er Wor	Ifter	nto ace.	shall	nm /	erse u	Size	gro	500 esigr	200	Alle 450	ent ent	own	spli weer	$\square$
Derherty Convuling Engineers Pty Ltd. (ABV 74 105-10) 540 - ACN 105-101-540 77 Anzoc Avenue (colorcy MSW 7037 juh/fax 02 9972 9812 encul Hye_docherty@appand		DOCHERTY CONSULTING ENGINEERS	(Y AND MECHANICAL ANCHORS After drilling holes for epoxy and mechanical anchors, remove all debris from hole using a combination of 'bottle' type stiff brushes and air pumps as specified by manufacturer	All masonry shall comply with AS3700 and Standards referenced within AS3700 Masonry shall be articulated where required by AS2870 to satisfy footing design selections	minimum compressive strength of 20 MPa unless otherwise noted	or beams until all propping has been removed Bricks used in load bearing construction shall have a	Masonry walls shall not be erected on sus	shall be level, smooth and covered with two layers of	n n n	to prevent plastic cracking in hot or windy conditions	rain protecting plastic sheeting and supports to clear of wet concrete, and also aliphatic alcohol	be kept 15mm clear from soffits of structure During concrete placing the builder shall have	structural drawings. All other building elements	sha	orizontal formwork shall be stripped	Immediately after removal of formwork	with Association where caring compound is used it must applied (a) onto slabs within 2 hours of finishing the concrete surface. (b) onto walls and columns	All concrete shall be placed and "cured"	Splice where necessary and lap with main 400mm	Where transverse tie bars are not shown, provide	nominal bar size in mm spacing in mm	- qué 1	N Grade 500 deformed bar Example of designation code for reinforciong bars	defe	Is F wire reinforcing fabric Grode 450 deformed wire	All reinforcement fabric shall be to AS1304 All reinforcement bars shall be to AS1302	Reinforcement is shown diagrammatically, it is not necessarily shown in true projection	CRETE Lapped fabric splices shall be so made that the measured between the outermost wires of each of fabric, is not less than the wire spacing plus	$\bigcirc$
7097 p		RTY	ANCH n ho shes	nply with foot	dstr	oppin	ot b		,, ,, ,,	ickin	. : an she	זים t	ti ot	ll be	nall		s wit	plac	e ⊓e	bars	, mL	17N20-350	in co	deformed	forci	sho	in di	shall e ou than	
BN /4 10 h/tox 02		CON	oxy and	in with	engti	ig ig g ig	e ero	100	n n	n g	eetin d al:	ne b	her	19	De	۲ ۹	o hin co	ed	cess	are	+ ) 1	) រ	ode ba	d bar	ng ≰_f	all b	proj	be term	$\bigcirc$
5 101 540 9972 981		SULT	and air	AS3 S37( Vhere desi	h of	as b onstr	acted	vere	3	hot	s g ar	tits	build s sn	n y	strip	form	12 ho	nd ,	ary	not	24 F S	Ϋ́	for H	bar	abric	e to	ectic	so i ost wir	Z
ACN 10		NG E	mec a c pum	9700 90 90 90	20	een ucti	on	L M	ncer	٩	id su	r sh	ling	onto			nd ours	cure	and	sho	paci	ar g	eınfo			AS1 AS1	ntica	e sp wire:	$\overline{}$
05 101 54 Me_do		ENGI	hanı omb	quire	MPo	nem s	SUS	th;	2	wind	rpbo	all r	elen	the	whe		colui	ٽم آ	lap	wn,	- bu	rade	orcio			302	ılly,	e th s of	$\sim$
i0 therty@big		VEER	cal inat as s	d A		ovec shall	spen	wo I	5	y co	rts	ture 1ave	hent	be	ر م		inish nns		with	prov	с Т	an	ng			4	it is	at t eac	$\square$
pond com	1		anch Ion speci	Australian		hav	ded	ayer	† D		h to		s sh	ams,	when approved		, E	ccor	m	vide	Ш	-bar grade and type	bars				not		μ
	ructure		hors, of cified	lian		e D	Masonry walls shall not be erected on suspended slabs	s of		ions	keep it sprcvs	site	shall	Slabs and beams shall bear only onto the beams, walls	/ed	L	g the	in accordance	ī			0e	I					overlap, sheet 25mm	$\mathcal{O}$
	Structural & Civil						S	00	Ď	Ĩ	β <del>1</del>																	л ф,	
	1	1	F2 F3	FOUNDATIONS F1 Footings and Site The foun pressure	77	ы Б	T4	L2	T2	TIME	S7		00 00	л Л	S U 4 U	202	S2	STRUCTURAL STEELWORK		B13	B12	B	-	,	88 88	86	88 54	BLOCKWORK B1 Blockwor B2 Concrete B3 Reinforc	
CONSTRUCTION NOTES	Drowing Tile	Projuci PRO 14 J For	lay	NDA Foc The	Des	Pro	Pro	50	∪se All	TIMBER FRAMING	A	spe	- In c	ste	Pro	٩ra			5			b V No			Use	Clea	Bor	Ren CKW	
STRI	T UC	Posi	npac acco plac plac ect	ting: fou	ign	° gal	vide	not	wort AS	FRA	welc	cific	tels,	elwo	vide		ess AS	JRAL	one	ere v	ere h	rodo	t 4-	core	ut eo	an o	cks	ORK ckwo icret	
UCTI	8	SON SON	rdan com ced fill o fill o	e an nda:	d S	vani	stru	use	indec intec	MING	s S	e ho	bea	rk s	25	300	0the	- ST	leng	verti		ling	1/2	s si	:esse	aneo	shall	e in	
NO	6	Proped PROPOSED CARPORT AND BALCONY 14 HUDSON PARADE, AVALON For Mr & Mrs VIENI	ub-ce v pact and ver	ive t	asec	sed	Provide structure bro	- tim	4 an 4 an	•,	nall	ns a	ms	steelwork supported on masonry	Provide 25 thick cement mortar	Gra	SIMJS	EELV	th		i on to	and an	par	al a	be b	d ou	etair be	bas bas	
NOT	TTTT I	RPORT ARADE,	ion subcorr subcorr	been lassi shat	on	fixin	re b	ber	nber A		be 6	ab DD s	colu	orted		de .	e no	NORK	o st	Dars	4 00	clec	ts be	be f	lock: Grad	ings t be	ווח Gra	be se st	
ES	ľ		shall AS appac	des ficat l be	roo	igs ∖	racir	uns	whe		mm	prop	nns	2 g	ign	350	04, 1	3	at d	are	Irs o	ncre	and p	illed	e S S	fore	de 1		
		AND BAI AVALON	95% 1280 be ted sh sh S% S		f m	where	nı pı	Jitab	20 a		COT	priat	par	ma	it m	for	all :	+	oubl	sho	re .	out		. vit	on Mo	gro	s vi 2 to	ccor be (	
		ALC	DD to so	sing of the second s	iteri	e n ex	0	e f	eau s ap		Itinu	e and	tty a	sonr	orta	hollo	;79 stru	2	e – U	Nn -	peq	bet	cem	) gr	th 1	ut f	AS	danc Grad	
		ANC	n a 5% 5% 0/e () 5%		ar si	pose	cord	or e	All workmanship and materials shall be with AS1684 and AS1720 as applicable Use treated timber where required for		sno	pa	sxpo:	~	Provide 25 thick cement mortar pad under	N NC	and ture	2	blo	appe	fied	ore	- 5 5	out .	utal J	n out openings shall be used in cleaned out before grout filling	Construct retaining walls with double Blocks shall be Grade 12 to AS2733	s <sup>⊎</sup> é 20 ≼	
			tanc SDD acec			dano	ance	sodx	for e		fille	nted	sed	2	. pad under	ectio	AS1 St	5	oks	ed, t	5'	dror	ີ 4 ີ - ມີ	 	bars	all	3 e U	ars o	
Shown	Soule OF	Drawn KRD Date	d re d re d ne		- OP	¥e ₩e	witt	ure	in c		all	ť	Lintels, beams columns partly exposed to the v	5	ıder	su(	163 9el :	5	n si	het	oth	ting	~2	9.09	aren	Clean out openings shall be used in all cores and cleaned out before grout filling	blo	XWORK Blockwork shall be in accordance with AS2733 Concrete in base shall be Grade 20 Reinforcement symbol S requires bars as Note	
	_		Compact sub-grade to 95% SDD (standard dry density) in accordance with AS 1289 Sub-grade soft spots observed during compaction shall be removed and replaced with select fill, placed and compacted to 95% SDD Select fill over subgrade shall be placed in 150mm (max) thick layers compacted to 95% SDD in accordance with AS1289	NDATIONS Footings have been designed for a beliffidy pressure of 100 and Site Soil Classification S in debitfidy pressure, of 100 The foundation shall be approved by the Engineer for this pressure and classification before placing concrete in thousand prosure and classification before placing concrete in the second	Design is based on roof material shown on the drawings	Provide structure tie down in accordance with AS1684 Use galvanised fixings where exposed to weather	Provide structure bracing in accordance with AS1684	Do not use timber unsuitable for exposure to moisture	All workmanship and materials shall be in accordance with AS1684 and AS1720 as applicable Use treated timber where required for durchility		roui	shall be not dip galvanised and painted to architect's specifications as appropriate	he w	, + ) ) - )			unit working and and and an		tack	bar r	Where horizontal bars are specified in both faces they shall be in standared courses	cor	All mortar shall be 1 part cement to 1/2 part lime and 4-1/2 parts sand (1 0.5 4.5)	. 0	Use recessed blocks for horizontal bars Grout shall be Grade 20 with 10mm anarenate and 230 slumn	es	cks	r33 ote	
A3 8	Sheet Project No. Dr.	Approvu K R Purpase	den oots ed w nm th A	ate 1	dra	aS16	5168	nois	rdan		nd (	nitec	veath				appli.	2	bon	may	SS	es d	- Ime		and			60	
8020t	innert C		sity) obs /ith (ma	in tr	<u>y</u> ng	00 4	4	ture	Ce		JNC	ts	her				cable	2	à	be			, v	5	2.30				
80205 S01	No Dr	Proved K R DOCHERTY	erve selec 39 ti		S						~						(D							2	<u>»</u>				
01 1	z	R.	hick a	¢ <u>x</u> D	L																			7	m				
0	š			-																									















