## **BASIX** Certificate

Building Sustainability Index www.basix.nsw.gov.au

## Alterations and Additions

Certificate number: A365760

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Alterations and Additions Definitions" dated 06/10/2017 published by the Department. This document is available at www.basix.nsw.gov.au

Secretarv

Date of issue: Friday, 10, January 2020 To be valid, this certificate must be lodged within 3 months of the date of issue.



Planning, Industry & Environment

Project address	
Project name	Wilson Terrey Hills
Street address	91 Booralie Road Terrey Hills 2084
Local Government Area	Northern Beaches Council
Plan type and number	Deposited Plan 752017
Lot number	106
Section number	
Section number Project type	
	Separate dwelling house

Certificate Prepared by (please complete before submitting to Council or PCA)

Name / Company Name: Michelle Walker Architect

ABN (if applicable): 15146642622

Fixtures and systems	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Lighting			
The applicant must ensure a minimum of 40% of new or altered light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting-diode (LED) lamps.		~	~
Fixtures			
The applicant must ensure new or altered showerheads have a flow rate no greater than 9 litres per minute or a 3 star water rating.		$\checkmark$	$\checkmark$
The applicant must ensure new or altered toilets have a flow rate no greater than 4 litres per average flush or a minimum 3 star water rating.		$\checkmark$	$\checkmark$
The applicant must ensure new or altered taps have a flow rate no greater than 9 litres per minute or minimum 3 star water rating.		$\checkmark$	

Construction			Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Insulation requirements					
The applicant must construct the new or altered construction (floor(s), walls, and ceilings/roofs) in accordance with the specifications listed in the table below, except that a) additional insulation is not required where the area of new construction is less than 2m2, b) insulation specified is not required for parts of altered construction where insulation already exists.					~
Construction	Additional insulation required (R-value)	Other specifications			
external wall: framed (weatherboard, fibro, metal clad)	R1.30 (or R1.70 including construction)				

	equirements						Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Windows	and glazed do	ors					I	1	
The applicant must install the windows, glazed doors and shading devices, in accordance with the specifications listed in the table below. Relevant overshadowing specifications must be satisfied for each window and glazed door.							$\checkmark$	~	~
The following requirements must also be satisfied in relation to each window and glazed door:							$\checkmark$	$\checkmark$	
have a U-v	alue and a Solar	Heat Gair	n Coefficie	ent (SHGC)		ed glass may either match the description, or, le below. Total system U-values and SHGCs s.		~	~
	For projections described in millimetres, the leading edge of each eave, pergola, verandah, balcony or awning must be no more than 500 mm above the head of the window or glazed door and no more than 2400 mm above the sill.						$\checkmark$	$\checkmark$	$\checkmark$
Pergolas with polycarbonate roof or similar translucent material must have a shading coefficient of less than 0.35.							$\checkmark$	$\checkmark$	
Pergolas with fixed battens must have battens parallel to the window or glazed door above which they are situated, unless the pergola also shades a perpendicular window. The spacing between battens must not be more than 50 mm.							$\checkmark$	~	
Overshadowing buildings or vegetation must be of the height and distance from the centre and the base of the window and glazed door, as specified in the 'overshadowing' column in the table below.						$\checkmark$	$\checkmark$	~	
Windows	s and glazed	doors g	lazing r	equireme	nts				
Window / door Orientation Area of Overshadowing Shading device Frame and glass type									
		glass	Height	Distance (m)					
Window / c no.		inc. frame (m2)	(m)	(111)					
	E	frame	(m) 4	4.4	eave/verandah/pergola/balcony >=600 mm	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
no.	E	frame (m2)							

Glazing requi	rements			Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
The applicant m	The applicant must install the glazed roofs described in the table below, in accordance with the specifications listed in the table.					
The following re	The following requirements must also be satisfied in relation to each glazed roof:					$\checkmark$
Each glazed roof with standard aluminium or timber frames and single clear or toned glass may either match the description, or, have a U-value and a Solar Heat Gain Coefficient (SHGC) no greater than that listed in the table below. Total system U-values and SHGCs must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions.					~	~
Glazed roofs	s glazing require	ments		-		
Glazed roof number	Area of glazing (m2)	Shading device	Glass type			
G1	0.7	no shading	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)			

## Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a "," in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a "v" in the "Show on CC/CDC plans & specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.