

## **Construction Certificate Determination**

## Certificate No 2008/2859

Roy 241744  30 00  311718	Determination  issued under the Environmental Planning and Assessment Act 1979 Section 109C (1) (b) 81A (2) and 81A (4)
21/2/0	Certificate No 2008/2859
Council	Pittwater
Determination	Approved
date of issue	18 July 2008
Subject land	
Address	4A The Avenue, Newport
Lot No DP No	Lot 5 DP 1059003
Applicant	
Name	W & B Consulting Pty Ltd
Address	11 Harst Place Belrose NSW 2085
Contact No (phone)	0419 244 670
Owner	
Name	Mr Daryl & Mrs Aimee Hennessy
Address	4A The Avenue, Newport NSW 2106
Contact No (phone)	0419 244 670
Description of Development	
Type of Work	New Dwelling & Swimming Pool
Builder or Owner/Builder	
Name	Daryl Hennessy
Contractor Licence No/Permit	40685 SCANNED
Value of Work	2 2 JUL 2008
Building	\$500,000 00 PITTI SOUNCIL

## **Attachments**

- Copy of completed Construction Certificate Application Form
- Basix Certificate no 2060975 dated 17 July 2008
- Pittwater Council Receipt no 240597 for payment of Long Service Levy
- Pittwater Council Receipt no 240597 for payment of Long Service Levy
   Correspondence from Pittwater Council dated 11 June 2008 confirming Condition C12 is satisfied

## Plans & Specifications certified

The development is to be carried out in compliance with the following plans and documentation listed below and endorsed with *Insight Building Certifiers* stamp

- Architectural Plans & Construction Specifications reference nos 01 to 17 (inclusive) prepared by W
   & B Consulting Pty Ltd dated 4 April 2007
- Structural Details reference nos H-08-21095-1B & 2B prepared & endorsed by Civil & Structural Engineering Design Services Pty Ltd dated 24 June 2008 & BHP 07L15732 Sheets 1 to 5 (inclusive) prepared and endorsed by Keighran and Associates Pty Ltd dated 25 October 2007
- Completed Form 2 (two pages) of the Geotechnical Risk Management Policy for Pittwater dated 27
  June 2008
- Rainwater Treatment Plan (including design certification) reference no H-08-21095-3A prepared by Civil & Structural Engineering Design Services Pty Ltd dated 24 June 2008
- Driveway Design Certification prepared by Civil & Structural Engineering Design Services Pty Ltd, dated 19 June 2008
- Driveway Design Certification reference no 1883 prepared by DP Surveying Services dated 18
  June 2008
- Arborist's Report (updated) prepared by Urban Forestry Australia dated June 2008
- Landscape Plan reference no 07 HENNESSY 01, prepared by Catriona Mackenzie dated 1 July 2008
- Copy of Sydney Water Approval dated 29 May 2008

## Certificate

I hereby certify that the above Plans documents or Certificates satisfy

The relevant provisions of the Building Code of Australia

The relevant conditions of this Development Consent

and that work completed in accordance with the documentation accompanying the application for this Certificate (and any modifications as verified by me and shown on that documentation) will comply with the requirements of the Environmental Planning & Assessment Regulation referred to in Section 81A(5) of the Environmental Planning & Assessment Act 1979

Signed

Date of endorsement Certificate No 18 JUL 2008

**Certifying Authority** 

Name of Accredited Certifier Accreditation No

Accreditation Authority

Contact No

Address

Tom Bowden BPB0042

**Building Professionals Board** 

(02) 9999 0003

13/90 Mona Vale Road, Mona Vale NSW 2103

**Development Consent** 

Development Application No Date of Determination

N0176/07 15 October 2007

**BCA Classification** 

1a & 10b





## APPLICATION FOR A CONSTRUCTION CERTIFICATE

1. Applicant's details	
It is important that we are able to contact you if we need more information. Plea  Mr. Mrs Ms Dr. Other W&B	CONSULTING PYLTS
Given Names (or ACN) Family Name (or Company)	UNTING PHY LTD
32 OCI BGA 955 W & B CONST Postal Address (We will post all mail to this address)	UN TING IFY NTO
11 HARSY PLACE	
BELROSE NSW  Doytime telephone Alternate no:	Post Code 2005
0419 244670	
2. Owner's consent	
Every owner of the land must sign this form. If the owner is a company the form comman seal must be stamped on this form. If the property is a unit under the stamped to the owner's signature the common seal of the body corporate must be stamped.	rata title or a lot in a community title, then in additio
signed by the Chairman or Secretary of the Body Corporate on the appointed man Owner(s)	
Daryl and Almee Hennessy	58 barren joey le
Address () 57 AA The Avenue	Hona Nate
Newport PH 9979 5143	0410 535 143
As owner(s) of the land-to which this application relates, II/We consent to this app Certifying Authority and/or Accredited Certifier to enter the land-to carry out in	blication: I/We also consent for the Principals
FFSignature(s).	Special Country of the
D Hermeny Olive	ONU
Without the owner's consent we will not accept the application. This is a very struction the owner's behalf as the owner's legal representative, you must state the natural	ct requirement for all applications. If you are signing re of your legal authority and attach documentary
avidence (eg. power, of a homey, executors trustees company, director, etc).	
Unity/Streetino. Street pane	
4A THE AVENUE	
NEWPORT	051 code 1 (2) 06
Legal Property Description (these details are shown an your rate notices; property	general I Wall
5 1059003 V	

# 4. Description of work What type of work as you propose to carry out? Please describe briefly everything that you want approve RESIDENCE & SWIMMING POOL 5. Estimated cost of work The estimated cost of the development or contract price may be subject to review. Estimated cost of work \$ 500, 000.00 6. Development Consent Council Consent no NO 176/07 15/10/2007 Date of Determination 7. Building Code of Australia classification This can be found on the development consen BCA Classification CLASS 1a = 10h 8. Builder's details If known, to be completed in the case of residential building work. 40685 HENNESSEY License no DARYL Owner/builder permit no 9. Applicant's declaration Eapply far a Coreneus ton Certificate to carry anticalding works as described in this application. Edeclare that all the information in this application and the stissers to the best of my knowledge, true and correct. Signature Machael & Ledling

## **SUBMISSION REQUIREMENTS**

Α	GENE	<u>RAL</u>	
Are	the plans	submitted with th	ne Construction Certificate Application in accordance with the Development Consent?
			Yes ♥ No □
Hav	e all the co	onditions of Deve	elopment Consent relating to the issue of the Construction Certificate been fully complied with?
			yes ☑ No □
		answered NO t	to either of the above questions, then you will need to speak with the Accredited Certifier
BE.			has the following required information been submitted?)
_	<u> </u>	Not	In the case of an application for a Construction Certificate for
Yes	No	Applicable	building work
		П	Three (3) copies of detailed architectural plans and specifications
_/	, <u> </u>		
\blacktriangledown			The plan for the building must consist of a general plan drawn to a scale not less that 1 100 and a site plan drawn to a scale not less than 1 200. The general plan of the building is to  a) show a plan of each floor section  b) show a plan of each elevation of the building  c) show the levels of the lowest floor and of any yard or unbuilt on area belonging to the floor and the levels of the adjacent ground  d) indicate the height design and full construction details  e) indicate the provision for fire safety and fire resistance (if any)
Ø		v	Where the proposed building work involves any alteration or addition to or rebuilding of an existing building all copies of the general plan are to be coloured or otherwise marked to the satisfaction of the Council to adequately distinguish the proposed alteration addition or rebuilding with a separate letter listing the proposed changes being submitted
<b>e</b>			3 copies of a specification  a) to describe the construction and materials of which the building is to be built and the method of drainage sewerage and water supply  b) state whether the materials proposed to be used are new or second hand and give particular
		ष्	Where the proposed building work involves a modification to previously approved plans and specifications the general plans must be coloured or otherwise marked to the satisfaction of the Accredited Certifier to adequately distinguish the modification
		ð	If the proposed building work involves a modification to previously approved plans and specification which were subject of a Development Consent, has the original Development Consent been modified by Council?
		囡	<ul> <li>Except in the case of an application for or in respect of domestic building work</li> <li>a) a list of any fire safety measures that are proposed to be implemented in the building or on the land on which the building is situated and</li> <li>b) if the application relates to a proposal to carry out any alteration or rebuilding of or addition to an existing building a separate list of such of those measures as are currently implemented in the building or on the land on which the building is situated. This list must specify the standard of design of each of those fire safety measures to which they were originally installed.</li> <li>c) This list must describe the extent capability and basis of design of each of the measures concerned.</li> </ul>
Ø	′ ⊏		Copy of BASIX Certificate & Report
Q	´ [		All other documentation to satisfy conditions of Development Consent

## HOME BUILDING ACT 1989 (as amended) OWNER/BUILDER REQUIREMENTS

Applicants for work at a residential property with a value of work over \$12 000 require insurance as specified in the Home Building Act 1989

Owner Builders require Property Owner Builder's Permit issued by the Department of Fair Trading for all projects over \$5 000 In addition to this permit all projects valued in excess of \$12 000 may also require a contract of insurance under the provisions of the Home Building At 1989 as amended This requirement will take effect should the property owner offer the property for sale in the ensuing period of 7 years

Enquines on any matters relevant to this section should be taken up with the Department of Fair Trading at Level 21 Astra House 227 Elizabeth Street Sydney (ph 133220)

## LONG SERVICE LEVY (applies to all classes of buildings)

A Long Service Levy at 0 35% of the cost of works is payable on projects valued \$25 000 or more. This sum can be paid directly to the Long Service Payments Corporation or to Council acting as an agent to the Corporation. Partial exemption from the levy may be granted to non profit organizations churches and to owner/builders. The levy may also be paid in instalments. Application forms for these exemptions are available from Council but all enquiries in this regard should be address to the Long Service Payments Corporation.

THE CONSTRUCTION CERTIFICATION CANNOT BE ISSUED UNLESS THE LONG SERVICE LEVY AND HOME BUILDING ACT 1989 INSURANCE (APPLICABLE TO RESIDENTIAL PROPERTIES) HAVE BEEN PAID OR EVIDENCE OF THE EXEMPTION PROVIDED TO COUNCIL

PARTICULARS OF THE PROPOSAL	
What is the area of the land $(m^2)^2$ $1200$	Gross floor area of building (m²) as proposed 465
What are the current uses of all or parts of the building(s)/land?  VACANT	Use Nowport.
Does the site contain a dual occupancy?	What is the gross floor area of the proposed addition or new building (sq metres)?  465
What are the proposed uses of all parts of the building(s land?	Number of pre-existing dwellings
Number of dwellings to be demolished	How many dwellings proposed?
How many storeys will the building consist of?	Will the new building be attached to the existing building?
3	Will the new building be attached to any new building?

## MATERIALS TO BE USED

The following information must be supplied for the Australian Bureau of Statistics

Place a tick ( $\sqrt{\ }$ ) in the box which best describes the materials the new work will be constructed of

WALLS Brick veneer		FLOOR Concrete		ROOF Aluminium		FRAME Timber	
Full brick		Timber	<b>✓</b>	Concrete		Steel	
Single brick		Other		Concrete tile		Other	
Concrete block		Unknown		Fibrous cement		Unknown	
Concrete/masonry				Fibreglass			
Concrete				Masonry/terracotta shingle			
Steel				Tiles			
Fibrous cement				Slate	$\Box$		
Hardıplank	$\Box$			Steel			
Timber/weatherboard				Terracotta tile			
Cladding aluminium				Other			
Curtain glass				Unknown			
Other							
Unknown							

	<u></u>		



Matt Hansen 8am to 5pm Mon – Fri Phone 9970 1624

11th June 2008

Insight Building Certifiers PO Box 326 Mona Vale NSW 1660

To whom it may concern,



ABN61340837871
Telephone 02 9970 1111
Facsımile 02 9970 7150
Postal Address
PO Box 882
Mona Vale NSW 1660
DX 9018 Mona Vale

## Re Development Application No N0176/07 Property 4a The Avenue, Newport


I have provided advice to the applicant in relation to a condition of consent on the above DA This relates to condition C12 "An Ecological Sustainability Plan complying with Councils ESP templates (Forms 3a/3b) is to be submitted to Council for approval by Councils Natural Environment Assessor prior to release of the Construction Certificate "The applicant has since submitted the required ESP which I have reviewed, and it is acceptable in the context of the property and its natural resources. Therefore this ESP has adequately satisfied condition C12 and should be considered when proceeding in the issue of the Construction Certificate.

If you have any questions, please do not hesitate to contact me

Yours faithfully

Matt Hansen

**Natural Resources Assessment Officer** 



# BASI COLLICOR

page 1/10

Building Sustainability Index

www basix nsw gov au

Certificate number 206097S

This certificate confirms that the proposed development will meet the NSW governments requirements for sustainability if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments have the meaning given by the document entitled "BASIX Definitions" dated 29/06/2006, published by the Department of Planning. This document is available at www basix nsw gov au.

Director General
Date of Issue Thursday 17 July 2008



NSW GOVERNMENT

Department of Planning

# Score

√ Water 44 (Target 40)

✓ Thermal comfort pass (Target pass)

✓ Energy 42 (Target 40)

										2.5		× =	, m. 4		<b>\$</b> {	ξ .	۲.,	ž ¢	<u>.</u>	γ ≥*	3 ~		-4
	none	Other	Heating load (MJ/m² year)	Cooling load (MJ/m² year)	Certificate number	Assessor number	Assessor details and thermal	Total area of garden and lawn (m2)	Unconditioned floor area (m2)	Conditioned floor area (m2)	Roof area (m²)	Site area (m²)	Site details	No of bedrooms	Project type	Project type	Section no	Lot no	Plan type and plan number	Local Government Area	Street address	Project name	Proj⊏o address
A CONTRACTOR OF THE PROPERTY O	n/a		n/a	n/a	n/a	n/a	loads	800	465	-2	322	1200		5	separate dwelling house		0.0	5	Deposited Plan 1059003	Pittwater Council	4a The Avenue Avenue Newport 2106	Mr and Mrs Hennessy for Construction Certificate	

# Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted or complying development certificate issued, for the proposed development, that BASIX commitments be complied with

,	~	<	The swimming pool must not have a volume greater than 57 kilolitres
			Swittining pool.
<	<		a tap that is located within 10 metres of the swimming pool in the development
<b>~</b>	<		at least one outdoor tap in the development (Note NSWHealth does not recommend that rainwater be used for human consumption in areas with potable water supply.)
<u> </u>	<		all toilets in the development
			The applicant must connect the rainwater tank to
<	~		The applicant must configure the rainwater tank to collect rain runoff from at least 322 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam)
•	<	<	The applicant must install a rainwater tank of at least 10000 litres on the site. This rainwater tank must meet, and be installed in accordance with the requirements of all applicable regulatory authorities.
			Alfernative water Palmuse sank
	<	,	The applicant must install basin taps with a minimum rating of 6 star in each bathroom in the development
	<b>~</b>		The applicant must install taps with a minimum rating of 6 star in the kilchen in the development
<	~		The applicant must install a tollet flushing system with a minimum rating of 4 star in each tollet in the development
<	~		The applicant must install showerheads with a minimum rating of 3 star in all showers in the development
			Fixtures.
	<	<	The applicant must plant indigenous or low water use species of vegetation throughout 750 square metres of the site
			Landscape
Certifier check	Show on CC/CDC plans & specs	Show on DA plans	Water Commitments
AND DESCRIPTIONS OF THE PERSON.		Commence of the Persons of	

3			
ביניתו בי בי שמשמשות בין		Water Commitments The swimning pool must be outdoors	
3		Sw G	
		3 G	
Ų.		j e	
چ ک		g E	
.,		<u> </u>	
		<del>i</del> ii	
		e o	
		<u>ā</u>	
		§ All	
	 	"	
-			
ž.			
THE PROPERTY OF THE PARTY OF TH			
i z			
1			
) =			
_			
306			
ই			
	i 		
Ţì		Show on DA plans	
		<b>\ E</b>	
3		5 2	
'n			
Fig. 2002 State of the deposit of the first		Show on CC/CDC plans & specs	
į		76 €	
<b>j</b>		< ₽ 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	
ž		<b>38</b>	
,		Ş %	
Š		Õ	
7			
.,		Certifier check	
ŗ		오를	
έ.		Ċ.	
5	1	100000000000000000000000000000000000000	

ceiling and roof - flat ceiling / pitched roof	internal wall shared with garage - plasterboard	external wall framed (weatherboard fibro metal clad)	floor - suspended floor above open subfloor framed	Construction	Floor, walls and celling/roof  The applicant must construct the floor(s) walls and ceiling/below	Thermal Comfort Commitments
ceiling 2.75 (up) roof thermocellular reflective	Di.	1 30 (or 1 70 including construction)	0 8 (or 1 5 including construction) (down)	Additional insulation required (R-Value)	The applicant must construct the floor(s) walls and ceiling/roof of the dwelling in accordance with the specifications listed in the table below	
4 wind driven ventilator(s) + eave vents dark (solar absorptance > 0.70)			site slope > 10% below floor	Othersosplications	d in the table	Show on Show on CC/CDC Certifier

Pergolas with polycarbonate roof or similar translucent material must have a shading coefficient of less than 0.35  Unless they have adjustable shading pergolas must have fixed batters parallel to the window or glazed door above which they are situated unless the pergola also shades a perpendicular window. The spacing between battens must not be more than 50 mm.	The leading edge of each eave pergola verandah balcony or awning must be no more than 500 millimetres above the head of the window or glazed door except that a projection greater than 500 mm and up to 1500 mm above the head must be twice the value in the table	Except where the glass is single clear or single toned each window and glazed door must have a U value no greater than that listed and a Solar Heat Gain Coefficient (SHGC) +/ 10% of that listed. Total system U-values and SHGC must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions.	The following requirements must also be satisfied in relation to each window and glazed door	The dwelling may have 1 skylight (<0.7 square metres) and up to 2 windows/glazed doors (<0.7 square metres) which are not listed in the table	The applicant must install the windows glazed doors and shading devices described in the table below in accordance with the specifications listed in the table. Relevant overstadowing specifications must be satisfied for each window and glazed door	Thermal Comfort Commitments  Nindows, glazed doors and stylights
	<		< !	<	<	Show on DA plans
	<		<b>*</b>	<b>~</b>	*	Show on CC/CDC plans & specs
< <	<	<	<	<b>~</b>	<	Certifier check

W/176 12	Z	936	improved aluminium single toned (U-value 6 39 SHGC 0 56)	eave/ygrandah/pergola/balcony	not overshadowed
. W2	Z	504	timber or uPVC single toned (or U-value 5 67 SHGC 0 49)	eave/verandah/pergola/balcony > 2 000 mm	not overshadowed
W3	, m	0 68	improved aluminium single toned (U-value 6 39 SHGC 0 56)	ก๊กัone	not overshadowed
Ŵ12A	Z	2 88	improved aluminium single toned (U-value 6 39 SHGC 0 56)	.eave/verandah/pergola/balcony 1,500-2 000 mm	not overshadowed
W4 5,9 18 10	Ŝ	12 36	improved aluminium, single toned (U-value 6 39 SHGC 0 56)	eave/verandah/pergola/balcony -451_600 mm	not overshadowed
W10 11 14	N 3,	984	improved aluminium single toned (U value 6 39 SHGC 0 56)	eave/verandah/pergola/balcony	not overshadowed

BASIX Certificate number 206097S

Window/glazed door no.	Orientation	Waximum area (square metres)	Type	Shading	
, Mig	SE	288	improved aluminium single toned (U-value 6 39 SHGC 0 56)	, eave/Verandah/përgola/balcony ⟨ 901 1 200 mm	
W17	Z	204	improved aluminium single toned (U-value 6 39 SHGC 0 56)	eave/verandah/pergola/balcony 601-750 mm	not overshadowed
W6 17	. Nassa	702	improved aluminium single toned (U-value 6 39 SHGC 0 56)	eave/verandah/pergola/balcony 6012750 mm	not overshadowed
W7 15	m	104	improved aluminium single toned (U-value 6 39 SHGC 0 56)	eave/verandah/pergola/balcony 601-750 mm	not overshadowed
W10	W	2.88	mproved aluminium single toned (U-value 6 39 SHGC 0 56)	eave/verandah/pergola/balcony 601-750 mm	not overshadowed
W8	·	216	mproved aluminium single toned (U-value 6 39 SHGC 0 56)	eave/verandah/pergola/balcony a	ny >2 000 not overshadowed
*W5	W	288	improved aluminium single toned (U-value 6 39 SHGC 0 56)	eave/verandah/pergola/balcony 601-750 mm	not overshadowed
מום	W.	864	improved aluminium single toned (U-value 6 39 SHGC 0 56)	eave/verandah/pergola/baicony 601-750 mm	not overshadowed
D11	Z	864	improved aluminium single toned (U-value 6 39 SHGC 0 56)	eave/verandah/pergola/balcony 601-750 mm	not overshadowed


(c) have only 1 doorway or opening less than 2 square metres in size located in the direct path between them	(b) be at least 1 square metre in size and	(a) not be more than 15 metres apart	The 2 ventilation openings must meet the following specifications	Breeze path 4 opposite external walls	Breeze path 3 opposite external walls	Breeze path 2 >3 m apart and on adjacent external walls	Breeze path 1 opposite external walls	The 2 ventilation openings must be located as follows	The applicant must construct the dwelling so that at least 1 ventilation opening is provided in each such room or area. (If only 1 room or area of a dwelling is mentioned for a breeze path, then that room or area must have at least 2 ventilation openings).	Breeze path 4 within Bedroom 3 (not ensuite)	Breeze path 3 within Bedroom 2 (not ensuite)	Breeze path 2 within Bedroom 1 (not ensuite)	Breeze path 1 within main living area	The commitment below applies to the following rooms or areas of a dwelling which comprise a breeze path for the dwelling	the second of the second secon	Thermal Comfort Commitments
<	<	<		<	<	<	<	1	<					<		Show on
<	<	<		<	<	<	<	-	<u> </u>					A Contract of the contract of	plans & specs	Show on CC/CDC
< 	<	<		< 	<	< 	< - ~		V						Check	Gertifier


the kitchen dedicated all bathrooms/toilets dedicated	• at least 6 of the bedrooms / study at least 2 of the living / dining rooms	Antificial lighting  Antificial lighting  The applicant must ensure that the primary type of artificial lighting is fluorescent or light emitting diode (LED) lighting in each of the following rooms and where the word 'dedicated' appears the fittings for those lights must only be capable of accepting fluorescent or light emitting diode (LED) larins.	Laundry individual fan ducted to façade or roof. Operation control. manual switch on/off	At least 1 Bathroom individual fan ducted to façade or roof. Operation control interlocked to light.  Kitchen individual fan, ducted to façade or roof. Operation control inanual switch on/off.	<b>Vernilation</b> The applicant must install the following exhaust systems in the development	The applicant must install the following heating system or a system with a higher energy rating in at least 1 bedroom gas fixed flued heater Energy rating 3.5 Star	Heating system  The applicant must install the following heating system or a system with a higher energy rating in at least 1 living area gas fixed flued heater Energy rating 3.5 Star	The applicant must install the following cooling system or a system with a higher energy rating, in at least 1 bedroom ceiling fans Energy rating n/a	<b>Cociling system</b> The applicant must install the following cooling system or a system with a higher energy rating, in at least 1 living area ceiling fans Energy rating in/a	Hotwate  The applicant must install the following hot water system in the development or a system with a higher energy rating gas instantaneous with a performance of 6 stars	
	. •		< <b>*</b>			<b>\</b>		<b>\</b>	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	DA plans plans to proceed to plans to p	
< < <			< <	< <		<	<	<		check	


BASIX Certificate number 206097S


	The applicant must install a fixed indoor or sheltered clothes drying line as part of the development	The applicant must install a fixed outdoor clothes drying line as part of the development	The applicant must construct each refigerator space in the development so that it is 'well ventilated as defined in the BASIX definitions	The applicant must install a gas cooktop & electric oven in the kitchen of the dwelling	Other	The applicant must install a timer for the swimming pool pump in the development	The development must not incorporate any heating system for the swimming pool	Swinning pool	The applicant must install a window and/or skylight in 5 bathroom(s)/toilet(s) in the development for natural lighting	The applicant must install a window and/or skylight in the kitchen of the dwelling for natural lighting	Natural Highting	all hallways dedicated	the laundry dedicated	Energy Commitments
			a same						<	<				Show on Sho
and confidence on the confiden	<u> </u>	<	<u> </u>	<					<	•		< 	<b>~</b>	Show on CC/CDC plans & specs
	The state of the s									<b>~</b>			<	Certifier check


	Commitments identified with a $$ in the "Certifier check column must be certified by a certifying authority as having been fulfilled before a final occupation certificate(either interim or final) for the development may be issued	Commitments identified with a $$ in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development	lentified with a $\sqrt{\ }$ in the "Show on DA plans column must be shown on the plans accompanying the development application is to be lodged for the proposed development)		Legend	
--	---	--	--	--	--------	--











۲-2 'n C11 C10 65 62 CS 40 000 0 000 0 2 9 B THE DESIGN OF THE POOL HAS BEEN BASED ON BEING SUPPORTED BY UNFORM NATURAL GROUND WITH A MINIMUM SAFE BEARING VALUE OF 150494 (UNLESS SHOWN AS SUSPENDED ON PRIERS) THE BUILDER SHALL NOTIFY THE ENGINEER IF ANY OTHER GROUND CONDITIONS ARE ENCOUNTERED PRIOR TO COPPLETING THE EXCANATION THE BUILDER SHALL ALSO NOTIFY THE ENGINEER IF A CLASS HORE E SUBGRADE IS ENCOUNTERED. THE EXCANATION SHALL BE REPOYED AND THE EXCANATION SHALL BE REPOYED AND THE EXCANATION SHALL BE REPOYED AND THE ENGINEER OF THE POOL SHALL BE SEPARATED FROM THE SUBGRADE MATERIAL SHALL BE REPOYED AND THE BUILDER SHALL BE SEPARATED FROM THE SUBGRADE WITH A 2004M POLYTHENE MEMBRANE OVER 50 CRUSHED STONE COURSE AGGREGATE OR OTHER TATERIAL AS APPROVED BY THE ENGINEER NATIONAL PROPERTY TO COPPLEXICITIES OF AN EXISTING STRUCTURE SHALL BE REFERRED TO THE FINANCEER PRIOR TO COPPLEXICITIES. THE SETTING OUT DIMENSIONS STALL BE IN ACCORDANCE WITH AS2783 - 1992

ANY UNFORSEER VARIATIONS TO THE ASSUMED SITE CONDITIONS SHALL BE REFERRED TO THE ENGINEER PRIOR TO PROCEEDING SEEN AND COPINGS HAND BEEN DESIGNED FOR A LIVE LOAD OF AMP

THE WALKWAYS AND COPINGS HAVE BEEN DESIGNED FOR A LIVE LOAD OF AMP

THE ENGINEER SHALL BE NOTIFIED OF ANY PROPOSED VARIATION TO THIS PRIOR TO PLACING THE REMPORCEMENT

PRIOR TO E-PRTYING THE POOL

FROM THE BASE AND WALLS OF THE DOOL


THE ENGINEER SHALL BE NOTIFIED IF THE POOL IS OUT OF THE GROUND BY MORE THAN 900 MINIMUM 28 DAY CONCRETE COMPRESSIVE STRENGTH OF 32MPs
CONCRETE SIZES SHOWN DO NOT INCLIDE FINISH AND HUST NOT BE REDUCED OR HOLED IN ANY WAY WITHOUT THE
CONCRETE SIZES SHOWN DO NOT INCLIDE FINISH AND HUST NOT BE REDUCED OR HOLED INCREASED
APPROVAL OF THE ENGINEER HOWEVER THE RADIUS OR CONCRETE THICKNESS MAY BE INCREASED
APPROVAL OF THE ENGINEER HOWEVER THE RADIUS OR CONCRETE WITH ASSTRESTED STRENGS NOT BE CONCRETE COVER SHALL BE IN ACCORDANCE WITH ASSTRESTED TO CONCRETE SHALL BE MANITAINED BY THE USE OF APPROVED CHAIRS AT APPROXIMATELY 750 CROSS CENTRES
ALL CONCRETE SHALL BE CURED BY THE OWNER FOR A MINIMUM OF 7 DAY'S AFTER POURING BY KEEPING ALL EXPOSED
ALL CONCRETE SHALL BE CURED BY THE OWNER FOR A MINIMUM OF 7 DAY'S AFTER POURING BY KEEPING ALL EXPOSED THE DETAILS PRESENTED ON THE FOLLOWING SHEETS COMPLY WITH THE REQUIREMENTS OF AS2783-1992
ALL WORKMANSHIP SHALL BE IN ACCORDANCE WITH AS3500
ALL CONCRETE SHALL HAVE A MINIMUM 28 DAY CONCRETE COMPRESSIVE STRENGTH OF 25MP3 AND HAVE A MAXIMUM AGGREGATE SIZE OF TOMM AND A MAXIMUM SLUMP OF 80MM UNLESS NOTED OTHERWISE
WHERE THE POOL IS LOCATED WITHIN INM DF LARGE EXPANSES OF SALT WATER THE CONCRETE SHELL SHALL HAVE A PROVIDE 10mm CONTROL JOINTS BETWEEN THE PERIMETER LUGE OF THE POOL AND ALL ABUTTING CONCRETE OR MASONRY S NOTATION TO REINTORCEMENT DENOTES GRADE 230 DEFORMED BAR
UNLESS OTHERWISE NOTED ALL REINFORCEMENT LAPS SHALL BE A MINIMUM OF 500mm GENERAL FOUNDATION FINISHES SURFACES WET WITH WATER CONCRETE CONTROL JOINTS IN THE WALKWAY FINISH AT MAXIMUM 4000 CENTRES AND AT POINTS OF RE-ENTRANT 5400

> ά 4

> > (1)

83 Q

(F)



T 4

REFERRED TO THE ENGINEER PRIOR

# BLUE HAVEN POOLS جع SPAS γI٩ O.T.

68 Hume Highway Lansvale NSW 2166 Site Plan & Pool Plans prepared by Blue Haver. Pools & Spas Pty Ltd Telephone (02) 9728 C444 Fax (02) 9728 0455

> APPROVED Consulting Structural and Civil Engineers Keighran and Associates Pty Ltd Golden wa. ABN 25 003 832 291 25/


DATE


Structural details only certified by


BE (Hons) MEMSON FIENUST OPEng Registered NPER 3719 (Structural & Civil) / 10/ 07 Ą


07L15732 유 5

Z









# SYDNEY WATER BUILDING PLAN APPROVED SUBJECT TO REQUIREMENTS

Dolfin No D07/8-11294

Quick Check Ref No 2273795

e-Developer Case No N/A

**Property Location** 

Street No 4A

Lot No 5

Street Name The Avenue

Suburb Newport

Building/Structure Description New Residence

Building Plan No 07 Hennessy 01

Engineers Plan No H-08-21095-1A

Proposed building/structure is APPROVED to construct OVER TO a Sydney Water sewer/asset, subject to the following requirements (NB Delete non applicable requirements)

- 1 The foundations/piers are to be founded below 1 in 1 zone of influence, soil strata
- 2 No part of the building/structure or its foundations to be less than a minimum 0 6 metre, horizontal distance from the centreline of the sewer
- 3 No part of the swmming pool or its foundations to be less than a minimum 0 6 metre, horizontal distance from the centreline of the sewer to the outer edge of the pool coping
- 4 No part of the building/structure or swimming pool coping to be less than 1 m horizontal distance from outside edge of maintenance hole rim
- 5 No piering of building/structure to be less than 2 m horizontal distance from centreline of maintenance hole to edge of piers
- 6 Foundations/piers are constructed in accordance with Engineers detail plans (stated above) as submitted to Sydney Water
- 7 All foundations/piers are to be founded to below the zone of influence or to solid rock
- 8 Concrete encase approximately 11 metres of sewer Concrete encasement to be carried out by an Accredited Constructor of Minor Works (Sewer) / Constructor and a Minor Works Agreement signed prior to commencement of works
- 9 Concrete encasement must extend a minimum of 600 mm past the external walls of the building/structure
- 10 Minimum of 300 mm vertical clearance between top of concrete encasement to underside of concrete slab

Doc. Name eDev08\_01\_Building Plan Approved\_ Subject to Requirements\_02 Doc Controller Planning Reporting & Compliance Manager

## SPECIAL REQUIREMENTS

- (a) Min 2 8m vertical clearance to be maintained to MH under deck
- (b)
- (c)

## NOTE

Above requirements must be inspected/supervised by an Accredited Supplier or Sydney Water to enable the issue of a satisfactory compliance letter

Permits are required to fill all new swimming pools with a capacity greater than 10,000 litres. To arrange for a permit please contact Sydney Water on 13 20 92 during business hours. Fines will apply for filling swimming pools without a permit.

## APPROVED BY

WSC Company Name AWPM - Northern Beaches


Name of Key Personnel Alex Ross

Ø.

Signature of Key Personnel

Date

29/05/2008







## Civil & Structural Engineering Design Services Pty. Ltd.

ABN 62 051 307 852 3 Wanniti Road BELROSE NSW 2085 Email civilandstructural@bigpond.com

Tel 02 9975 3899 Fax 02 99751943 Web www civilandstructural com au

19<sup>th</sup> June 2008

W & B Consulting Pty Ltd 11 Hurst Place BELROSE NSW 2085

Dear Sır,

Re

# New Dwelling & Swimming Pool at 4A The Avenue, Newport DRIVEWAY DESIGN ADEQUACY CERTIFICATE

I am an appropriately qualified and competent person in this area being listed in the National Professional Engineers Register (NPER) and I have been engaged by Mr Hennessy to prepare the driveway details for the above project and I am able to certify that the design for the proposed access driveway complies with the requirements of B6 1 of Pittwater DCP 21 to satisfy Condition C3

I possess Indemnity Insurance to the satisfaction of the building owner or my principal


Full Name of Designer
Qualifications
Address of Designer
Business Telephone No
Name of Employer
Ltd

Edward Arthur Bennett
M I E Aust CPE NPER 198230
3 Wanniti Road, Belrose NSW 2085
02 99753899 Fax No 02 99751943
Civil & Structural Engineering Design Services Pty

Yours faithfully,

leader est

EA Bennett MIE Aust



Site Inspection Report



A.B N 18 532 038 993

Land & Engineering Surveys
David Parsons, B Surv M I S. (Aust)
760A Barrenjoey Road Avenue Avalon 2107
Phone (02) 9974-3354 Fax (02) 9974-3352

Mobile 0414 183 220 Email david@dpsurveying com au

Our Ref 1883


18 June, 2008

DARYL HENNESSY 58 BARRENJOEY ROAD MONA VALE NSW 2103

Re 4A The Avenue, Newport

As instructed I have inspected the Pittwater Council approved plans of the proposed residence at the abovementioned address and prepared by W & B Consulting Pty Ltd dated 04/04/2007 and find that if the residence and driveway extension are constructed in accordance with the said plans the proposed access driveway will comply with the requirements of clause B6 1 of Pittwater 21 DCP in that egress to the shared driveway and The Avenue will be possible in a forward direction

David Parsons Registered Surveyor





## TREE MANAGEMENT CONSULTING ARBORICULTURISTS

## ARBORICULTURAL ASSESSMENT

for

Mr and Mrs Hennessy 58 Barrenjoey Road MONA VALE NSW 2103

> SITE ADDRESS 4A THE AVENUE NEWPORT NSW

> **JUNE 2008**

INSTITUTE OF AUSTRALIAN CONSULTING ABBORICULTURISTS

**URBAN FORESTRY AUSTRALIA** 

ABN 90 639 906 218 www.urbanforestry.com.au Correspondence

PO Box 151 NEWPORT NSW 2106 Telephone (92) 99 8 9830 0414 997 417

mackenzie1@bresond.com

## **CONTENTS**

1	INTRODUCTION	1
2	METHODOLOGY	2
3	OBSERVATIONS AND DISCUSSION 3 1 General 3 2 Tree Removal 3 3 Trees to be Retained 3 4 Impacts on Trees Proposed for Retention	3 3 3 4 4
4	CONCLUSIONS	6
5	RECOMMENDATIONS 5 1 Tree Removal 5 2 Minimising Impacts on Trees to be Retained 5 3 Tree Protection Zones 5 4 Pruning 5 5 General	<b>7</b> 7 7 10 11 11
6	BIBLIOGRAPHY	12
API API	PENDIX A - Terms and Definitions PENDIX B - SULE Categories PENDIX C - Schedule of Surveyed Trees PENDIX D - Original (2006) Tree Plan PENDIX F - Amended (2008) Tree Plan	

## 1 INTRODUCTION

- 1 1 This amendment to the original Arboricultural report by Urban Forestry Australia, dated April 2006, was commissioned by Emay and Daryl Hennessy, owners of the subject site
  - The subject site is identified as Lot 5 in D.P. 1059003, and known as 4A The Avenue, Newport, New South Wales
- 1 2 The original report of April, 2006 accompanied a development application to Pittwater Council for the proposed construction of a new dwelling, garage and pool on the subject site
- 1 3 The purpose of the original report was to assess the health and condition of trees within proximity to the proposed development of the subject site. The report also assessed any identified or potential impacts that the proposed development may have on the subject trees, and provided recommendations for tree retention and removal, and guidelines for tree protection and maintenance.
- 1 4 The Development Application DAN0176/07 was approved on 15<sup>th</sup> October, 2007 This amended report addresses the requirements of Development Consent condition C9, specifically addressing the protection measures for Trees 8 and 9
- Information contained in this Arboricultural Assessment covers only the trees that were examined and reflects the condition of the trees at the time of inspection Care has been taken to obtain all information from reliable sources All data has been verified as far as possible, however, I can neither guarantee nor be responsible for the accuracy of information provided by others
- 1 6 This report is not intended to be a comprehensive hazard assessment, however the report may make recommendations, where appropriate, for further assessment or testing of trees where potential structural problems have been identified or where below ground investigation may be required

## 2 METHODOLOGY

- 2 1 In preparation for the April 2006 report, a ground level visual tree assessment (Mattheck 1994) was undertaken by the author of this report on 5 April, 2006 A second inspection of Trees 8 and 9 was undertaken on 10 June, 2008
- 2 2 Tree height and canopy spread was estimated
  Trunk diameter was measured at 1 4 metres above ground level (DBH), using a standard metal tape
- 2.3 Field observations were written down
- 2.4 No aerial (climbing) inspections or woody tissue testing was undertaken as part of this tree assessment.
  Information contained in this tree report covers only the trees that were examined and reflects the condition of the trees at the time of inspection.
- 2.5 Plans and documents referenced for the preparation of this amended report include
  - Plans and Elevations, Dwg No's 07 HENNESSY 01- 13, dated
     04/04/07, prepared by W & B Consulting Pty Ltd
  - Pittwater Council Development Consent DAN0176/07, issued 15<sup>th</sup>
     October, 2007
- 2.6 Trees assessed at the original site inspection in 2006 include those within 5 metres of the proposed development, or where they may be outside the 5 metre setback, but potentially affected by the proposal (including neighbouring properties)
  - Only Trees 8 and 9 were re-inspected at the June 2008 site visit
- 27 Trees are shown on a marked up copy of the site plan. The plan is attached as Appendix D Tree Plan.

### 3 OBSERVATIONS AND DISCUSSION

#### 3 1 General

- 3 1 1 Many of the subject trees are in poor condition due to overplanting, pest and fungal problems, poor pruning techniques, and restricted area for crown and/or root development
- 3 1 2 There are six (6) trees within the site which are considered to contribute to the site amenity, and these are all proposed for retention For the most part, these trees exhibit good health and condition

#### 3 2 Tree removal

- 3 2 1 Of the sixteen (16) trees assessed, ten (10) are proposed for removal Of these trees it is noted
  - Eight (8) are in poor to very poor health and condition, and would be removed for safety reasons, regardless of site development
     These are Trees 2, 4, 6, 7, 10, 12 (which is outside the property boundary, but a significant hazard), 15 and 16, and
  - Two (2) are in fair condition Trees 11 and 14
- 3 2 2 The two (2) Guioa semiglaucas Trees 6 and 7, are in very poor condition, and are just too close to the proposal to retain without excessive branch removal. The ongoing risk of branch and/or stem failure at such proximity to the dwelling and open space precludes their safe retention in this location. Given the constraints of the site, e.g. planning controls on boundary setbacks, easements and land use restrictions, it would be reasonable to remove these two trees to construct the dwelling, enabling an area around the structure where the occupants can feel safe from high risk trees.

#### 3 3 Trees to be Retained

3 3 1 Six (6) trees are proposed for retention as part of this development proposal. These are Trees 1, 3, 5, 8, 9 and 13.

Of these it is noted.

- Tree 1 is in poor health and may not be a candidate for retention in the long term,
- Tree 3 is actually two trees which should always be treated as a single unit,
- o Trees 5, 8, 9 and 13 are generally in good health and condition

### 3 4 Impacts on Trees Proposed for Retention

#### 341 <u>Tree 1</u>

This rainforest tree is showing signs of decline, although it may recover to an extent where reasonable maintenance may allow retention for the short to medium term (e.g. 5-15 years). It is exposed as a result of approved subdivision works removing surrounding vegetation, which has probably contributed to its current poor vigour.

The crown is high and clear of the proposed garage roof line so no pruning, other than deadwooding, would be required

3 4 2 The proposed garage, stairs and deck on the west side of the dwelling are fully elevated. Provided piers are hand dug and located away from any primary roots, the development is not expected to accelerate the decline of the tree. Protection of the tree stem and rootzone would be required to ensure increased foot traffic and other site activities do not also contribute to the decline of the tree.

## 342 <u>Tree 3</u>

This mature Turpentine is well clear of the elevated structure, and would require normal protection measures to reduce any impacts of work activities

Fencing and silt control measures would suffice as protection against materials stargaze and particulates from encroaching into the majority of the root zone

Any pruning of the tree crown would be minor for garage roof clearance, and, given the good vigour of the tree, not expected to create a decline in tree health as a result

#### 343 Tree 5

A young Paperbark located well clear of the dwelling Normal tree protection would be required to ensure the tree is not affected by work activities

#### 344 Tree 8

The condition of development consent requires this tree to be retained. It is extremely close to the proposed deck, and it appears the approved roofline is over the tree on plan.

A proposed pier would be located within 300mm of the base of the tree

#### 345 Tree 9

The proposed pool is elevated well above ground, and approximately 1.2 metres from the tree. The greatest impact to the tree would occur via compaction of soil within the root zone, particularly upslope of the tree.

#### 346 Tree 13

This Turpentine is located approximately 3 metres from the east side of the elevated dwelling. Some branches are located approximately 4 metres and 8 metres above ground, on the west side of the tree, and may need to be removed or reduced to accommodate the dwelling.

The crown of the tree is reasonable well balanced and could tolerate branch removal and deadwooding to reduce dropping of limbs on, or near the dwelling

3 4 7 There are a few immature *Livistona australis* Cabbage Tree Palms scattered through the development area. These could be easily relocated outside the building footprint prior to works commencing

## 4 CONCLUSIONS

- **4.1** The trees nominated for removal are, for the most part, in poor health and/or condition, and do not warrant design changes to retain them
- 4 2 One tree proposed for removal is a locally significant species which could be retained if the proposed pool was redesigned to accommodate it. As the continued presence of this species in the local area is under threat the removal of two poor specimens should be considered reasonable if one good, healthy specimen can be retained.
- 4.3 The proposal will not have any significant or detrimental impacts on the trees to be retained as the development is fully elevated, and no alteration of the existing ground contours is proposed
  - Minor pruning works may be required to provide building clearances, however this would not affect the health of the trees
  - Appropriate protection measures to retained trees would be required to ensure potential impacts such as slurry runoff and soil compaction do not affect tree root zones
- The proposal is a reasonable one which does not intend to alter the nature, drainage patterns or topography of the site
- **4 5** Tree removal can be readily compensated for by planting in the large area where development is restricted
  - The replacement trees and understorey plantings would improve the landscape character, amenity and habitat potential of the site

## 5 RECOMMENDATIONS

#### 51 Tree Removal

- 5 1 1 Remove the nominated trees to allow development
- 5 1 2 The removal must be carried out by trained tree workers with a minimum Australian Qualification Framework Level 3 in Arboriculture. This is to ensure that untrained contractors do not inadvertently cause damage to trees to be retained.
- 5 1 3 Where possible roots should be cut below ground Do not pull out stumps that lie within the PRZ of trees to be retained
- 5 1 4 Removed trees should be chipped, and this material used for temporary ground protection within the PRZ's of trees to be retained

#### 5 2 Minimising Impacts on Trees to be Retained

521 Specific

#### Tree 8

Construction drawings need to modify the proposed roofline over the deck, to provide adequate clearance for the tree trunk

The drawings also must relocate any piers as far as practicable from the base of the tree Cantilevering of deck sections may be required to enable this Final pier locations must be determined by hand excavation to ensure woody anchor roots are not severed, damaged or significantly disturbed

5 2 2 Prior to construction, the tree is to be pruned to remove branches on its south side that may contact the built structure. It is also recommended the smaller of the three stems (i.e. smaller stem growing to the northwest) is removed, as it is well over the pool area, and likely to be damaged during works. The pruning must be carried out to Australian Standard 4373-2007. Pruning of Amenity Trees, and performed by a tree worker with a minimum Australian Qualification Framework Level 3 in arboriculture. Removal of live.

foliage is to be restricted to no more than 10% of the overall canopy area, otherwise an arboriculturist should be contacted for advice

- 5 2 3 Prior to construction, the tree must have the trunk protected from ground to7 metres The protection device is to be generally in accordance with thematerials and methods shown in Figure 1, page 10
- 5 2 4 To avoid unnecessary compaction of the soil within the root zone, and area of a minimum 4 metres radius of the tree, is to be covered in coarse mulch to a depth no less than 100mm. Where areas of heavy foot traffic occurs within this mulched area, the ground is to be further protected by placing temporary boardwalks, or sturdy timber or metal planks which can support wheelbarrows, and the like.

#### 525 <u>Tree 9</u>

Prior to construction, the tree must have the trunk protected from ground to 6 metres. The protection device is to be generally in accordance with the materials and methods shown in Figure 1, page 10.

- 5 2 6 To avoid unnecessary compaction of the soil within the root zone, and area of a minimum 4 metres radius of the tree, is to be covered in coarse mulch to a depth no less than 100mm. Where areas of heavy foot traffic occurs within this mulched area, the ground is to be further protected by placing temporary boardwalks, or sturdy timber or metal planks which can support wheelbarrows, and the like.
- 5 2 7 Any pruning of this tree must be carried out to Australian Standard 4373-2007 Pruning of Amenity Trees, and performed by a tree worker with a minimum Australian Qualification Framework Level 3 in arboriculture Removal of live foliage is to be restricted to no more than 10% of the overall canopy area, otherwise an arboriculturist should be contacted for advice

#### 528 General

Prior to commencement of any site works, the project arboriculturist is to meet the builder/project manager and determine the most appropriate tree protection measures to be adopted on site for the remaining trees to be retained

Protection devices may include mulching, tree guards and other devices other than fencing

- 5 2 9 Provide sediment control devices (i.e. silt arrestor fabric, etc.) in front of the protection fencing upslope of any tree to be retained. The silt control device must extend a minimum 4 metres in each direction across the slope to ensure runoff does not flow into the root zone. The silt control fabric should be securely placed at approximately 100mm below ground, and at least 300mm above ground to be effective.
- 5 2 10 Container size of proposed plants within the *Primary Root Zone* (PRZ) of trees to be retained should be determined by careful location of any woody tree roots prior to planting. Otherwise, proposed plants should consist of tubestock only. This is required to ensure that damage to the tree's roots is avoided or minimised.

Mattocks and similar digging instruments must not be used within 3 metres of the trees. Planting holes should be dug carefully by hand with a garden trowel, or similar small tool.


5 2 4 No strip footings are to be used within the PRZ of trees to be retained. Any pad footings proposed within the PRZ of trees must be dug by hand under the supervision of a qualified arboriculturist.

#### 5 3 Tree Protection Zones

5 3 1 Tree protection zones must be in place prior to any site works commencing, including clearing, demolition or grading

The following is strongly recommended

- It is recommended that an arboriculturist provide written certification that the TPZ is installed and will satisfy tree protection requirements
- The most appropriate fencing for TPZ is 1 8m chainlink with 50mm metal pole supports
- No stock-piling shall take place around the root zone of any tree intended for retention
- Nothing is to occur in the TPZ, so therefore all access to personnel and machinery, and storage of fuel, chemicals, cement or site sheds is prohibited
- Silt fencing and protection fencing must be inspected daily by the site supervisor. Any repairs required must be carried immediately
- Signage should explain exclusion from the TPZ and carry a contact name for access or advice
- o The TPZ cannot be removed, altered, or relocated without the projects arborists' prior assessment and approval



Lengths of treated timber at 150mm centres e g H5 TP 75 x 50mm (or similar)
Secure galvanized hoop strapping (or similar) - screws must not contact trunk

Insert expansion joint foam (or similar) at strategic locations to prevent direct contact between timber and trunk

Protect root crown and exposed roots in trafficable areas with 150mm depth mulch placed over geofabric

Where machinery is required to move within the CRZ / PRZ of retained trees provide steel rumble boards with timber bearers/battens to carry and spread the weight of the machinery so as to minimise soil compaction

Figure 1 Tree Guard detail

#### 54 Pruning

5 4 1 Pruning of any tree to be retained must be carried out by an AQF3 trained tree worker (or higher qualification), and be in strict accordance with Australian Standard 4373-2007 Pruning of Amenity Trees

#### 5 5 General

- 5 5 1 The following general comments apply to trees nominated for retention
  - o No stockpiling should take place around the root zone
  - A qualified arboriculturist must be retained to carry out and/or supervise works within the Critical Root Zone (CRZ) and PRZ of the trees
  - Any excavation within the CRZ should be carried out by hand i.e. a trench along the line of cut adjacent to the tree should be carefully dug by hand to expose any roots. The project arboriculturist is to advise on which roots may be severed, if any. After cutting of roots, machinery may complete the excavation.
  - Do not allow excavation vehicles or equipment to rip at, or remove the
    roots along the face of the excavation adjacent to a tree. In the event
    the vehicles 'grab' at roots during works, the machine operator must
    stop work immediately and allow the roots to be cut before continuing.
  - Any damage to trees, or incursions into the TPZ, must be reported immediately to the project arboriculturist
  - Service trenches should not pass through a fenced area, although if this
    cannot be avoided, a qualified arboriculturist should be present to
    supervise excavation, cut torn roots cleanly or redesign around roots
  - Regular monitoring of protected trees during development works for unforeseen changes or decline will help to maintain healthy trees, and identify any further potential impacts
  - All site trees should be re-assessed every two years, or after a major storm event, to ensure the trees are maintained in a safe and healthy manner. The assessor must be a competent arboriculturist with a minimum Australian Qualification Framework (AQF) Level 5 attained.

Should you require further assistance with this matter, or require my liaison with Council officers, please do not hesitate to contact me

Yours faithfully,

aprilevne Isa



Catriona Mackenzie MAIH, MIACA, MISAAC
Consulting arboriculturist, horticulturist and landscape designer
Certificate of Horticulture Honours
Diploma of Horticulture (Arboriculture) Distinction
Associate Diploma of Applied Science (Landscape) Distinction

## **6 BIBLIOGRAPHY**

Barrell, J (1995) Pre-development Tree Assessment from Trees and Building Sites, Eds Watson & Neely, International Society of Arboriculture, Illinois

Mattheck, C & Breloer, H (1999) *The Body Language of Trees* Research for Amenity Trees No 4, The Stationary Office, London

# APPENDIX A TERMS AND DEFINITIONS

#### **TERMS AND DEFINITIONS**

The following relates to terms or abbreviations that may have been used in this report and provides the reader with a detailed explanation of those terms

#### Age classes

- o (1) = immature and refers to a well established but juvenile tree
- (S) = semi-mature and refers to a tree at growth stages between immaturity and full size
- o (M) = mature and refers to a full sized tree with some capacity for further growth
- (O) = over-mature and refers to a tree about to enter decline or already declining

Condition refers to the tree's form and growth habit, as modified by its environment (aspect, suppression by other trees, soils) and the state of the scaffold(i e trunk and major branches), including structural defects such as cavities, crooked trunks or weak trunk/branch junctions. These are not directly connected with health and it is possible for a tree to be healthy but in poor condition.

**Critical Root Zone (CRZ)** refers to a radial offset of five (5) times the trunk DBH measured from the center of the trunk Excavation within this area may seriously destabilize the tree. Fully elevated construction within this area is possible with specific root zone assessment.

**Diameter at Breast Height (DBH)** refers to the tree trunk diameter at breast height (1 4 metres above ground level)

Health refers to the tree's vigour as exhibited by the crown density leaf colour presence of epicormic shoots, ability to withstand disease invasion and the degree of dieback

**Primary Root Zone (PRZ)** refers to a radial offset of ten (10) times the trunk DBH measured from the center of the trunk Excavation is possible within one offset only with this area and subject to specific rootzone assessment

#### SAFE USEFUL LIFE EXPECTANCY (SULE)

In a planning context, the time a tree can expect to be usefully retained is the most important long-term consideration. SULE i e. a system designed to classify trees into a number of categories so that information regarding tree retention can be concisely communicated in a non-technical manner.

SULE categories are easily verifiable by experienced personnel without great disparity. A tree s SULE category is the life expectancy of the tree modified first by its age health condition safety and location (to give safe life expectancy), then by economics (i.e. cost of maintenance retaining trees at an excessive management cost is not normally acceptable), effects on better trees, and sustained amenity (i.e. establishing a range of age classes in a local population).

SULE assessments are not static but may be modified as dictated by changes in tree health and environment. Trees with a short SULE may be at present be making a contribution to the landscape but their value to the local amenity will decrease rapidly towards the end of this period prior to them being removed for safety or aesthetic reasons.

For details of SULE categories see Appendix B, adapted from Barrell 1996

Scaffold branch A primary structural branch of the crown

**Tree Protection Zone (TPZ),** generally the minimum distance from the center of the tree trunk where protective fencing or barriers are to be installed to create an exclusion zone

## APPENDIX B SULE CATEGORIES

#### Safe Useful Life Expectancy (SULE) CATEGORIES (after Barrell 1996 Updated 01/04/01)

The five categories and their sub-groups are as follows

- 1 Long SULE tree appeared retainable at the time of assessment for over 40 years with an acceptable degree of risk, assuming reasonable maintenance
  - A structurally sound trees located in positions that can accommodate future growth
  - B trees which could be made suitable for long term retention by remedial care
  - C trees of special significance which would warrant extraordinary efforts to secure their long term retention
- 2 Medium SULE tree appeared to be retainable at the time of assessment for 15 to 40 years with an acceptable degree of risk assuming reasonable maintenance
  - A trees which may only live from 15 to 40 years
  - B trees which may live for more than 40 years but would be removed for safety or nuisance reasons
  - C trees which may live for more than 40 years but would be removed to prevent interference with more suitable individuals or to provide space for new planting
  - D trees which could be made suitable for retention in the medium term by remedial care
- 3 Short SULE tree appeared to be retainable at the time of assessment for 5 to 15 years with an acceptable degree of risk assuming reasonable maintenance
  - A trees which may only live from 5 to 15 years
  - B trees which may live for more than 15 years but would be removed for safety or nuisance reasons
  - C trees which may live for more than 15 years but would be removed to prevent interference with more suitable individuals or to provide space for new planting
  - D trees which require substantial remediation and are only suitable for retention in the short term
- 4 Removal trees which should be removed within the next 5 years
  - A dead dying suppressed or declining trees
  - B dangerous trees through instability or recent loss of adjacent trees
  - C dangerous trees because of structural defects including cavities decay, included bark wounds or poor form
  - D damaged trees that are clearly not safe to retain
  - E trees which may live for more than 5 years but would be removed to prevent interference with more suitable individuals or to provide space for new planting
  - F trees which are damaging or may cause damage to existing structures within the next 5 years
  - G trees that will become dangerous after removal of other trees for the reasons given in (a) to (f)
  - H trees in categories (a) to (g) that have a high wildlife habitat value and with appropriate treatment could be retained subject to regular review
- 5 Small, young or regularly pruned Trees that can be reliably moved or replaced
  - A small trees less than 5m in height
  - B young trees less than 15 years old but over 5m in height
  - C formal hedges and trees intended for regular pruning to artificially control growth

## APPENDIX C SCHEDULE OF ASSESSED TREES

## **SCHEDULE OF ASSESSED TREES**

## 4A The Avenue, Newport 5<sup>th</sup> April, 2006

Tree No	Species and Common Name	Height (m)	Crown spread (m)	DBH (mm)	Age	Health	Condition	SULE	Comments
1	Rainforest sp Unidentified at time of inspection	15	9	400	ОМ	Poor	Fair	4A	Locally indigenous species Appears to be in decline as a result of adjacent subdivision works and exposure
2	Brachychiton populneus Kurrajong	11	4	220	SM	Poor	Fair	3B	Native species Poor form health Close to proposed dwelling
3	Syncarpia glomulifera Turpentine	13	12	320 + 400	М	Good	Fair	2A	Locally indigenous species Some crown suppression to south Two trees with shared crown
4	Melaleuca styphelioides Prickly-leaved Paperbark	13	6	450	OM	Poor	Poor	4A	Locally indigenous species Crown declining Major dieback Leaning Within development footprint
5	Melaleuca styphelioides Prickly-leaved Paperbark	8	1	100	SM	Good	Good	1A	Locally indigenous species Slightly suppressed by T6
6	Guioa semiglauca Guioa	10	7	180 to 300	ОМ	Poor	Poor	4C	Locally indigenous species Multiple stem and branch failures Declining condition Remove for safety reasons
7	Guioa semiglauca Guioa	8	5	130	SM	Good	Poor	4C	Locally indigenous species Heavily suppressed Significant lean to north Stem damage Failures noted
8	Syncarpia glomulifera Turpentine	16	12	2 x 400 280	M	Good	Good	2A	Remove for safety reasons Locally indigenous species One poorly developed stem Very close to proposed deck
9	Guioa semiglauca Guioa	11	7	250	М	Good	Good	ЗА	Locally indigenous species Close to pool
10	Syncarpia glomulifera Turpentine	11	4	110 120	SM	Poor	Poor	4A	Locally indigenous species Dead stern Highly suppressed High % dieback Within development footprint
11	Allocasuarına torulosa Forest Oak	15	6	300	ОМ	Fair	Fair	3D	Locally indigenous species Major branch inclusions Significant deadwood Within development footprint
12	Eucalyptus sp	18	5	500	ОМ	Poor	Poor	4C	Hard to identify species the condition of tree is so poor Significant decline Hazardous tree Outside property boundary Remove for safety reasons
13	Syncarpia glomulifera Turpentine	18	12	550	М	Good	Good	2A	Locally indigenous species Some deadwood to lower crown Outside property boundary


## URBAN FORESTRY AUSTRALIA - TREE MANAGEMENT & CONSULTING ARBORISTS

14	Syncarpia glomulifera Turpentine	11	8	310	М	Good	Fair	3D	Locally indigenous species Crown highly suppressed to west Within development footprint
15	Syncarpia glomulifera Turpentine	9	6	200	SM	Good	Poor	4C	Locally indigenous species Very poor form – kinked upper stem Within development footprint
16	Syncarpia glomulifera Turpentine							4A	Almost dead

## **LEGEND**


Trees to be retained	Trees to be removed	Tree which could be retained subject to amended pool design
----------------------	---------------------	---


APPENDIX D
ORIGINAL (2006) TREE PLAN




URBAN FORESTRY AUSTRALIA - TREE MANAGEMENT & CONSULTING ARBORISTS

APPENDIX E
UPDATED (2008) TREE PLAN






T to the minimum section




ALTERNATION AND ALL



Harry Land St. REVISIONS AT 48 THE AVENUE NEMPORT PROPOSED FIRST FLOOR PLAN FOR MR AND MRS HENNESSY PROPOSED NEW TIMBER FRAMED RESIDENCE 6 320 न्या ८०० नेय ०००क । ४८० के वन्छ । १० २ ७४० 3 382 4 515 4 425 ₹ 👺 42 MASTER BORM 1 | SONO 2 STARVITL Ŧ 14 415 14 415 5 370 (g) 3 830 8 682 S 4 430 PROJECT CONSULTANTS HOUSING INDUSTRY ASSOCIATION W & B CONSULTING PTY LTD THAIRST Place Beirose NSW 2005 MEMBER 2 400 90 25090 605 EAVE MIDTH (TYPICAL) 605 EAVE MIDTH (TYPCAL) 3 155 815 Ph 02 9452 4367 Fax 02 9452 4366 Mob 0419 244 670 EMAIL mied@bigpond net au ACN 32 001 864 955 SCALE DATE DRAWN BY MIKE LEDBURY 4 APRIL 01 -8

OTHENNESSY 04 DRAWING NUMBER


The state of the high





ASSESSMENT TO SHEET SHEET


THE PARTY OF THE P


A. R. A. L. S. C. L. S. C. S.























### **SPECIFICATION**

The erection and completion of proposed residence at -

4a The Avenue Newport

**Pittwater Council** 

for

Mr And Mrs Hennessy (heremafter called the Owner)

### **GENERAL CONDITIONS**

### **REGULATIONS AND NOTICES**

The Builder is to comply with the Building Code of Australia and/or any amendment thereto, the requirements of legally constituted Authorities for Local Government and/or Services The Builder is to give all notices obtain all permits and pay all fees required by such Authorities

The Builder must ensure that the work and services are performed in accordance with the contract and the provisions of the Building Services Corporation

### VISIT THE SITE

Builders tendering are to visit the site and satisfy themselves to the nature and extent of the work, the facilities available and the difficulties entailed in the execution of the said works. No extra amount above the accepted price will be allowed because of work arising due to neglect of this precaution

### LABOUR AND MATERIALS

The builder is to provide all materials labour, fittings and plant required to construct the works Material shall be of the standard specified and workmanship in each trade shall be performed by tradesmen of the particular trade and in conformity with current good building practice

### MAKING GOOD

The Builder shall be responsible for, and make good any damage to fencing, piping, footways, roads and surfaces generally, and any other work which may be disturbed or injured in carrying out this contract. He must leave the whole in as good a state of repair as they were in when he commenced the works

### GENERAL CONDITIONS (cont)

### **SETTING OUT**

The Builder is to set out and maintain the works in accordance with the drawings. Figured dimensions on plans are to be taken in preference to scaled measurements. No dimensions are to be scaled and used without first checking with the Designer. Where any doubt occurs as to boundary location, setout must be confirmed by a registered Land Surveyor.

### INSURANCE

Insurance of the works against fire will be effected by the Owner The Builder shall at his own expense adequately insure against Public Risk and arrange indemnification in respect of his liability for Workers Compensation, Superannuation and Long Service Leave

### **WORKMANSHIP AND MATERIALS**

The whole of the work is to be faithfully executed in the most tradesmanlike and substantial manner All materials are to be new and of the best quality

### ON COMPLETION

The whole of the works to be cleaned up on completion, all surplus materials and rubbish removed, the spaces under floors left clear of rubbish, all doors and windows eased, locks oiled, all keys properly tabulated and handed over, glass cleaned and the whole left ready for immediate occupation

### MAINTENANCE PERIOD

The Building shall maintain the works in respect of any defects, caused by faulty workmanship or materials, for a period of thirteen weeks from the date of practical completion

### SITE AND CHECK MEASURE

The Builder should check all dimensions on site, prior to commencement of work

### AUSTRALIAN STANDARDS

All work shall comply with the following Australian Standards and any other standards governing this style of work

AS 1684	SAA National Timber Framing Code
AS 1720 1	SAA Timber Structures Code
AS 3700	Masonry Code
AS 3600	Concrete Structures
AS 2040	Windows in Building
AS/NZS	Stormwater Drainage
AS 1657	Fixed Platforms, Walkways, Stairways and Ladders

### BASIX COMPLIANCE

All described in this specification shall compliance with Basix Certificate Number 72454M

It shall comply with the following items in particular

#### Water

- Indigenous plants are to be used for a minimum area of 750 Square metres of the site
- All internal shower heads are to have a 3 star rating
- Toilet flushing systems shall be 4 star
- All taps shall be 6 star
- Water tank must be 10,000 litres and must be configured as noted in Basix certificate
- Swimming pool must be outdoors

### Construction

- Floors, walls and ceilings must be constructed in accordance with the basix table
- Windows, glazed doors and shading devices must be constructed as detailed in the certificate

### Energy

- A 4 star gas instaneous hot water system must be installed for each residence
- Ventilation and Air Conditioning must be installed in each residence as detailed in the Basix Certificate
- Artificial and natural lighting must be installed as detailed in the Basix Certificate
- A gas cooktop and electric oven must be installed as detailed in the Basic certificate

### **Thermal Comfort**

• Thermal comfort performances as detailed in the Basix report must be adhered to

### EXCAVATOR

### **EXCAVATION FOR DRAINS**

Trenches for drains where running parallel to the building must not be within  $600 \mathrm{mm}$  of the building

Excavate to necessary depths and regulation grades for drains, trenches and service pipes

Allow for 300mm cover (minimum) for all drains

### DRAINER

### SEPTIC DRAINAGE

### **Sewered Areas**

Carry out dramage work to the rules and requirements of the local Authority responsible for Sewerage

The drainage system shall be carried out in approved sewerage pipes, laid to uniform falls, complete with necessary fittings, bends, inspection eyes, gully and boundary traps

Connect all required fittings to the system

### STORMWATER DRAINAGE

To be constructed in accordance with the Engineering Drawings

### PLASTERER

Provide plasterboard lining as required to all internal walls

### BRICKLAYER

### **MATERIALS**

Bricks

Common, approved for cement rendering

### Mortars

Cement mortar to be one part fresh cement to three parts sand

### GENERALLY

All brickwork is to be accurately bonded, keeping perpends plumb, and carried up true and plumb to the various heights on the drawings with beds and joints 10mm thick. All bricks are to be wetted before laying. The work shall be carried up in uniform scaffold heights, no part being taken higher than 15 courses above adjoining work. All work shall have flush joints ready for cement rendering

### WALLING

Provide brick veneer walling and single skin walling as noted on drawings  $\mathbf{DAMPCOURSE}$ 

Provide dampcourse to each wall

Dampcourse to be laid one course above finished ground level and underside of bearer and/or floor slab level where foundations exceed 600mm in height. Otherwise to underside of bearer or floor slab

### CARPENTER

### GENERALLY

All work shall comply with the relevant codes governing this type of work

### **TIMBER GRADES**

Timber grade shall be generally F5 unless described otherwise on the drawing

### **EAVES SOFFIT**

Provide overhang for eaves as shown on drawings and provide framing to support fibre cement soffit lining

### FASCIA

To be as described on the drawings

### **ROOF FRAMING**

To be as described on the drawings

### WALL LINING EXTERNALLY

Provide "Harditex lining boards to stud walls of first floor and finish externally with Granosite or similar in accordance with Manufacturer printed specification

### **OTHER ITEMS**

Provide all other timber items as described on the drawings  $\$  whether shown in this specification or not

### **BALCONY HANDRAILS**

All new handrails are to be as noted on the drawings

### DOOR FRAMES, DOORS, FURNITURE AND WINDOWS

### **Door Frames**

To all door openings, provide where required timber or pressed metal door frames

#### Doors

Provide doors as nominated on plan Doors to exterior are to be glazed panel Doors to interior to be hollow core

### Door Furniture

Provide all Door furniture as required as suitable for the individual application

#### Windows

Provide windows as described on the drawings Manufacturer of window is to be discussed with owner before ordering Refer window schedule for sizes

### ROOFER

Provide Colorbond Custom Orb roofing as noted on drawings

### PLUMBER

### **GENERALLY**

All plumbing work is to comply with the requirements of the appropriate authorities from which a certificate of satisfactory completion is to be obtained

### WATER SERVICE,

Connect to existing water service

### HOT WATER SERVICE

Extend from hot water unit properly lagged copper tubing to points over basins, shower recesses, sinks. Terminate at these points with approved fittings as required. Provide inlet and outlet stop cocks to hot water unit and in positions to be indicated.

### **SANITARY PLUMBER**

Provide fixtures in positions shown on plan

Provide wastes with traps to the above fittings and connect to the drainage system. The whole of the work to be performed in accordance with the rules and requirements of the relevant authority

Provide overflow outlet in wet area floors Fit grate

### STORMWATER DRAINAGE

Gutters to be as noted on plan, supported by gutter brackets as specified by manufacturer Downpipes to be as noted on Plan

### CONCRETOR

Provide concrete footings and slabs in accordance with engineers details

### TILER

Provide selected wall and floor tiles as required

### **ELECTRICIAN**

Provide all labour and materials for the proper installation of electricity service in accordance with the appropriate S.A A rules and the requirements of the local supply authority

Arrange with the supply authority for connection from supply mains to meter board

Provide for the proper installation of and connect electricity as required

Provide light points in positions to be determined Approved switch for each point is to be mounted in positions to be determined

Provide power points in positions to be determined

Refer to power and lighting diagram for location of light and power points

### **PAINTER**

### GENERALLY

All paints stains, varnishes and water colours are to be properly mixed, be of approved brands and brought to the job in unopened containers

Materials used for priming are to be as recommended by the manufacturers of the paints to be used

All finishing colours are to be selected by the owner

Do all necessary stopping after the priming has been applied Rub down all surfaces to a smooth finish prior to the application of each successive coat of paint.

### **EXTERNALLY**

### **Prime Before Fixing**

All dressed surfaces of external woodwork are to be primed before fixing

#### Waadwark

After priming, all exposed woodwork is to be given an undercoat and finished with one coat

### Cement Render

All rendered surfaces shall be given one undercoat and two finish coats of acrylic paint

### INTERNALLY

All plasterboardsurfaces to be given two coats of selected paints

### COMPLETION

The building is to be completed in every trade. Sashes and doors to be eased locks oiled and all plant, surplus building materials and rubbish removed from the site. Gutters and drains to be cleared and the building generally to be left clean and fit for occupation.

The Builder is to furnish the Owner with -

Notification of completion

Certificate from sewerage authority re sanitary dramage

Invoices for P C items

All keys for all doors

# GEOTECHNICAL RISK MANAGEMENT POLICY FOR PITTWATER FORM NO 2 – To be submitted with detailed design for construction certificate

	Development Application fo	
!		Name of Applicant
	Address of site 4A THE A	AVENUE, NEWPORT
Declaratio	on made by Structural or Civil E	Engineer in relation to the incorporation of the Geotechnical issues into the project design
	las H	on behalf of KEIGHRAN & ASSOCIATES PTY
	(insert name)	(trading or company name)
on this the	27/6/08	
above org at least \$2	anization/company to issue this d	neer as defined by the Geotechnical Risk Management Policy for Pittwater. I am authorised by the document and to certify that the organization/company has a current professional indemnity policy of e prepared the below listed structural documents in accordance with the recommendations given in elopment.
Seotechi	nical Report Details	
	Report Title RISK MANAGE VQ 22804	EMENT FOR PROPOSED NEW RESIDENCE AT 4A THE AVENUE NEWPORT
	Report Date 11 <sup>th</sup> JULY 2005	
	Author JACK HODGSON	
	Structural Documents list	
	DRAWINGS BHP 07615732 N	NO 1 5
ddressed nd justifie	to achieve an Acceptable Risk led	the geotechnical risk management aspects of the proposed development have been adequately Management level for the life of the structure taken as at least 100 years unless otherwise stated
	MWAND A 13	(signature)
eclaration	on made by Geotechnical Engir	neer or Engineering Geologist in relation to Structural Drawings
riewed the Geotechni am awar he basis t achieve ai	e above listed structural documen ical Report have been appropnat e that Pittwater Council relies on for ensuring that the geotechnical n Acceptable Risk Management	bovementioned Geotechnical Report as per Form 1 dated 11 <sup>TH</sup> JULY 2005 and now certify that I have into prepared for the same development. I am satisfied that the recommendations given in the te taken into account by the structural engineer in the preparation of these structural documents the processes covered by the Geotechnical Risk Management Policy including this certification as if risk management aspects of the proposed development have been adequately addressed to level for the life of the structure taken as at least 100 years unless otherwise stated and justified in call measures have been identified to remove foreseeable risk
	_	1 Hodge
		gnature Holdson
	Na	ame J HODGSON
	Na Ch	nartered Professional Status MEngSc FIEAust
	Na Ch Me	ame J HODGSON
	Na Ch Me	hartered Professional Status MEngSc FIEAust embership No 149 788
<b>3</b>	Na Ch Me Co	hartered Professional Status MEngSc FIEAust embership No 149 788

### GEOTECHNICAL RISK MANAGEMENT POLICY FOR PITTWATER FORM NO 2 - To be submitted with detailed design for construction certificate Development Application for\_ Name of Applicant Address of site 4A THE AVENUE, NEWPORT Declaration made by Structural or Civil Engineer in relation to the incorporation of the Geotechnical issues into the project design on behalf of **EDWARD A BENNETT CIVIL & STRUCTURAL ENGINEERING DESIGN** SERVICES PTY LTD (trading or company name) 08 on this the (date) certify that I am a Structural or Civil Engineer as defined by the Geotechnical Risk Management Policy for Pittwater I am authorised by the above organization/company to issue this document and to certify that the organization/company has a current professional indemnity policy of at least \$2million I also certify that I have prepared the below listed structural documents in accordance with the recommendations given in the Geotechnical Report for the above development Geotechnical Report Details Report Title RISK MANAGEMENT FOR PROPOSED NEW RESIDENCE AT 4A THE AVENUE NEWPORT Report Date 11th JULY 2005 Author JACK HODGSON Structural Documents list DRAWING NOS H 21095 1A 2B & 3A I am also aware that Pittwater Council relies on the processes covered by the Geotechnical Risk Management Policy including this certification as the basis for ensuring that the geotechnical risk management aspects of the proposed development have been adequately addressed to achieve an Acceptable Risk Management level for the life of the structure taken as at least 100 years unless otherwise stated and justified EDWARD A BENNETT Declaration made by Geotechnical Engineer or Engineering Geologist in relation to Structural Drawings I prepared and/or technically ventied the abovementioned Geotechnical Report as per Form 1 dated 11<sup>TH</sup> JULY 2005 and now certify that I have viewed the above listed structural documents prepared for the same development. I am satisfied that the recommendations given in the Geotechnical Report have been appropriate taken into account by the structural engineer in the preparation of these structural documents. I am aware that Pittwater Council relies on the processes covered by the Geotechnical Risk Management Policy including this certification as the basis for ensuring that the geotechnical risk management aspects of the proposed development have been adequately addressed to achieve an Acceptable Risk Management level for the life of the structure taken as at least 100 years unless otherwise stated and justified in the Report and that reasonable and practical measures have been identified to remove foreseeable risk Signature J HODGS Name MEngSc FIEAust Chartered Professional Status



Membership No

Company

149 788

Jack Hodgson Consultants Pty Ltd





## Civil & Structural Engineering Design Services Pty. Ltd.

ABN 62 051 307 852
3 Wanniti Road BELROSE NSW 2085
Email civilandstructural@bigpond.com

Tel 02 9975 3899 Fax 02 99751943 Web www.civilandstructural.com.au

19th June 2008

W & B Consulting Pty Ltd 11 Hurst Place BELROSE NSW 2085

Dear Sir,

Re

# New Dwelling & Swimming Pool at 4A The Avenue, Newport HYDRAULIC DESIGN ADEQUACY CERTIFICATE

I am an appropriately qualified and competent person in this area being listed in the National Professional Engineers Register (NPER) and I have been engaged by Mr Hennessy to prepare the Hydraulic Details for the above project and I am able to certify that the design and performance of the design complies with the requirements of B5 3 of Pittwater DCP 21 to satisfy Condition C2

I possess Indemnity Insurance to the satisfaction of the building owner or my principal

Full Name of Designer Qualifications Address of Designer Business Telephone No Name of Employer Ltd Edward Arthur Bennett
M I E Aust CPE NPER 198230
3 Wanniti Road, Belrose NSW 2085
02 99753899 Fax No 02 99751943
Civil & Structural Engineering Design Services Pty

Yours faithfully,

Gealen de

EA Bennett MIE Aust