

BASIX®Certificate

Building Sustainability Index www.basix.nsw.gov.au

Alterations and Additions

Certificate number: A420217_02

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Alterations and Additions Definitions" dated 06/10/2017 published by the Department. This document is available at www.basix.nsw.gov.au

Secretary
Date of issue: Tuesday, 15 June 2021
To be valid, this certificate must be lodged within 3 months of the date of issue.



Description of project

Project address	
Project name	106 BYNYA_02
Street address	106 BYNYA Road PALM BEACH 2108
Local Government Area	Northern Beaches Council
Plan type and number	Deposited Plan 1016938
Lot number	1
Section number	
Project type	
Dwelling type	Separate dwelling house
Type of alteration and addition	My renovation work is valued at \$50,000 or more, and includes a pool (and/or spa).

Certificate Prepared by (please complete before submitting to Council or PCA)
Name / Company Name: HAMPTON ARCHITECTURE
ABN (if applicable): 36085540442

BASIX Certificate number: A420217_02

Pool and Spa	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Rainwater tank			
The applicant must install a rainwater tank of at least 1968 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	✓	✓	✓
The applicant must configure the rainwater tank to collect rainwater runoff from at least 43 square metres of roof area.		✓	✓
The applicant must connect the rainwater tank to a tap located within 10 metres of the edge of the outdoor spa.		✓	✓
Outdoor spa			
The spa must not have a capacity greater than 3.5 kilolitres.	✓	✓	✓
The spa must have a spa cover.		✓	✓
The applicant must install a spa pump timer.		✓	✓
The applicant must install the following heating system for the outdoor spa that is part of this development: electric heat pump.		✓	✓

page 2 / 7

BASIX Certificate number: A420217_02

Fixtures and systems	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Lighting			
The applicant must ensure a minimum of 40% of new or altered light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting diode (LED) lamps.		✓	✓
Fixtures			
The applicant must ensure new or altered showerheads have a flow rate no greater than 9 litres per minute or a 3 star water rating.		✓	✓
The applicant must ensure new or altered toilets have a flow rate no greater than 4 litres per average flush or a minimum 3 star water rating.		✓	✓
The applicant must ensure new or altered taps have a flow rate no greater than 9 litres per minute or minimum 3 star water rating.		✓	

page 3 / 7

BASIX Certificate number: A420217_02

Construction			Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Insulation requirements					
The applicant must construct the new or altered construction (floor(s), walls, and ceilings/roofs) in accordance with the specifications listed in the table below, except that a) additional insulation is not required where the area of new construction is less than 2m2, b) insulation specified is not required for parts of altered construction where insulation already exists.			✓	✓	✓
Construction	Additional insulation required (R-value)	Other specifications			
concrete slab on ground floor.	nil				
external wall: cavity brick	nil				
external wall: brick veneer	R1.16 (or R1.70 including construction)				

page 4 / 7

BASIX Certificate number: A420217_02

Glazing requirements	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check			
Windows and glazed doors						
The applicant must install the windows, glazed doors and shading devices, in accordance with the specifications listed in the table below. Relevant overshadowing specifications must be satisfied for each window and glazed door.	✓	✓	✓			
The following requirements must also be satisfied in relation to each window and glazed door:		✓	✓			
Each window or glazed door with standard aluminium or timber frames and single clear or toned glass may either match the description, or, have a U-value and a Solar Heat Gain Coefficient (SHGC) no greater than that listed in the table below. Total system U-values and SHGCs must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions.		✓	✓			
For projections described in millimetres, the leading edge of each eave, pergola, verandah, balcony or awning must be no more than 500 mm above the head of the window or glazed door and no more than 2400 mm above the sill.	✓	✓	✓			
Pergolas with polycarbonate roof or similar translucent material must have a shading coefficient of less than 0.35.		✓	✓			
Pergolas with fixed battens must have battens parallel to the window or glazed door above which they are situated, unless the pergola also shades a perpendicular window. The spacing between battens must not be more than 50 mm.		✓	✓			
Overshadowing buildings or vegetation must be of the height and distance from the centre and the base of the window and glazed door, as specified in the 'overshadowing' column in the table below.	✓	✓	✓			
Windows and glazed doors glazing requirements						
Window / door no.	Orientation	Area of glass inc. frame (m2)	Overshadowing Height (m) Distance (m)	Shading device	Frame and glass type	
W1	N	16.66	0	0	eave/verandah/pergola/balcony >=900 mm	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)
W2	W	7.28	4	1.5	none	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)
W3	S	3.33	0	0	none	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)
W4	S	8.48	0	0	none	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)

page 5 / 7

BASIX Certificate number: A420217_02

Glazing requirements	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check								
Skylights											
The applicant must install the skylights in accordance with the specifications listed in the table below.	✓	✓	✓								
The following requirements must also be satisfied in relation to each skylight:		✓	✓								
Each skylight may either match the description, or, have a U-value and a Solar Heat Gain Coefficient (SHGC) no greater than that listed in the table below.		✓	✓								
Skylights glazing requirements											
<table><tr><th>Skylight number</th><th>Area of glazing inc. frame (m2)</th><th>Shading device</th><th>Frame and glass type</th></tr><tr><td>S1</td><td>0.49</td><td>no shading</td><td>aluminium, moulded plastic single clear, (or U-value: 6.21, SHGC: 0.808)</td></tr></table>	Skylight number	Area of glazing inc. frame (m2)	Shading device	Frame and glass type	S1	0.49	no shading	aluminium, moulded plastic single clear, (or U-value: 6.21, SHGC: 0.808)			
Skylight number	Area of glazing inc. frame (m2)	Shading device	Frame and glass type								
S1	0.49	no shading	aluminium, moulded plastic single clear, (or U-value: 6.21, SHGC: 0.808)								

page 6 / 7

Planning, Industry & Environment

Building Sustainability Index www.basix.nsw.gov.au

Planning, Industry & Environment

Building Sustainability Index www.basix.nsw.gov.au

Planning, Industry & Environment

Building Sustainability Index www.basix.nsw.gov.au

BASIX Certificate number: A420217_02

page 7 / 7

Legend
In these commitments, 'applicant' means the person carrying out the development.
Commitments identified with a "✓" in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).
Commitments identified with a "✓" in the "Show on CC/CDC plans & specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.
Commitments identified with a "✓" in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate for the development may be issued.

Planning, Industry & Environment

Building Sustainability Index www.basix.nsw.gov.au

DOCUMENT ISSUE:
A DEVELOPMENT APPLICATION

DATE
JUNE 2021

PROJECT: CADMAN RESIDENCE
ADDRESS: 106 Byrny Rd PALM BEACH
PURPOSE: DA APPLICATION
DRAWING: BASIX CERTIFICATE

SCALE: 1:100 @ A1
DATE: JUNE 2021
DRAWN: AH/KR
PROJECT No: # 084
DWG: DA.07



- Do not scale from drawings or build from these concept drawings.
- Dimensions indicated on concept plans are of finished surfaces, not structural surfaces.
- All drawings may not be reproduced or distributed without prior permission from the Architect.
- All works to be in accordance with Australian Standards, The Building Code of Australia, other relevant codes and manufacturers recommendations and instructions.