





- NOTES:**
1. ALL WORK IS TO BE CARRIED OUT IN ACCORDANCE WITH NORTHERN BEACHES COUNCIL'S DCP, AS3500.3 STORMWATER DRAINAGE.
 2. THE CONTRACTOR IS TO LOCATE AND LEVEL ALL EXISTING SERVICES PRIOR TO THE COMMENCEMENT OF CONSTRUCTION, WHETHER INDICATED ON THE PLANS OR NOT, AND MAKE ARRANGEMENTS WITH THE RELEVANT AUTHORITY TO RELOCATE OR ADJUST IF NECESSARY. ANY DAMAGE TO EXISTING SERVICES SHALL BE RECTIFIED AT THE CONTRACTORS EXPENSE.
 3. THE CONTRACTOR IS NOT TO ENTER UPON NOR DO ANY WORK WITHIN ADJOINING LANDS WITHOUT THE PERMISSION OF THE SUPERINTENDENT.
 4. THE CONTRACTOR SHALL EFFECT TEMPORARY DRAINAGE MEASURES TO AVOID LOCALISED PONDING OF SURFACE RUN-OFF.
 5. ALL NEW WORKS TO MAKE SMOOTH CONNECTION TO EXISTING CONDITIONS.
 6. THE CONTRACTOR IS TO MAINTAIN SERVICES AND ALL WEATHER ACCESS AT ALL TIMES TO ADJOINING PROPERTIES.
 7. ALL DRAINAGE ELEMENTS ARE SHOWN DIAGRAMATICALLY BASED ON AVAILABLE DRAWINGS, TO BE INSTALLED WITH CONSIDERATION TO SITE CONSTRAINTS AND THE INTENT OF THE DRAINAGE CONCEPT.
 8. ALL DOWNPIPES ARE SHOWN DIAGRAMATICALLY, POSITIONS ARE TO BE CONFIRMED ON SITE USING THE WORKING DRAWINGS.
 9. THE CONTRACTOR IS TO LOCATE AND LEVEL ALL EXISTING DRAINAGE PITS AND PIPES PRIOR TO THE COMMENCEMENT OF CONSTRUCTION AND THE CONSTRUCTION IS TO COMMENCE FROM THE DOWNSTREAM PIT AND STRUCTURES.
 10. ALL DOWNPIPES ARE TO BE MINIMUM 90mm uPVC OR 100mm x 75mm U.N.O.
 11. ALL DOWNPIPES TO BE PROVIDED WITH CLEANING EYES.
 12. ALL STORMWATER PIPES ARE TO BE MINIMUM 100mm uPVC ON 1% MINIMUM GRADE U.N.O. AND TO HAVE MIN 100mm COVER.
 13. ALL GUTTERS TO BE INSTALLED WITH GUTTER GUARDS UNLESS NOTED OTHERWISE.
 14. ENSURE THAT ALL PITS AND PIPES ARE LOCATED CLEAR FROM ANY TREE ROOT SYSTEMS.
 15. ALL STORMWATER PITS TO BE LOCATED AT LOW POINTS TO PREVENT PONDED WATER.
 16. CHARGED DOWNPIPE LINES ARE TO BE 100MM SEWER GRADE UPVC AND SEALED FROM 300MM BELOW THE TOP OF THE DOWNPIPE.


PREDEVELOPMENT CATCHMENT PLAN (1 OF 2)
SCALE 1:100

LEGEND PROPOSED	
	BOUNDARY LINE
	LOT 2 IMPERVIOUS AREA - 2q,262m²
	LOT 2 PERVIOUS AREA - 340,900m²
	LOT 1 IMPERVIOUS AREA - 50,871m²
	LOT 1 PERVIOUS AREA - 690,231m²
	LOT 1 EXISTING DRAINAGE - 539,085m²
	LOT 1 AND LOT 2 OMITTED AREA - 503,886m²



PREDEVELOPMENT CATCHMENT PLAN

A1, 1:100 SW01



- NOTES:**
1. ALL WORK IS TO BE CARRIED OUT IN ACCORDANCE WITH NORTHERN BEACHES COUNCIL'S DCP, AS3500.3 STORMWATER DRAINAGE.
 2. THE CONTRACTOR IS TO LOCATE AND LEVEL ALL EXISTING SERVICES PRIOR TO THE COMMENCEMENT OF CONSTRUCTION, WHETHER INDICATED ON THE PLANS OR NOT, AND MAKE ARRANGEMENTS WITH THE RELEVANT AUTHORITY TO RELOCATE OR ADJUST IF NECESSARY. ANY DAMAGE TO EXISTING SERVICES SHALL BE RECTIFIED AT THE CONTRACTORS EXPENSE.
 3. THE CONTRACTOR IS NOT TO ENTER UPON NOR DO ANY WORK WITHIN ADJOINING LANDS WITHOUT THE PERMISSION OF THE SUPERINTENDENT.
 4. THE CONTRACTOR SHALL EFFECT TEMPORARY DRAINAGE MEASURES TO AVOID LOCALISED PONDING OF SURFACE RUN-OFF.
 5. ALL NEW WORKS TO MAKE SMOOTH CONNECTION TO EXISTING CONDITIONS.
 6. THE CONTRACTOR IS TO MAINTAIN SERVICES AND ALL WEATHER ACCESS AT ALL TIMES TO ADJOINING PROPERTIES.
 7. ALL DRAINAGE ELEMENTS ARE SHOWN DIAGRAMATICALLY BASED ON AVAILABLE DRAWINGS, TO BE INSTALLED WITH CONSIDERATION TO SITE CONSTRAINTS AND THE INTENT OF THE DRAINAGE CONCEPT.
 8. ALL DOWNPIPES ARE SHOWN DIAGRAMATICALLY, POSITIONS ARE TO BE CONFIRMED ON SITE USING THE WORKING DRAWINGS.
 9. THE CONTRACTOR IS TO LOCATE AND LEVEL ALL EXISTING DRAINAGE PITS AND PIPES PRIOR TO THE COMMENCEMENT OF CONSTRUCTION AND THE CONSTRUCTION IS TO COMMENCE FROM THE DOWNSTREAM PIT AND STRUCTURES.
 10. ALL DOWNPIPES ARE TO BE MINIMUM 90mm uPVC OR 100mm x 75mm U.N.O.
 11. ALL DOWNPIPES TO BE PROVIDED WITH CLEANING EYES.
 12. ALL STORMWATER PIPES ARE TO BE MINIMUM 100mm uPVC ON 1% MINIMUM GRADE U.N.O. AND TO HAVE MIN 100mm COVER.
 13. ALL GUTTERS TO BE INSTALLED WITH GUTTER GUARDS UNLESS NOTED OTHERWISE.
 14. ENSURE THAT ALL PITS AND PIPES ARE LOCATED CLEAR FROM ANY TREE ROOT SYSTEMS.
 15. ALL STORMWATER PITS TO BE LOCATED AT LOW POINTS TO PREVENT PONDED WATER.
 16. CHARGED DOWNPIPE LINES ARE TO BE 100MM SEWER GRADE UPVC AND SEALED FROM 300MM BELOW THE TOP OF THE DOWNPIPE.

0 1 2 4 6
SCALE (m) 1:100


PREDEVELOPMENT CATCHMENT PLAN

A1, 1:100 SW02



NORTHERN BEACHES WATER MANAGEMENT FOR DEVELOPMENT POLICY
ASSUMED DRAINAGE FOR EXISTING HOUSES IS ADEQUATE.
FRONT PORTION OF LOT 1 AND 2 HAVE BEEN OMITTED FROM DRAINS CALCULATION DUE
TO LIMITATION OF THE SITE WHERE RAINWATER CANNOT BE CAPTURED
PIT HEIGHT WILL BE DETERMINED AFTER DRIVEWAY LEVEL HAVE BEEN PROVIDED

- NOTES:
1. ALL WORK IS TO BE CARRIED OUT IN ACCORDANCE WITH NORTHERN BEACHES COUNCIL'S DCP, AS3500.3 STORMWATER DRAINAGE.
 2. THE CONTRACTOR IS TO LOCATE AND LEVEL ALL EXISTING SERVICES PRIOR TO THE COMMENCEMENT OF CONSTRUCTION, WHETHER INDICATED ON THE PLANS OR NOT, AND MAKE ARRANGEMENTS WITH THE RELEVANT AUTHORITY TO RELOCATE OR ADJUST IF NECESSARY. ANY DAMAGE TO EXISTING SERVICES SHALL BE RECTIFIED AT THE CONTRACTORS EXPENSE.
 3. THE CONTRACTOR IS NOT TO ENTER UPON NOR DO ANY WORK WITHIN ADJOINING LANDS WITHOUT THE PERMISSION OF THE SUPERINTENDENT.
 4. THE CONTRACTOR SHALL EFFECT TEMPORARY DRAINAGE MEASURES TO AVOID LOCALISED PONDING OF SURFACE RUN-OFF.
 5. ALL NEW WORKS TO MAKE SMOOTH CONNECTION TO EXISTING CONDITIONS.
 6. THE CONTRACTOR IS TO MAINTAIN SERVICES AND ALL WEATHER ACCESS AT ALL TIMES TO ADJOINING PROPERTIES.
 7. ALL DRAINAGE ELEMENTS ARE SHOWN DIAGRAMATICALLY BASED ON AVAILABLE DRAWINGS, TO BE INSTALLED WITH CONSIDERATION TO SITE CONSTRAINTS AND THE INTENT OF THE DRAINAGE CONCEPT.
 8. ALL DOWNPIPES ARE SHOWN DIAGRAMATICALLY, POSITIONS ARE TO BE CONFIRMED ON SITE USING THE WORKING DRAWINGS.
 9. THE CONTRACTOR IS TO LOCATE AND LEVEL ALL EXISTING DRAINAGE PITS AND PIPES PRIOR TO THE COMMENCEMENT OF CONSTRUCTION AND THE CONSTRUCTION IS TO COMMENCE FROM THE DOWNSTREAM PIT AND STRUCTURES.
 10. ALL DOWNPIPES ARE TO BE MINIMUM 90mm uPVC OR 100mm x 75mm U.N.O.
 11. ALL DOWNPIPES TO BE PROVIDED WITH CLEANING EYES.
 12. ALL STORMWATER PIPES ARE TO BE MINIMUM 100mm uPVC ON 1% MINIMUM GRADE U.N.O. AND TO HAVE MIN 100mm COVER.
 13. ALL GUTTERS TO BE INSTALLED WITH GUTTER GUARDS UNLESS NOTED OTHERWISE.
 14. ENSURE THAT ALL PITS AND PIPES ARE LOCATED CLEAR FROM ANY TREE ROOT SYSTEMS.
 15. ALL STORMWATER PITS TO BE LOCATED AT LOW POINTS TO PREVENT PONDED WATER.
 16. CHARGED DOWNPIPE LINES ARE TO BE 100MM SEWER GRADE UPVC AND SEALED FROM 300MM BELOW THE TOP OF THE DOWNPIPE.





POSTDEVELOPMENT CATCHMENT PLAN (1 OF 2)
SCALE 1:100

LEGEND PROPOSED	
DP 31532	BOUNDARY LINE
	LOT 2 IMPERVIOUS AREA - 329.86m ²
	LOT 2 PERVIOUS AREA - 220.610m ²
	LOT 1 IMPERVIOUS AREA - 269.162m ²
	LOT 1 PERVIOUS AREA - 473.392m ²
	LOT 1 EXISTING DRAINAGE - 539.269m ²
	LOT 1 AND LOT 2 OMITTED AREA - 512.028m ²

POSTDEVELOPMENT CATCHMENT PLAN


A1, 1:100 SW03




NORTHERN BEACHES WATER MANAGEMENT FOR DEVELOPMENT POLICY
ASSUMED DRAINAGE FOR EXISTING HOUSES IS ADEQUATE.
FRONT PORTION OF LOT 1 AND 2 HAVE BEEN OMITTED FROM DRAINS CALCULATION DUE
TO LIMITATION OF THE SITE WHERE RAINWATER CANNOT BE CAPTURED
PIT HEIGHT WILL BE DETERMINED AFTER DRIVEWAY LEVEL HAVE BEEN PROVIDED

POSTDEVELOPMENT CATCHMENT PLAN

A1, 1:100 SW04




- NOTES:
1. ALL WORK IS TO BE CARRIED OUT IN ACCORDANCE WITH NORTHERN BEACHES COUNCIL'S DCP, AS3500.3 STORMWATER DRAINAGE.
 2. THE CONTRACTOR IS TO LOCATE AND LEVEL ALL EXISTING SERVICES PRIOR TO THE COMMENCEMENT OF CONSTRUCTION, WHETHER INDICATED ON THE PLANS OR NOT, AND MAKE ARRANGEMENTS WITH THE RELEVANT AUTHORITY TO RELOCATE OR ADJUST IF NECESSARY. ANY DAMAGE TO EXISTING SERVICES SHALL BE RECTIFIED AT THE CONTRACTORS EXPENSE.
 3. THE CONTRACTOR IS NOT TO ENTER UPON NOR DO ANY WORK WITHIN ADJOINING LANDS WITHOUT THE PERMISSION OF THE SUPERINTENDENT.
 4. THE CONTRACTOR SHALL EFFECT TEMPORARY DRAINAGE MEASURES TO AVOID LOCALISED PONDING OF SURFACE RUN-OFF.
 5. ALL NEW WORKS TO MAKE SMOOTH CONNECTION TO EXISTING CONDITIONS.
 6. THE CONTRACTOR IS TO MAINTAIN SERVICES AND ALL WEATHER ACCESS AT ALL TIMES TO ADJOINING PROPERTIES.
 7. ALL DRAINAGE ELEMENTS ARE SHOWN DIAGRAMATICALLY BASED ON AVAILABLE DRAWINGS, TO BE INSTALLED WITH CONSIDERATION TO SITE CONSTRAINTS AND THE INTENT OF THE DRAINAGE CONCEPT.
 8. ALL DOWNPIPES ARE SHOWN DIAGRAMATICALLY, POSITIONS ARE TO BE CONFIRMED ON SITE USING THE WORKING DRAWINGS.
 9. THE CONTRACTOR IS TO LOCATE AND LEVEL ALL EXISTING DRAINAGE PITS AND PIPES PRIOR TO THE COMMENCEMENT OF CONSTRUCTION AND THE CONSTRUCTION IS TO COMMENCE FROM THE DOWNSTREAM PIT AND STRUCTURES.
 10. ALL DOWNPIPES ARE TO BE MINIMUM 90mm uPVC OR 100mm x 75mm U.N.O.
 11. ALL DOWNPIPES TO BE PROVIDED WITH CLEANING EYES.
 12. ALL STORMWATER PIPES ARE TO BE MINIMUM 100mm uPVC ON 1% MINIMUM GRADE U.N.O. AND TO HAVE MIN 100mm COVER.
 13. ALL GUTTERS TO BE INSTALLED WITH GUTTER GUARDS UNLESS NOTED OTHERWISE.
 14. ENSURE THAT ALL PITS AND PIPES ARE LOCATED CLEAR FROM ANY TREE ROOT SYSTEMS.
 15. ALL STORMWATER PITS TO BE LOCATED AT LOW POINTS TO PREVENT PONDED WATER.
 16. CHARGED DOWNPIPE LINES ARE TO BE 100MM SEWER GRADE UPVC AND SEALED FROM 300MM BELOW THE TOP OF THE DOWNPIPE.



STORMWATER PLAN (1 OF 2)
SCALE 1:100


STORMWATER PLAN

A1, 1:100 SW05



NOTES:

1. ALL WORK IS TO BE CARRIED OUT IN ACCORDANCE WITH NORTHERN BEACHES COUNCIL'S DCP, AS3500.3 STORMWATER DRAINAGE.
2. THE CONTRACTOR IS TO LOCATE AND LEVEL ALL EXISTING SERVICES PRIOR TO THE COMMENCEMENT OF CONSTRUCTION, WHETHER INDICATED ON THE PLANS OR NOT, AND MAKE ARRANGEMENTS WITH THE RELEVANT AUTHORITY TO RELOCATE OR ADJUST IF NECESSARY. ANY DAMAGE TO EXISTING SERVICES SHALL BE RECTIFIED AT THE CONTRACTORS EXPENSE.
3. THE CONTRACTOR IS NOT TO ENTER UPON NOR DO ANY WORK WITHIN ADJOINING LANDS WITHOUT THE PERMISSION OF THE SUPERINTENDENT.
4. THE CONTRACTOR SHALL EFFECT TEMPORARY DRAINAGE MEASURES TO AVOID LOCALISED PONDING OF SURFACE RUN-OFF.
5. ALL NEW WORKS TO MAKE SMOOTH CONNECTION TO EXISTING CONDITIONS.
6. THE CONTRACTOR IS TO MAINTAIN SERVICES AND ALL WEATHER ACCESS AT ALL TIMES TO ADJOINING PROPERTIES.
7. ALL DRAINAGE ELEMENTS ARE SHOWN DIAGRAMATICALLY BASED ON AVAILABLE DRAWINGS, TO BE INSTALLED WITH CONSIDERATION TO SITE CONSTRAINTS AND THE INTENT OF THE DRAINAGE CONCEPT.
8. ALL DOWNPIPES ARE SHOWN DIAGRAMATICALLY, POSITIONS ARE TO BE CONFIRMED ON SITE USING THE WORKING DRAWINGS.
9. THE CONTRACTOR IS TO LOCATE AND LEVEL ALL EXISTING DRAINAGE PITS AND PIPES PRIOR TO THE COMMENCEMENT OF CONSTRUCTION AND THE CONSTRUCTION IS TO COMMENCE FROM THE DOWNSTREAM PIT AND STRUCTURES.
10. ALL DOWNPIPES ARE TO BE MINIMUM 90mm uPVC OR 100mm x 75mm U.N.O.
11. ALL DOWNPIPES TO BE PROVIDED WITH CLEANING EYES.
12. ALL STORMWATER PIPES ARE TO BE MINIMUM 100mm uPVC ON 1% MINIMUM GRADE U.N.O. AND TO HAVE MIN 100mm COVER.
13. ALL GUTTERS TO BE INSTALLED WITH GUTTER GUARDS UNLESS NOTED OTHERWISE.
14. ENSURE THAT ALL PITS AND PIPES ARE LOCATED CLEAR FROM ANY TREE ROOT SYSTEMS.
15. ALL STORMWATER PITS TO BE LOCATED AT LOW POINTS TO PREVENT PONDED WATER.
16. CHARGED DOWNPIPE LINES ARE TO BE 100MM SEWER GRADE UPVC AND SEALED FROM 300MM BELOW THE TOP OF THE DOWNPIPE.




ON-SITE DETENTION TANK SECTION

SCALE: NTS


OSD TANK NOTES:

1. REFER TO SW05 AND SW06 FOR CRITICAL LEVELS
2. INSTALL TO MANUFACTURES INSTRUCTION



DISPERSAL TRENCH

SCALE: NTS




ORIFICE DIAMETER = 60mm FOR
10500L OSD TANK
ORIFICE DIAMETER = 98mm FOR
22500L OSD TANK
CIRCULAR HOLE WITH SHARP
EDGES TO 0.5mm ACCURACY

PIPE BEYOND
PIT WALL
EPOXY PLATE TO WALL
AND INTALL 4M12
MASONRY ANCHORS

ORIFICE PLATE DETAIL

SCALE 1:10




TRASH SCREEN DETAIL

N.T.S.

TRASH SCREEN NOTES:

1. MAXIMESH SCREENS MUST BE PLACED SUCH THAT THE LONGAXIS OF THE OVAL SHAPED HOLES ARE ORIENTATED HORIZONTALLY WITH THE PORTRUDING LIP ANGLED UPWARDS AND FACING TOWARDS THE OUTLET.
2. THE SCREEN IS TO BE FORMED BY WELDING TWO TRIANGULAR MAXIMESH (OR EQUIVALENT) PANELS TO A RECTANGULAR FRONT MAXIMESH PANEL (OR EQUIVALENT).



TYPICAL PIT

N.T.S.