

BASIX[®]Certificate

Building Sustainability Index www.basix.nsw.gov.au

Single Dwelling

Certificate number: 1100574S_05

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.basix.nsw.gov.au

This certificate is a revision of certificate number 1100574S_04 lodged with the consent authority or certifier on 28 January 2021 with application DA2020/1772.

It is the responsibility of the applicant to verify with the consent authority that the original, or any revised certificate, complies with the requirements of Schedule 1 Clause 2A, 4A or 6A of the Environmental Planning and Assessment Regulation 2000

Secretary

Date of issue: Sunday, 21 March 2021

To be valid, this certificate must be lodged within 3 months of the date of issue.



Planning,
Industry &
Environment

Project summary

Project name	0651_9 WANDEEN RD, CLAREVILLE_05
Street address	9 WANDEEN Road CLAREVILLE 2107
Local Government Area	Northern Beaches Council
Plan type and plan number	deposited 393629
Lot no.	A
Section no.	-
Project type	separate dwelling house
No. of bedrooms	4

Project score

Water	✓ 40	Target 40
Thermal Comfort	✓ Pass	Target Pass
Energy	✓ 56	Target 50

Certificate Prepared by

Name / Company Name: Action Plans

ABN (if applicable): 17118297587

Description of project

Project address

Project name	0651_9 WANDEEN RD, CLAREVILLE_05
Street address	9 WANDEEN Road CLAREVILLE 2107
Local Government Area	Northern Beaches Council
Plan type and plan number	Deposited Plan 393629
Lot no.	A
Section no.	-

Project type

Project type	separate dwelling house
No. of bedrooms	4

Site details

Site area (m ²)	698
Roof area (m ²)	154
Conditioned floor area (m2)	287.88
Unconditioned floor area (m2)	20.04
Total area of garden and lawn (m2)	379

Assessor details and thermal loads

Assessor number	n/a
Certificate number	n/a
Climate zone	n/a
Area adjusted cooling load (MJ/m ² .year)	n/a
Area adjusted heating load (MJ/m ² .year)	n/a
Ceiling fan in at least one bedroom	n/a
Ceiling fan in at least one living room or other conditioned area	n/a

Project score

Water	✓ 40	Target 40
Thermal Comfort	✓ Pass	Target Pass
Energy	✓ 56	Target 50

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Landscape			
The applicant must plant indigenous or low water use species of vegetation throughout 150 square metres of the site.	✓	✓	
Fixtures			
The applicant must install showerheads with a minimum rating of 4 star (> 4.5 but ≤ 6 L/min plus spray force and/or coverage tests) in all showers in the development.		✓	✓
The applicant must install a toilet flushing system with a minimum rating of 5 star in each toilet in the development.		✓	✓
The applicant must install taps with a minimum rating of 5 star in the kitchen in the development.		✓	
The applicant must install basin taps with a minimum rating of 5 star in each bathroom in the development.		✓	
Alternative water			
Rainwater tank			
The applicant must install a rainwater tank of at least 6000 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	✓	✓	✓
The applicant must configure the rainwater tank to collect rain runoff from at least 153.94 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam).		✓	✓
The applicant must connect the rainwater tank to: <ul style="list-style-type: none"> at least one outdoor tap in the development (Note: NSW Health does not recommend that rainwater be used for human consumption in areas with potable water supply.) a tap that is located within 10 metres of the swimming pool in the development 		✓ ✓	✓ ✓
Swimming pool			
The swimming pool must not have a volume greater than 13.5 kilolitres.	✓	✓	

Water Commitments

The swimming pool must be outdoors.

Show on
DA plans

Show on CC/CDC
plans & specs

Certifier
check



Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
General features			
The dwelling must not have more than 2 storeys.	✓	✓	✓
The conditioned floor area of the dwelling must not exceed 300 square metres.	✓	✓	✓
The dwelling must not contain open mezzanine area exceeding 25 square metres.	✓	✓	✓
The dwelling must not contain third level habitable attic room.	✓	✓	✓
Floor, walls and ceiling/roof			
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	✓	✓	✓

Construction	Additional insulation required (R-Value)	Other specifications
floor - concrete slab on ground, 107.49 square metres	nil	
floor - above habitable rooms or mezzanine, 141.43 square metres, concrete	nil	
floor - suspended floor above garage, concrete	nil	
external wall - concrete block/plasterboard	1.88 (or 2.40 including construction)	
external wall - framed (weatherboard, fibre cement, metal clad)	2.00 (or 2.40 including construction)	
ceiling and roof - flat ceiling / flat roof, framed	ceiling: 3.5 (up), roof: foil backed blanket (75 mm)	framed; light (solar absorptance < 0.475)

Note	• Insulation specified in this Certificate must be installed in accordance with Part 3.12.1.1 of the Building Code of Australia.
Note	• In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Windows, glazed doors and skylights			
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each window and glazed door.	✓	✓	✓
The dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table.	✓	✓	✓
<p>The following requirements must also be satisfied in relation to each window and glazed door:</p> <ul style="list-style-type: none"> For the following glass and frame types, the certifier check can be performed by visual inspection. <ul style="list-style-type: none"> Aluminium single clear Aluminium double (air) clear Timber/uPVC/fibreglass single clear Timber/uPVC/fibreglass double (air) clear For other glass or frame types, each window and glazed door must be accompanied with certification showing a U value no greater than that listed and a Solar Heat Gain Coefficient (SHGC) within the range of those listed. Total system U values and SHGC must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions. Frame and glass types shown in the table below are for reference only. Overshadowing buildings/vegetation must be of the height and distance from the centre and the base of the window and glazed door, as specified in the 'overshadowing' column. 	✓	✓	✓ ✓ ✓
The applicant must install the skylights described in the table below, in accordance with the specifications listed in the table. Total skylight area must not exceed 3 square metres (the 3 square metre limit does not include the optional additional skylight of less than 0.7 square metres that does not have to be listed in the table).	✓	✓	✓

Skylight no.	Maximum area (square metres)	Type	Shading device
S01	1.34	aluminium, moulded plastic single clear	no shading
S02	1.34	aluminium, moulded plastic single clear	no shading

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Type	Shading Device (Dimension within 10%)	Overshadowing
North facing					

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Type	Shading Device (Dimension within 10%)	Overshadowing
D04	2400	1500	aluminium, single, clear	solid overhang 1800 mm, 300 mm above head of window or glazed door	not overshadowed
W11	2000	1800	aluminium, single, clear	eave 250 mm, 800 mm above head of window or glazed door	>4 m high, 2-5 m away
D05	2400	1500	aluminium, single, clear	solid overhang 1800 mm, 300 mm above head of window or glazed door	not overshadowed
D06	2400	1500	aluminium, single, clear	solid overhang 1800 mm, 300 mm above head of window or glazed door	>4 m high, 2-5 m away
D07	2400	1500	aluminium, single, clear	solid overhang 1800 mm, 300 mm above head of window or glazed door	>4 m high, 2-5 m away
W10	2000	3400	U-value: 4.9, SHGC: 0.297 - 0.363 (aluminium, double (air), Lo-Tsol Low-e/clear)	eave 250 mm, 800 mm above head of window or glazed door	not overshadowed
W09	3000	2200	U-value: 4.9, SHGC: 0.297 - 0.363 (aluminium, double (air), Lo-Tsol Low-e/clear)	eave 250 mm, 800 mm above head of window or glazed door	not overshadowed
D10	3000	4200	U-value: 3.1, SHGC: 0.351 - 0.429 (aluminium: thermally broken, double (air), Hi-Tsol Low-e/clear)	eave 250 mm, 800 mm above head of window or glazed door	>4 m high, 2-5 m away
East facing					
W01	1500	2400	U-value: 3.1, SHGC: 0.243 - 0.297 (aluminium: thermally broken, double (air), Lo-Tsol Low-e/clear)	eave 250 mm, 4100 mm above head of window or glazed door	>4 m high, 5-8 m away
W12	1800	900	aluminium, single, clear	eave 250 mm, 1000 mm above head of window or glazed door	>4 m high, 5-8 m away
South facing					
W14	3000	3000	U-value: 3.1, SHGC: 0.243 - 0.297 (aluminium: thermally broken, double (air), Lo-Tsol Low-e/clear)	eave 600 mm, 780 mm above head of window or glazed door	not overshadowed


Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Type	Shading Device (Dimension within 10%)	Overshadowing
W02	900	1400	aluminium, single, clear	eave 600 mm, 3700 mm above head of window or glazed door	not overshadowed
W05	2400	2000	U-value: 3.1, SHGC: 0.441 - 0.539 (aluminium: thermally broken, double (air), Hi-Tsol Low-e/clear)	none	not overshadowed
W13	1200	2400	aluminium, single, clear	eave 600 mm, 780 mm above head of window or glazed door	not overshadowed
W03	2400	1000	aluminium, single, clear	solid overhang 1200 mm, 300 mm above head of window or glazed door	not overshadowed
D02	2400	3100	aluminium, single, clear	eave 600 mm, 3700 mm above head of window or glazed door	>4 m high, 2-5 m away
W04	600	2100	aluminium, single, clear	none	not overshadowed
West facing					
D09	3000	3415	U-value: 2.3, SHGC: 0.171 - 0.209 (timber/UPVC/fibreglass, double (air), Lo-Tsol Low-e/clear)	eave 250 mm, 850 mm above head of window or glazed door	>4 m high, 8-12 m away
D08	3000	3415	U-value: 2.3, SHGC: 0.171 - 0.209 (timber/UPVC/fibreglass, double (air), Lo-Tsol Low-e/clear)	eave 250 mm, 850 mm above head of window or glazed door	>4 m high, 8-12 m away
W07	2400	2400	U-value: 3.1, SHGC: 0.243 - 0.297 (aluminium: thermally broken, double (air), Lo-Tsol Low-e/clear)	none	>4 m high, 2-5 m away
W08	600	1200	aluminium, single, clear	none	>4 m high, 2-5 m away
W06	600	1200	aluminium, single, clear	none	>4 m high, 2-5 m away


Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Hot water			
The applicant must install the following hot water system in the development, or a system with a higher energy rating: gas instantaneous with a performance of 5 stars.	✓	✓	✓
Cooling system			
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 living area: ceiling fans + 1-phase airconditioning; Energy rating: 5 Star (old label)		✓	✓
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 bedroom: ceiling fans + 1-phase airconditioning; Energy rating: 5 Star (old label)		✓	✓
The cooling system must provide for day/night zoning between living areas and bedrooms.		✓	✓
Heating system			
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 living area: gas fixed flued heater; Energy rating: 3 Star		✓	✓
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 bedroom: 1-phase airconditioning; Energy rating: 5 Star (old label)		✓	✓
Ventilation			
The applicant must install the following exhaust systems in the development:			
At least 1 Bathroom: individual fan, ducted to façade or roof; Operation control: manual switch on/off		✓	✓
Kitchen: individual fan, ducted to façade or roof; Operation control: manual switch on/off		✓	✓
Laundry: individual fan, ducted to façade or roof; Operation control: manual switch on/off		✓	✓
Artificial lighting			
The applicant must ensure that the "primary type of artificial lighting" is fluorescent or light emitting diode (LED) lighting in each of the following rooms, and where the word "dedicated" appears, the fittings for those lights must only be capable of accepting fluorescent or light emitting diode (LED) lamps:			
• at least 5 of the bedrooms / study; dedicated		✓	✓
• at least 2 of the living / dining rooms; dedicated		✓	✓


Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
<ul style="list-style-type: none"> the kitchen; dedicated 		✓	✓
<ul style="list-style-type: none"> all bathrooms/toilets; dedicated 		✓	✓
<ul style="list-style-type: none"> the laundry; dedicated 		✓	✓
<ul style="list-style-type: none"> all hallways; dedicated 		✓	✓
Natural lighting			
The applicant must install a window and/or skylight in the kitchen of the dwelling for natural lighting.	✓	✓	✓
The applicant must install a window and/or skylight in 7 bathroom(s)/toilet(s) in the development for natural lighting.	✓	✓	✓
Swimming pool			
The applicant must install the following heating system for the swimming pool in the development (or alternatively must not install any heating system for the swimming pool): solar only		✓	
The applicant must install a timer for the swimming pool pump in the development.		✓	
Alternative energy			
The applicant must install a photovoltaic system with the capacity to generate at least 0.75 peak kilowatts of electricity as part of the development. The applicant must connect this system to the development's electrical system.	✓	✓	✓
Other			
The applicant must install a gas cooktop & electric oven in the kitchen of the dwelling.		✓	
The applicant must construct each refrigerator space in the development so that it is "well ventilated", as defined in the BASIX definitions.		✓	
The applicant must install a fixed outdoor clothes drying line as part of the development.		✓	
The applicant must install a fixed indoor or sheltered clothes drying line as part of the development.		✓	

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a  in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a  in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a  in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate (either interim or final) for the development may be issued.