

ASSESSMENT DETAILS			
Assessor Name	Padraig Healy		
Direct number	0498 051 209		
Office number	(02) 9281 8555		
AAO	ABSA		
Assessor Number	101026		
Project name	240231 - 618 Barrenjoey Road, Avalon		
Software	BERSPro – v5.1.9 (3.23)		
Date of assessment	22/08/2024		
BASIX Certificate Number	1761168S_03		
NatHERS Certificate Number	0009706136		
Client Name	Cristina Gomes		
Client Phone	0447 541 081		
Client Email	contact@cristinagomes.com		

NCC COMPLIANCE

Building compliance is required to comply as applicable with the 'New South Wales Additions' in the NCC 2022 Energy Efficiency

Concrete slab on ground with an in-slab or in-screed heating or cooling system must have insulation installed in accordance with Part NSWJ3D10 Building fabric in accordance with J3D5, J3D6 and J3D10

Thermal construction is to be built in accordance with Part J4D3

Any roof lights, windows, doors, and exhaust fans are sealed in accordance with Part J5D2 to J5D8

Any new air-conditioning system is installed in accordance with Part J6D3

Any new mechanical ventilation system is installed in accordance with Part J6D4

Any new miscellaneous exhaust system is installed in accordance with Part J6D5

Any new heated hot water system is installed in accordance with Part J8D2

Any new energy monitoring equipment is installed in accordance with Part J9D3 Electrical Distribution boards dedicated to EV Charging are to be installed in accordance with Part J9D4

Switchboards of a building dedicated to PV systems and battery systems are to be installed in accordance with Part J9D5

WATER				
Refer to BASIX Report for further information	Landscape	Area of lawn	Indigenous/low water use species	
		163m2		75m2
	Fixtures	Showerheads	Toilets	Taps
		4 star (4.5 -6L/min)	4 star	6 star
	Appliances	na	na na	
	Rainwater Tank	Individ	Connection	
		2kL - 88m2 roof c	Landscape irrigation	
	Pool	Volume	Pool cover	On timer/Shaded
		na	na	na
	Cna	Volume	Outdoor spa cover	Shaded
	Spa	na	na	na
SCORE			40% (Pass)	

ENERGY				
Refer to BASIX Report for further information	Hot Water System	Gas instantaneous - 4 star		
		Bathroom	No mechanical ventilation (natural ventilated)	
	Ventilation System & Control	Laundry	No mechanical ventilation (natural ventilated)	
		Kitchen	No mechanical ventilation (natural ventilated)	
	Heating System	None		
	Cooling System	None		
	Lighting	Sealed LED light throughout		
	Appliances	Gas cooktop & electric oven		
	Clothes Drying Line	Outdoor clothes drying line		
	Photovoltaic System	None		
SCORE		72% (Pass)		

Material				
Refer to BASIX Report for further information	Construction Material	Floors, Walls, Ceiling & roof, Glazing		
SCORE		No target set in BASIX (Pass)		

NCC2022 NatHERS Thermal Performance Specification - Avalon					
External Walls	Insulation	Colour	Туре	Comments	
	Additional R2.3 board insulation (50mm)	Light - SA < 0.475	EPS with timber frame + additional board insulation	Ground level	
	R2.7	Medium - SA 0.475 - 0.70	Weatherboard cladding with timber frame	Level 1	
Internal Walls		Туре		Comments	
internal wans	R2.0	Plasterboard stud with timber frame		Internally inside dwelling	
	Insulation		Туре	Comments	
Floor	None	Con	crete slab on ground	Ground floor	
	R2.0		Timber	Level 1 floor	
Floor covering	Level 1 bedrooms, hall	way, WIR: Timber Wet areas/Pantry: Tile		Kitchen, living, entry, bedroom 1: Polished concrete	
	Insulation	Туре		Comments	
Ceiling	R4.0 (215mm)	Plasterboard		Exposed ceiling of Ground level	
	R6.0 (260mm)	Plasterboard		Level 1 ceiling	
Df	Insulation	Colour	Туре	Comments	
Roof	R1.3 foil-faced blanket	Light - SA < 0.475	Metal	All roof throughout including Ground level (unvented cavity)	
Size			Location		
Celling rans	Ceiling fans Minimum 1400mm in diameter		All bedrooms + living room + media room		
	Downlight		Exhaust fan		
Ceiling penetration	Sealed LED downlights throughout* * Continuous insulation in ceiling (downlights to be IC4 rated)		Sealed exhaust fan in kitchen and all wet areas		
Glazing	U-Value	SHGC	Opening type	Comments	
	4.1 or less	0.52 (+/-5%)	Fixed, Double hung, sliding	e.g., Double glazed clear low-e Argon Aluminium frame	
	5.4 or less	0.58 (+/-5%)	Louvre windows	e.g., Single glazed low-e clear Aluminium frame	
Skylight	U-Value	SHGC	Opening type	Comments	
	Double gl	azed	Fixed	na	