# **BASIX** Certificate

Building Sustainability Index www.basix.nsw.gov.au

## **Alterations and Additions**

Certificate number: A427793

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Alterations and Additions Definitions" dated 06/10/2017 published by the Department. This document is available at www.basix.nsw.gov.au

### Secretary

Date of issue: Monday, 16, August 2021

To be valid, this certificate must be lodged within 3 months of the date of issue.



# Description of project

Project address					
Project name	20018_IL_Doran_Forestville				
Street address	10 Curraweela Street Forestville 2087				
Local Government Area	Northern Beaches Council				
Plan type and number	Deposited Plan 221367				
Lot number	13				
Section number					
Project type					
Dwelling type	Separate dwelling house				
Type of alteration and addition	My renovation work is valued at \$50,000 or more, and does not include a pool (and/or spa).				

Certificate Prepared by (please complete before submitting to Council or PCA)

Name / Company Name: Azure Project Services

ABN (if applicable): 18002159284

BASIX Certificate number: A427793 page 2 / 5

Fixtures and systems	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Lighting			
The applicant must ensure a minimum of 40% of new or altered light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting-diode (LED) lamps.		<b>✓</b>	<b>✓</b>
Fixtures			
The applicant must ensure new or altered showerheads have a flow rate no greater than 9 litres per minute or a 3 star water rating.		✓	✓
The applicant must ensure new or altered toilets have a flow rate no greater than 4 litres per average flush or a minimum 3 star water rating.		<b>✓</b>	✓
The applicant must ensure new or altered taps have a flow rate no greater than 9 litres per minute or minimum 3 star water rating.		<b>✓</b>	

BASIX Certificate number: A427793 page 3 / 5

Construction			Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Insulation requirements					
The applicant must construct the new or altered construction (floor(s), walls, and ceilings/roofs) in accordance with the specifications listed in the table below, except that a) additional insulation is not required where the area of new construction is less than 2m2, b) insulation specified is not required for parts of altered construction where insulation already exists.					<b>✓</b>
Construction	Additional insulation required (R-value)	Other specifications			
suspended floor with enclosed subfloor: framed (R0.7).	R0.60 (down) (or R1.30 including construction)				
external wall: external insulated façade system (EIFS)(façade panel: 160 mm)	nil				
flat ceiling, pitched roof	ceiling: R3.00 (up), roof: foil/sarking	medium (solar absorptance 0.475 - 0.70)			

BASIX Certificate number: A427793 page 4 / 5

Glazing red	quirements						Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Windows ar	nd glazed do	ors						'	
The applicant must install the windows, glazed doors and shading devices, in accordance with the specifications listed in the table below. Relevant overshadowing specifications must be satisfied for each window and glazed door.						<b>✓</b>	<b>✓</b>	<b>✓</b>	
The following requirements must also be satisfied in relation to each window and glazed door:						<b>✓</b>	<b>✓</b>		
Each window or glazed door with standard aluminium or timber frames and single clear or toned glass may either match the description, or, have a U-value and a Solar Heat Gain Coefficient (SHGC) no greater than that listed in the table below. Total system U-values and SHGCs must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions.							✓	<b>✓</b>	
For projections described as a ratio, the ratio of the projection from the wall to the height above the window or glazed door sill must be at least that shown in the table below.						<b>✓</b>	<b>✓</b>	✓	
Windows a	and glazed o	doors g	lazing r	equiremer	nts				
Window / doo	or Orientation	Area of glass inc. frame (m2)	Oversha Height (m)	Distance (m)	Shading device	Frame and glass type			
W1	W	1.44	0	0	projection/height above sill ratio >=0.43	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
W2	S	1.44	0	0	projection/height above sill ratio >=0.43	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
W3	W	1.89	0	0	projection/height above sill ratio >=0.36	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
W4	S	1.08	0	0	projection/height above sill ratio >=0.43	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			
W5	S	0.9	0	0	projection/height above sill ratio >=0.43	timber or uPVC, single clear, (or U-value: 5.71, SHGC: 0.66)			

BASIX Certificate number: A427793 page 5 / 5

### Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a " " in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a "

"" in the "Show on CC/CDC plans & specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a "

"" in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate for the development may be issued.